

Declaration of performance

*according to Annex III of Regulation (EU) No 305/2011
amended by Delegated Regulation (EU) No. 574/2014*

Epoxy Adhesive Mortar EKY 91

No. AT012/01

Seite 1 von 2

1. **Unique identification code of the product type:**
EN 12004:2007+A1:2012 – R2 T – Epoxy Adhesive Mortar EKY 91
2. **Intended use:**
Reaction resin adhesive for increased performance requirements with reduced slip, for interior and exterior use
3. **Manufacturer:**
Murexin GmbH, Franz von Furtenbachstrasse 1, A-2700 Wiener Neustadt, Austria
4. **Authorised representative**
Not relevant
5. **Systems for assessing and verifying performance constancy:**
System 3
6. **Harmonised standard:**
EN 12004:2007+A1:2012
7. **Notified body:**
Smart Minerals GmbH, identification number: 0997
8. **European Assessment Document/ European Technical Assessment:**
Not relevant



qualityaustria
SYSTEMZERTIFIZIERT
ISO 9001:2015
ISO 14001:2015

Zertifizierter Netzwerkpartner der

LEITBETRIEBE AUSTRIA
NR. 007781
www.leitbetriebe.at

Murexin GmbH | Franz von Furtenbach Strasse 1 | 2700 Wiener Neustadt | Austria | Tel.: +43 2622 27401-0
Fax: +43 2622 27401-173 | info@murexin.com | murexin.com

Commercial Register Court: Wiener Neustadt Regional Court, Commercial Register Number: FN 121116 m - UID No.: ATU 14257908, ARA No.: 568, DVR No.: 0047279
Legal form of the company: Limited liability company, registered office: Wiener Neustadt, Austria

Das hält.

Declaration of performance

according to Annex III of Regulation (EU) No 305/2011
amended by Delegated Regulation (EU) No. 574/2014

Epoxy Adhesive Mortar EKY 91

No. AT012/01

Seite 2 von 2

9. Declaration of performance:

Main features	Performance	Harmonised technical specification
Reaction to fire	F	EN 12004:2007 +A1:2012
Adhesion strength (shear tensile strength) after dry storage	$\geq 2.0 \text{ N/mm}^2$	
Adhesion strength (shear tensile strength) after water immersion	$\geq 2.0 \text{ N/mm}^2$	
Adhesion strength (shear tensile strength) after thermal shock	$\geq 2.0 \text{ N/mm}^2$	
Slip	$\leq 0.5 \text{ mm}$	
Open time (tensile adhesion strength)	$\geq 0.5 \text{ N/mm}^2$ after at least 20 min	
Release of hazardous substances	see safety data sheet	

10. The performance of the above product is as declared

The manufacturer named above is solely responsible for drawing up the declaration of performance in accordance with Regulation (EU) No 305/2011.

Signed for and on behalf of the manufacturer by:



Bernhard Mucherl

Management



Alexander Rauch

Product Management

Wiener Neustadt, on 15/10/2024



Zertifizierter Netzwerkpartner der



Murexin GmbH | Franz von Furtenbach Strasse 1 | 2700 Wiener Neustadt | Austria | Tel.: +43 2622 27401-0

Fax: +43 2622 27401-173 | info@murexin.com | murexin.com

Commercial Register Court: Wiener Neustadt Regional Court, Commercial Register Number: FN 121116 m - UID No.: ATU 14257908, ARA No.: 568, DVR No.: 0047279
Legal form of the company: Limited liability company, registered office: Wiener Neustadt, Austria

Das hält.