

Declaration of performance

*according to Annex III of Regulation (EU) No 305/2011
amended by Delegated Regulation (EU) No. 574/2014*

Flex Adhesive Mortar Trass KTF 55

No. AT085/01

Seite 1 von 2

- 1. Unique identification code of the product type:**
EN 12004:2007+A1:2012 – C2 T S1 – Flex Adhesive Mortar Trass KTF 55
- 2. Intended use:**
Deformable cementitious mortar for increased requirements with reduced slippage for interior and exterior tiling and panel work
- 3. Manufacturer:**
Murexin GmbH, Franz von Furtenbachstrasse 1, A-2700 Wiener Neustadt, Austria
- 4. Authorised representative**
Not relevant
- 5. Systems for assessing and verifying performance constancy:**
System 3
System 4 for fire behaviour
- 6. Harmonised standard:**
EN 12004:2007+A1:2012
Fire behaviour EN 13501-1
- 7. Notified body:**
Smart Minerals GmbH, identification number: 0997
Magistrat der Stadt Wien, identification number: 1139
- 8. European Assessment Document/ European Technical Assessment:**
Not relevant



qualityaustria
Zertifiziert nach
ISO 9001:2015
ISO 14001:2015
NR. 007781
NR. 002410

Zertifizierter Netzwerkpartner der
LEITBETRIEBE AUSTRIA
www.leitbetriebe.at

Murexin GmbH | Franz von Furtenbach Strasse 1 | 2700 Wiener Neustadt | Austria | Tel.: +43 2622 27401-0
Fax: +43 2622 27401-173 | info@murexin.com | murexin.com

Commercial Register Court: Wiener Neustadt Regional Court, Commercial Register Number: FN 121116 m - UID No.: ATU 14257908, ARA No.: 568, DVR No.: 0047279
Legal form of the company: Limited liability company, registered office: Wiener Neustadt, Austria

Das hält.

Declaration of performance

according to Annex III of Regulation (EU) No 305/2011
amended by Delegated Regulation (EU) No. 574/2014

Flex Adhesive Mortar Trass KTF 55 No. AT085/01

Seite 2 von 2

9. Declaration of performance:

Main features	Performance	Harmonised technical specification
Fire behaviour	A1	EN 12004:2007 +A1:2012
Adhesive tensile strength after dry storage	$\geq 1.0 \text{ N/mm}^2$	
Adhesive tensile strength after water storage	$\geq 1.0 \text{ N/mm}^2$	
Adhesive tensile strength after warm storage	$\geq 1.0 \text{ N/mm}^2$	
Adhesive tensile strength after freeze-thaw cycle storage	$\geq 1.0 \text{ N/mm}^2$	
Open time: adhesive tensile strength	$\geq 0.5 \text{ N/mm}^2$ after at least 20 min	
Slippage	$\leq 0.5 \text{ mm}$	
Deformable mortar: deflection	$\geq 2.5 \text{ mm}$ and $\leq 5 \text{ mm}$	
Release of hazardous substances	see safety data sheet	

10. The performance of the above product is as declared


The manufacturer named above is solely responsible for drawing up the declaration of performance in accordance with Regulation (EU) No 305/2011.

Signed for and on behalf of the manufacturer by:



Bernhard Mucherl

Management



Alexander Rauch

Product Management

Wiener Neustadt, on 27/03/2024



Zertifizierter Netzwerkpartner der



Murexin GmbH | Franz von Furtenbach Strasse 1 | 2700 Wiener Neustadt | Austria | Tel.: +43 2622 27401-0
Fax: +43 2622 27401-173 | info@murexin.com | murexin.com

Commercial Register Court: Wiener Neustadt Regional Court, Commercial Register Number: FN 121116 m - UID No.: ATU 14257908, ARA No.: 568, DVR No.: 0047279
Legal form of the company: Limited liability company, registered office: Wiener Neustadt, Austria

Das hält.