

Declaration of performance

according to Annex III of Regulation (EU) No 305/2011
amended by Delegated Regulation (EU) No. 574/2014

Supraflex SFR 89 Rapid
No. AT351/02

Page 1 of 2

1. **Unique identification code of the product type:**
EN 12004:2007+A1:2012 – C2 FE S2 – Supraflex SFR 89 Rapid
2. **Intended use:**
Highly deformable, fast-setting cementitious mortar for increased requirements and extended open time for tile, slab, and mosaic installation work
3. **Manufacturer:**
Murexin GmbH, Franz von Furtenbachstrasse 1, A-2700 Wiener Neustadt, Austria
4. **Authorised representative**
Not relevant
5. **Systems for assessing and verifying performance constancy:**
System 3
System 3 for reaction to fire
6. **Harmonised standard:**
EN 12004:2007+A1:2012
7. **Notified body:**
Smart Minerals GmbH, identification number: 0997
Municipal Department of the City of Vienna, identification number: 1139
8. **European Assessment Document/ European Technical Assessment:**
Not relevant



qualityaustria
SYSTEMZERTIFIZIERT
ISO 9001:2015
ISO 14001:2015
NR.007761

Zertifizierter Netzwerkpartner der
LEITBETRIEBE AUSTRIA
www.leitbetriebe.at

Murexin GmbH | Franz von Furtenbach Strasse 1 | 2700 Wiener Neustadt | Austria | Tel.: +43 2622 27401-0
Fax: +43 2622 27401-173 | info@murexin.com | murexin.com

Commercial Register Court: Wiener Neustadt Regional Court, Commercial Register Number: FN 121116 m - UID No.: ATU 14257908, ARA No.: 568, DVR No.: 0047279
Legal form of the company: Limited liability company, registered office: Wiener Neustadt, Austria

Das hält.

Declaration of performance

according to Annex III of Regulation (EU) No 305/2011
amended by Delegated Regulation (EU) No. 574/2014

Supraflex SFR 89 Rapid
No. AT351/02

Page 2 of 2

9. Declaration of performance:

Main features	Performance	Harmonised technical specification
Reaction to fire	A2 – s1, d0	EN 12004:2007 +A1:2012
Adhesive tensile strength after dry storage	$\geq 1.0 \text{ N/mm}^2$	
Adhesive tensile strength after water storage	$\geq 1.0 \text{ N/mm}^2$	
Adhesive tensile strength after warm storage	$\geq 1.0 \text{ N/mm}^2$	
Adhesive tensile strength after freeze-thaw cycle storage	$\geq 1.0 \text{ N/mm}^2$	
Early adhesive tensile strength	$\geq 0.5 \text{ N/mm}^2$ after 6 h at the latest	
Open time: adhesive tensile strength	$\geq 0.5 \text{ N/mm}^2$ after at least 30 min	
Highly deformable mortar: deflection	$\geq 5 \text{ mm}$	
Release of hazardous substances	see safety data sheet	


10. The performance of the above product is as declared

The manufacturer named above is solely responsible for drawing up the declaration of performance in accordance with Regulation (EU) No 305/2011.

Signed for and on behalf of the manufacturer by:



Bernhard Mucherl



Alexander Rauch

Management

Product Management

Wiener Neustadt, on 19/01/2026



qualityaustria
SYSTEMZERTIFIZIERT
ISO 9001:2015
ISO 14001:2015
NR.0027761
NR.0026410

Zertifizierter Netzwerkpartner der
LEITBETRIEBE AUSTRIA
www.leitbetriebe.at

Murexin GmbH | Franz von Furtenbach Strasse 1 | 2700 Wiener Neustadt | Austria | Tel.: +43 2622 27401-0
Fax: +43 2622 27401-173 | info@murexin.com | murexin.com

Commercial Register Court: Wiener Neustadt Regional Court, Commercial Register Number: FN 121116 m - UID No.: ATU 14257908, ARA No.: 568, DVR No.: 0047279
Legal form of the company: Limited liability company, registered office: Wiener Neustadt, Austria

Das hält.