

# Declaration of performance

according to Annex III of Regulation (EU) No 305/2011  
amended by Delegated Regulation (EU) No. 574/2014

**MureFlex MFK 45 Flexible Tile Adhesive**  
No. AT008/02

Page 1 of 2

1. **Unique identification code of the product type:**  
AT008/02
2. **Intended use:**  
Deformable cementitious mortar for increased requirements with reduced slippage and extended open time for interior and exterior tiling and panel work
3. **Manufacturer:**  
Murexin GmbH, Franz von Furtenbachstrasse 1, A-2700 Wiener Neustadt, Austria
4. **Authorised representative**  
Not relevant
5. **Systems for assessing and verifying performance constancy:**  
System 3  
System 3 for reaction to fire
6. **Harmonised standard:**  
EN 12004:2007+A1:2012  
Reaction to fire EN 13501-1
7. **Notified body:**  
Technische Universität Wien, identification number: 1746  
Magistrat der Stadt Wien, identification number: 1139
8. **European Assessment Document/ European Technical Assessment:**  
Not relevant



Zertifizierter Netzwerkpartner der



Murexin GmbH | Franz von Furtenbach Strasse 1 | 2700 Wiener Neustadt | Austria | Tel.: +43 2622 27401-0  
Fax: +43 2622 27401-173 | info@murexin.com | murexin.com

Commercial Register Court: Wiener Neustadt Regional Court, Commercial Register Number: FN 121116 m - UID No.: ATU 14257908, ARA No.: 568, DVR No.: 0047279  
Legal form of the company: Limited liability company, registered office: Wiener Neustadt, Austria

**Das hält.**

# Declaration of performance

according to Annex III of Regulation (EU) No 305/2011  
amended by Delegated Regulation (EU) No. 574/2014

**MureFlex MFK 45 Flexible Tile Adhesive**  
No. AT008/02

**9. Declaration of performance:**

Main features	Performance	Harmonised technical specification
Reaction to fire	A2-s1, d0	EN 12004:2007 +A1:2012
Adhesive tensile strength after dry storage	≥ 1.0 N/mm <sup>2</sup>	
Adhesive tensile strength after water storage	≥ 1.0 N/mm <sup>2</sup>	
Adhesive tensile strength after warm storage	≥ 1.0 N/mm <sup>2</sup>	
Adhesive tensile strength after freeze-thaw cycle storage	≥ 1.0 N/mm <sup>2</sup>	
Extended open time: adhesive tensile strength	≥ 0.5 N/mm <sup>2</sup> after at least 30 min	
Slippage	≤ 0.5 mm	
Deformable mortar: deflection	≥ 2.5 mm and ≤ 5 mm	
Release of hazardous substances	see safety data sheet	

**10. The performance of the above product is as declared**

The manufacturer named above is solely responsible for drawing up the declaration of performance in accordance with Regulation (EU) No 305/2011.

Signed for and on behalf of the manufacturer by:



Bernhard Mucherl

Management



Alexander Rauch

Product Management

Wiener Neustadt, on 03/02/2026



Zertifizierter Netzwerkpartner der



Murexin GmbH | Franz von Furtenbach Strasse 1 | 2700 Wiener Neustadt | Austria | Tel.: +43 2622 27401-0  
Fax: +43 2622 27401-173 | info@murexin.com | murexin.com

Commercial Register Court: Wiener Neustadt Regional Court, Commercial Register Number: FN 121116 m - UID No.: ATU 14257908, ARA No.: 568, DVR No.: 0047279  
Legal form of the company: Limited liability company, registered office: Wiener Neustadt, Austria

**Das hält.**