Revision: 16.09.2021

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.09.2021

Version number 6 (replaces version 4)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name AQUA SEALING AS 1500 KOMP B
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Epoxy resin
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

MUREXIN GmbH

Franz v. Furtenbachstr. 1 A-2700 Wiener Neustadt

Tel.: +43 (0)2622/27401

- · Informing department: chemikalieninfo@murexin.com
- · 1.4 Emergency telephone number:

UK National poisons Emergency number.: +44 (0) 870 600 6266

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



health hazard

Muta. 2

H341 Suspected of causing genetic defects.



environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Irrit. 2

H315 Causes skin irritation.

Eye Irrit. 2

H319 Causes serious eye irritation.

Skin Sens. 1

H317 May cause an allergic skin reaction.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS07 GHS08 GHS09

- · Signal word Warning
- · Hazard-determining components of labelling:

2,3-epoxypropyl o-tolyl ether

bis[4-(2,3-epoxypropoxy)phenyl]propane

· Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H341 Suspected of causing genetic defects.

H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 2)

Printing date 16.09.2021 Version number 6 (replaces version 4) Revision: 16.09.2021

Trade name AQUA SEALING AS 1500 KOMP B

(Contd. of page 1)

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.
P261 Avoid breathing mist/vapours/spray.
P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Additional information:

Contains epoxy constituents. May produce an allergic reaction.

- 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture consisting of the following components with harmless additives.

· Dangerous components:		
CAS: 2210-79-9 EINECS: 218-645-3	2,3-epoxypropyl o-tolyl ether Muta. 2, H341 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; Skin Sens. 1, H317	50-100%
CAS: 1675-54-3 EINECS: 216-823-5	bis[4-(2,3-epoxypropoxy)phenyl]propane Aquatic Chronic 2, H411 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 EUH205 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 %	25-50%

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information Instantly remove any clothing soiled by the product.
- · After inhalation

Take affected persons into the open air and position comfortably

Seek medical treatment in case of complaints.

· After skin contact

If skin irritation continues, consult a doctor.

Instantly wash with water and soap and rinse thoroughly.

· After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

· After swallowing

Do not induce vomiting; instantly call for medical help.

Rinse out mouth and then drink plenty of water.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 3)

Printing date 16.09.2021 Vers

Version number 6 (replaces version 4)

Trade name AQUA SEALING AS 1500 KOMP B

(Contd. of page 2)

Revision: 16.09.2021

· 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents

Use fire fighting measures that suit the environment.

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

- · For safety reasons unsuitable extinguishing agents Water with a full water jet.
- · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- · 5.3 Advice for firefighters
- Protective equipment:

Wear self-contained breathing apparatus.

Do not inhale explosion gases or combustion gases.

· Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective clothing.

6.2 Environmental precautions:

Do not allow product to reach sewage system or water bodies.

Inform respective authorities in case product reaches water or sewage system.

Do not allow to enter the ground/soil.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep containers tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Store in cool, dry place in tightly closed containers.

Keep away from heat and direct sunlight.

- Information about protection against explosions and fires: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- Requirements to be met by storerooms and containers:

Store only in the original container.

Provide floor trough without outlet.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Protect from frost.

Keep container tightly sealed.

· Storage class 10

(Contd. on page 4)

Printing date 16.09.2021 Version number 6 (replaces version 4) Revision: 16.09.2021

Trade name AQUA SEALING AS 1500 KOMP B

(Contd. of page 3)

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Components with critical values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the compilation were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures

The usual precautionary measures should be adhered to in handling the chemicals.

Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.

Filter AX.

- · Hand protection Protective gloves.
- Material of gloves

Butyl rubber, BR

Nitrile rubber, NBR

Fluorocarbon rubber (Viton)

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Not suitable are gloves made of the following materials:

Strong gloves

Leather gloves

- · Eye/face protection Tightly sealed safety glasses.
- · Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour: Yellowish · Smell: Aromatic

· Boiling point or initial boiling point and

boiling range >200 °C

· Lower and upper explosion limit

· Lower: Not determined.
Upper: Not determined.

Flash point: 113 °C

· **Self-inflammability:** Product is not selfigniting.

PH Not determined.

· Viscosity:

· dynamic at 20 °C: 500-1,000 mPas

· Solubility

• Water: Not miscible or difficult to mix

(Contd. on page 5)

Void

Void

Void

Void

Void

Void

Void

Version number 6 (replaces version 4) Revision: 16.09.2021 Printing date 16.09.2021

Trade name AQUA SEALING AS 1500 KOMP B

(Contd. of page 4)

· Partition coefficient n-octanol/water (log

value) Not determined.

· Steam pressure at 20 °C: 0 hPa

· Density and/or relative density

· Density at 20 °C 1.1 g/cm3 · Relative density Not determined. · Vapour density Not determined.

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health

and environment, and on safety.

· Ignition temperature: 436 °C

Explosive properties: Product is not explosive.

Solvent content:

Solids content: 50.0 %

· Change in condition

· Evaporation rate Not determined.

· Information with regard to physical hazard classes

· Explosives Flammable gases · Aerosols · Oxidising gases

· Gases under pressure Flammable liquids · Flammable solids · Self-reactive substances and mixtures

Void · Pyrophoric liquids Void Pyrophoric solids Void Self-heating substances and mixtures Void

Substances and mixtures, which emit

flammable gases in contact with water Void · Oxidising liquids Void Oxidising solids Void Organic peroxides Void Corrosive to metals Void · Desensitised explosives Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions Reacts with alkali, amines and strong acids
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Poisonous gases/vapours

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 6)

Printing date 16.09.2021

Version number 6 (replaces version 4)

Trade name AQUA SEALING AS 1500 KOMP B

(Contd. of page 5)

Revision: 16.09.2021

· LD/LC5	0 valu	es that are relevant for classification:
Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)

1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane				
Oral	LD50	>2,000 mg/kg (rat)		
Dermal	LD50	>2,000 mg/kg (rat)		

Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

Germ cell mutagenicity

Suspected of causing genetic defects.

- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

EC 50 3.3 mg/l (Daphnia magna (Großer Wasserfloh)) (48h)

- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Water hazard class (Germany) 2 (Self-assessment): hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Can be deposited with household garbage after solidification following consultation with the operator of the waste disposal facility and the pertinent authorities and under adherence to the necessary technical regulations.

(Contd. on page 7)

Printing date 16.09.2021

Version number 6 (replaces version 4)

Trade name AQUA SEALING AS 1500 KOMP B

(Contd. of page 6)

Revision: 16.09.2021

Must be specially treated under adherence to official regulations.

- · Uncleaned packagings: · Recommendation: Disposal must be made according to official regulations.

14.1 UN number or ID number	
ADR, IMDG, IATA	UN3082
14.2 UN proper shipping name ADR	3082 ENVIRONMENTALLY HAZARDO SUBSTANCE, LIQUID, N.O.S. (2,3-epoxypropy tolyl ether, bis[4-(2,3-epoxypropoxy)phen
IMDG	propane) ENVIRONMENTALLY HAZARDOUS SUBSTANG LIQUID, N.O.S. (2,3-epoxypropyl o-tolyl eth bis[4-(2,3-epoxypropoxy)phenyl]propane), MARI POLLUTANT
IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANG LIQUID, N.O.S. (2,3-epoxypropyl o-tolyl eth bis[4-(2,3-epoxypropoxy)phenyl]propane)
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class	9 Miscellaneous dangerous substances a articles.
Label	9
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards:	Product contains environmentally hazardo substances: 2,3-epoxypropyl o-tolyl ether
Marine pollutant:	Yes Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
Special marking (IATA):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Miscellaneous dangerous substances a articles.
Kemler Number:	90
EMS Number:	F-A,S-F
Stowage Category	A
14.7 Maritime transport in bulk accordi IMO instruments	ing to Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Transport category Tunnel restriction code	3
	(-)
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOU

Printing date 16.09.2021 Version number 6 (replaces version 4) Revision: 16.09.2021

Trade name AQUA SEALING AS 1500 KOMP B

(Contd. of page 7)

• EPOXYPROPYL O-TOLYL ETHER, BIS[4-(2,3-EPOXYPROPOXY)PHENYL]PROPANE), 9, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category E2 Hazardous to the Aquatic Environment
- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H341 Suspected of causing genetic defects.

H411 Toxic to aquatic life with long lasting effects.

EUH205 Contains epoxy constituents. May produce an allergic reaction.

· Contact: chemikalieninfo@murexin.com (+43 02622/27401)

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation - Category 1

Muta. 2: Germ cell mutagenicity – Category 2

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

* Data compared to the previous version altered.