

Safety data sheet according to UK REACH

Printing date 14.07.2026

Version number 10

Revision: 14.07.2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name** *DesignCoat ASD 130 Komp. B*
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** *Hardening agent/ Curing agent*
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
MUREXIN GmbH
Franz v. Furtenbachstr. 1
A-2700 Wiener Neustadt
Tel.: +43 (0)2622/27401
- **Informing department:** *chemikalieninfo@murexin.com*
- **1.4 Emergency telephone number:**
UK National poisons Emergency number.: +44 (0) 870 600 6266

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS05 corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.
 Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.
 Acute Tox. 4 H332 Harmful if inhaled.
 Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS05 GHS07

- **Signal word** *Danger*
- **Hazard-determining components of labelling:**
benzyl alcohol
3-aminomethyl-3,5,5-trimethylcyclohexylamine
Cyclohexanemethanamine
m-phenylenebis(methylamine)
Phenol, mono- + distyrenated (MSP+DSP)
3,3,5-trimethylhexamethylene-diamine
Phenol, methylstyrenated
- **Hazard statements**
H302+H332 Harmful if swallowed or if inhaled.
H314 Causes severe skin burns and eye damage.

(Contd. on page 2)

GB

Safety data sheet according to UK REACH

Printing date 14.07.2026

Version number 10

Revision: 14.07.2026

Trade name DesignCoat ASD 130 Komp. B

(Contd. of page 1)

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P260 Do not breathe mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P362+P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable

vPvB:

Phenol, methylstyrenated

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture consisting of the following components with harmless additives.

Dangerous components:

CAS: 100-51-6 EINECS: 202-859-9 Reg.nr.: 01-2119492630-38-xxxxx	benzyl alcohol ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1B, H317 ATE: LD50 oral: 1,200 mg/kg	25-50%
CAS: 2855-13-2 EINECS: 220-666-8	3-aminomethyl-3,5,5-trimethylcyclohexylamine ⚠ Skin Corr. 1B, H314; Eye Dam. 1, H318 ⚠ Acute Tox. 4, H302; Skin Sens. 1A, H317 ATE: LD50 oral: 1,030 mg/kg Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.001 %	10-25%
CAS: 68609-08-5	Cyclohexanemethanamine ⚠ Skin Corr. 1B, H314; Eye Dam. 1, H318	10-25%
CAS: 1477-55-0 EINECS: 216-032-5	m-phenylenebis(methylamine) ⚠ Skin Corr. 1B, H314; Eye Dam. 1, H318 ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1, H317 Aquatic Chronic 3, H412	≥3-<5%
	Phenol, methylstyrenated ⚠ Skin Irrit. 2, H315; Skin Sens. 1B, H317 Aquatic Chronic 3, H412 vPvB	2.5-5%

(Contd. on page 3)

GB

Safety data sheet according to UK REACH

Printing date 14.07.2026

Version number 10

Revision: 14.07.2026

Trade name **DesignCoat ASD 130 Komp. B**

(Contd. of page 2)

Reg.nr.: 01-2119980970-27-xxxx	Phenol, mono- + distyrenated (MSP+DSP) Alternative CAS number: 61788-44-1  Aquatic Chronic 2, H411  Skin Irrit. 2, H315; Skin Sens. 1A, H317	2.5-5%
CAS: 69-72-7 EINECS: 200-712-3 Reg.nr.: 01-2119486984-17-xxxx	salicylic acid  Repr. 2, H361d  Eye Dam. 1, H318  Acute Tox. 4, H302	1-2.5%
CAS: 25513-64-8 EINECS: 247-063-2 Reg.nr.: 01-2119560598-25-xxxx	3,3,5-trimethylhexamethylene-diamine  Skin Corr. 1A, H314; Eye Dam. 1, H318  Acute Tox. 4, H302; Skin Sens. 1A, H317	1-2.5%

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Instantly remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation

Take affected persons into the open air and position comfortably

Seek medical treatment in case of complaints.

Supply fresh air and call for doctor for safety reasons.

In case of unconsciousness bring patient into stable side position for transport.

After skin contact

Instantly wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

After swallowing

Instantly call for doctor.

Drink copious amounts of water and provide fresh air. Instantly call for doctor.

In case of persistent symptoms consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents Use fire fighting measures that suit the environment.

5.2 Special hazards arising from the substance or mixture

Formation of poisonous gases during heating or in fires.

5.3 Advice for firefighters

Protective equipment: Put on breathing apparatus.

Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

(Contd. on page 4)

Safety data sheet according to UK REACH

Printing date 14.07.2026

Version number 10

Revision: 14.07.2026

Trade name DesignCoat ASD 130 Komp. B

(Contd. of page 3)

*Put on breathing apparatus.**Wear protective clothing.***· 6.2 Environmental precautions:***Do not allow to enter the ground/soil.**Do not allow product to reach sewage system or water bodies.**Inform respective authorities in case product reaches water or sewage system.***· 6.3 Methods and material for containment and cleaning up:***Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).**Use neutralising agent.**Dispose of contaminated material as waste according to item 13.**Ensure adequate ventilation.***· 6.4 Reference to other sections***See Section 7 for information on safe handling**See Section 8 for information on personal protection equipment.**See Section 13 for information on disposal.*

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling*Keep containers tightly sealed.**Ensure good ventilation/exhaustion at the workplace.**Open and handle container with care.**Prevent formation of aerosols.***· Information about protection against explosions and fires:** *Keep breathing equipment ready.***· 7.2 Conditions for safe storage, including any incompatibilities****· Storage****· Requirements to be met by storerooms and containers:***Provide floor trough without outlet.**Store only in the original container.***· Information about storage in one common storage facility:** *Store away from foodstuffs.***· Further information about storage conditions:***Protect from frost.**Keep container tightly sealed.***· Storage class 8 A****· 7.3 Specific end use(s)** *No further relevant information available.*

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters**· Components with critical values that require monitoring at the workplace:***The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.***· Additional information:** *The lists that were valid during the compilation were used as basis.***· 8.2 Exposure controls****· Appropriate engineering controls** *No further data; see section 7.***· Individual protection measures, such as personal protective equipment****· General protective and hygienic measures***The usual precautionary measures should be adhered to in handling the chemicals.**Keep away from foodstuffs, beverages and food.**Instantly remove any soiled and impregnated garments.**Wash hands during breaks and at the end of the work.**Store protective clothing separately.**Avoid contact with the eyes.**Avoid contact with the eyes and skin.*

(Contd. on page 5)

Safety data sheet according to UK REACH

Printing date 14.07.2026

Version number 10

Revision: 14.07.2026

Trade name DesignCoat ASD 130 Komp. B

(Contd. of page 5)

- | | |
|--------------------------------|---------------------------|
| · Explosive properties: | Product is not explosive. |
| · Solvent content: | |
| · Solids content: | 0.0 % |
| · Change in condition | |
| · Evaporation rate | Not determined |

· **Information with regard to physical hazard classes**

- | | |
|--|------|
| · Explosives | Void |
| · Flammable gases | Void |
| · Aerosols | Void |
| · Oxidising gases | Void |
| · Gases under pressure | Void |
| · Flammable liquids | Void |
| · Flammable solids | Void |
| · Self-reactive substances and mixtures | Void |
| · Pyrophoric liquids | Void |
| · Pyrophoric solids | Void |
| · Self-heating substances and mixtures | Void |
| · Substances and mixtures, which emit flammable gases in contact with water | Void |
| · Oxidising liquids | Void |
| · Oxidising solids | Void |
| · Organic peroxides | Void |
| · Corrosive to metals | Void |
| · Desensitised explosives | Void |

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
Poisonous gases/vapours
Corrosive gases/vapours

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Harmful if swallowed or if inhaled.

· **LD/LC50 values that are relevant for classification:**

100-51-6 benzyl alcohol

Oral	LD50	1,200 mg/kg (ATE)
		1,230 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine

Oral	LD50	1,030 mg/kg (ATE)
------	------	-------------------

- **Primary irritant effect:**
- **Skin corrosion/irritation** Causes severe skin burns and eye damage.
- **Serious eye damage/irritation** Causes serious eye damage.

(Contd. on page 7)

Safety data sheet according to UK REACH

Printing date 14.07.2026

Version number 10

Revision: 14.07.2026

Trade name DesignCoat ASD 130 Komp. B

(Contd. of page 6)

· 11.2 Information on other hazards

· Endocrine disrupting properties

	Phenol, methylstyrenated	List II; III
69-72-7	salicylic acid	List II; III

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine

EC 50	37 mg/l (Acartia Tonsa) (DIN 38412 (72h))
	42 mg/l (G) (DIN 38412 24h)

· 12.2 Persistence and degradability No further relevant information available.

· 12.3 Bioaccumulative potential No further relevant information available.

· 12.4 Mobility in soil No further relevant information available.

· 12.5 Results of PBT and vPvB assessment

· PBT: Not applicable

· vPvB:

Phenol, methylstyrenated

· 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

· 12.7 Other adverse effects

· Remark: Harmful to fish

· Additional ecological information:

· General notes:

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Harmful to aquatic organisms

Water hazard class (Germany) 2 (Self-assessment): hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

· Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, IMDG, IATA

UN2735

· 14.2 UN proper shipping name

· ADR

2735 AMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine)), ISOPHORONEDIAMINE)

(Contd. on page 8)

Safety data sheet according to UK REACH

Printing date 14.07.2026

Version number 10

Revision: 14.07.2026

Trade name DesignCoat ASD 130 Komp. B

(Contd. of page 7)

· IMDG, IATA	AMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine), ISOPHORONEDIAMINE)
· 14.3 Transport hazard class(es)	
· ADR, IMDG, IATA	
	
· Class	8 Corrosive substances.
· Label	8
· 14.4 Packing group	
· ADR, IMDG, IATA	II
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Corrosive substances.
· Kemler Number:	80
· EMS Number:	F-A, S-B
· Segregation groups	(SGG18) Alkalis
· Stowage Category	A
· Segregation Code	SG35 Stow "separated from" SGG1-acids
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Transport category	2
· Tunnel restriction code	E
· UN "Model Regulation":	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (M-PHENYLENEBIS(METHYLAMINE), ISOPHORONEDIAMINE), 8, II

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Poisons Act**

· **Regulated explosives precursors**

None of the ingredients is listed.

· **Regulated poisons**

None of the ingredients is listed.

· **Reportable explosives precursors**

None of the ingredients is listed.

· **Reportable poisons**

None of the ingredients is listed.

· **Directive 2012/18/EU**

- **Named dangerous substances - ANNEX I** None of the ingredients is listed.

(Contd. on page 9)

Safety data sheet according to UK REACH

Printing date 14.07.2026

Version number 10

Revision: 14.07.2026

Trade name DesignCoat ASD 130 Komp. B

(Contd. of page 8)

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H302 Harmful if swallowed.
 H314 Causes severe skin burns and eye damage.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H332 Harmful if inhaled.
 H361d Suspected of damaging the unborn child.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

· **Contact:** chemikalieninfo@murexin.com (+43 02622/27401)

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 ICAO: International Civil Aviation Organisation
 ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 ATE: Acute toxicity estimate values
 Acute Tox. 4: Acute toxicity – Category 4
 Skin Corr. 1A: Skin corrosion/irritation – Category 1A
 Skin Corr. 1B: Skin corrosion/irritation – Category 1B
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1
 Skin Sens. 1: Skin sensitisation – Category 1
 Skin Sens. 1A: Skin sensitisation – Category 1A
 Skin Sens. 1B: Skin sensitisation – Category 1B
 Repr. 2: Reproductive toxicity – Category 2
 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· *** Data compared to the previous version altered.**

GB