

Safety data sheet according to UK REACH

Printing date 01.09.2026

Version number 11 (replaces version 10)

Revision: 25.08.2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name** *DesignCoat NX 85 seidenmatt*
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** *Sealing*
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
MUREXIN GmbH
Franz v. Furtenbachstr. 1
A-2700 Wiener Neustadt
Tel.: +43 (0)2622/27401
- **Informing department:** *chemikalieninfo@murexin.com*
- **1.4 Emergency telephone number:**
UK National poisons Emergency number.: +44 (0) 870 600 6266

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

- **Additional information:**
The full text of the classification and labelling elements mentioned is given in Section 16.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS07

- **Signal word** *Warning*
- **Hazard statements**
H315 Causes skin irritation.
H319 Causes serious eye irritation.
- **Precautionary statements**

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.
P264	Wash thoroughly after handling.
P280	Wear eye protection / face protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Additional information:**
Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1), 1,2-benzisothiazol-3(2H)-one [EC no. 220-120-9], 4-morpholinecarbaldehyde. May produce an allergic reaction.
Contains microplastics. Observe the instructions for use and disposal to prevent release into the environment. Allow construction products to fully cure before recycling or disposal. Cleaning water should be reused or properly disposed of – avoid any discharge into the environment!

(Contd. on page 2)

GB

Safety data sheet according to UK REACH

Printing date 01.09.2026

Version number 11 (replaces version 10)

Revision: 25.08.2026

Trade name DesignCoat NX 85 seidenmatt

(Contd. of page 1)

- 2.3 Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable
- vPvB: Not applicable

SECTION 3: Composition/information on ingredients

3.2 Mixtures

· **Description:** Mixture consisting of the following components with harmless additives.

· Dangerous components:

CAS: 34590-94-8 EINECS: 252-104-2	Dipropylene glycol monomethyl ether substance with a Community workplace exposure limit	2.5-5%
CAS: 108-01-0 EINECS: 203-542-8	2-dimethylaminoethanol Flam. Liq. 3, H226 Skin Corr. 1B, H314 Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332 Specific concentration limit: STOT SE 3; H335: C ≥ 5 %	1-2.5%
CAS: 112-34-5 EINECS: 203-961-6 Reg.nr.: 01-2119475104-44	2-(2-butoxyethoxy)ethanol Eye Irrit. 2, H319	0.5-1%
CAS: 4394-85-8 EINECS: 224-518-3	4-morpholinecarbaldehyde Skin Sens. 1B, H317	≥0.1-<0.5%
CAS: 2634-33-5 EINECS: 220-120-9	1,2-benzisothiazol-3(2H)-one [EC no. 220-120-9] Acute Tox. 2, H330 Eye Dam. 1, H318 Aquatic Acute 1, H400 Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317 ATE: LD50 oral: 450 mg/kg LC50/4 h inhalative: 0.21 mg/l Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.036 %	<0.1%
CAS: 55965-84-9	reaction mass of: 5-chloro-2-methyl-4- isothiazolin-3-one [EC no. 247-500-7] and 2- methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox. 2, H330 Skin Corr. 1C, H314 Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100) Skin Sens. 1A, H317 EUH071 Specific concentration limits: Skin Corr. 1C; H314: C ≥ 0.6 % Skin Irrit. 2; H315: 0.06 % ≤ C < 0.6 % Eye Dam. 1; H318: C ≥ 0.6 % Eye Irrit. 2; H319: 0.06 % ≤ C < 0.6 % Skin Sens. 1A; H317: C ≥ 0.0015 %	≥0.00025-<0.0025%

GB

(Contd. on page 3)

Safety data sheet according to UK REACH

Printing date 01.09.2026

Version number 11 (replaces version 10)

Revision: 25.08.2026

Trade name DesignCoat NX 85 seidenmatt

(Contd. of page 2)

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **After inhalation** In case of unconsciousness bring patient into stable side position for transport.
- **After skin contact**
Instantly wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
- **After eye contact**
Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.
- **After swallowing** In case of persistent symptoms consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** Use fire fighting measures that suit the environment.
- **5.2 Special hazards arising from the substance or mixture**
No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective clothing.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or water bodies.
Dilute with much water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of contaminated material as waste according to item 13.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Keep containers tightly sealed.
- **Information about protection against explosions and fires:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** Store only in the original container.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:**
Protect from frost.
Keep container tightly sealed.
- **Storage class** 12
- **7.3 Specific end use(s)** No further relevant information available.

GB

(Contd. on page 4)

Safety data sheet according to UK REACH

Printing date 01.09.2026

Version number 11 (replaces version 10)

Revision: 25.08.2026

Trade name DesignCoat NX 85 seidenmatt

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with critical values that require monitoring at the workplace:

34590-94-8 Dipropylene glycol monomethyl ether

WEL	Long-term value: 308 mg/m ³ , 50 ppm
Sk	

108-01-0 2-dimethylaminoethanol

WEL	Short-term value: 22 mg/m ³ , 6 ppm
	Long-term value: 7.4 mg/m ³ , 2 ppm

112-34-5 2-(2-butoxyethoxy)ethanol

WEL	Short-term value: 101.2 mg/m ³ , 15 ppm
	Long-term value: 67.5 mg/m ³ , 10 ppm

Additional information: The lists that were valid during the compilation were used as basis.

8.2 Exposure controls

Appropriate engineering controls No further data; see section 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures

The usual precautionary measures should be adhered to in handling the chemicals.

Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

Breathing equipment: Not required

Hand protection

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection Gauze goggles

Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state

Liquid

Colour:

Whitish

Smell:

Characteristic

Odour threshold:

Not determined

Melting point/freezing point:

Not determined

Boiling point or initial boiling point and boiling range

100 °C (7732-18-5 water, distilled, conductivity or of similar purity)

Flammability

Not applicable

Lower and upper explosion limit

Lower:

Not determined

Upper:

Not determined

Flash point:

Not applicable

Decomposition temperature:

Not determined

pH at 20 °C

7.5-8.2

(Contd. on page 5)

Safety data sheet according to UK REACH

Printing date 01.09.2026

Version number 11 (replaces version 10)

Revision: 25.08.2026

Trade name DesignCoat NX 85 seidenmatt

(Contd. of page 4)

· Viscosity:	
· Kinematic viscosity at 20 °C	20-23 s (DIN 53211/4)
· dynamic:	Not determined
· Solubility	
· Water:	Partly miscible
· Partition coefficient n-octanol/water (log value)	Not determined
· Steam pressure at 20 °C:	23 hPa (7732-18-5 water, distilled, conductivity or of similar purity)
· Density and/or relative density	
· Density at 20 °C	1 g/cm ³
· Relative density	Not determined
· Vapour density	Not determined
· 9.2 Other information	
· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Self-inflammability:	Product is not selfigniting.
· Explosive properties:	Product is not explosive.
· Solvent content:	
· Water:	50.3 %
· Solids content:	25.9-27.4 %
· Change in condition	
· Evaporation rate	Not determined
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** None

GB

(Contd. on page 6)

Safety data sheet according to UK REACH

Printing date 01.09.2026

Version number 11 (replaces version 10)

Revision: 25.08.2026

Trade name DesignCoat NX 85 seidenmatt

(Contd. of page 5)

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values that are relevant for classification:**

34590-94-8 Dipropylene glycol monomethyl ether

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	9,500 mg/kg (rat)

108-01-0 2-dimethylaminoethanol

Oral	LD50	2,000 mg/kg (rat)
Dermal	LD50	1,370 mg/kg (rabbit)
Inhalative	LC50/4 h	3.25 mg/l (mouse)

4394-85-8 4-morpholinecarbaldehyde

Dermal	LD50	>18,300 mg/kg (rabbit)
--------	------	------------------------

2634-33-5 1,2-benzisothiazol-3(2H)-one [EC no. 220-120-9]

Oral	LD50	450 mg/kg (ATE)
Inhalative	LC50/4 h	0.21 mg/l (ATE)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction) -**
- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

7447-41-8	lithium chloride	List III
556-67-2	octamethylcyclotetrasiloxane	List II

SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

2634-33-5 1,2-benzisothiazol-3(2H)-one [EC no. 220-120-9]

EC 50/48h	3.27 mg/l (Daphnie)
-----------	---------------------

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**

- **PBT:** Not applicable
- **vPvB:** Not applicable

- **12.6 Endocrine disrupting properties**

For information on endocrine disrupting properties see section 11.

- **12.7 Other adverse effects**

- **Additional ecological information:**

- **General notes:**

Water hazard class (Germany) 1 (Self-assessment): slightly hazardous for water.

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

GB

(Contd. on page 7)

Safety data sheet according to UK REACH

Printing date 01.09.2026

Version number 11 (replaces version 10)

Revision: 25.08.2026

Trade name DesignCoat NX 85 seidenmatt

(Contd. of page 6)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncleaned packagings:

Recommendation: Disposal must be made according to official regulations.

Recommended cleaning agent: Water, if necessary with cleaning agent.

SECTION 14: Transport information

14.1 UN number or ID number

ADR, ADN, IMDG, IATA Void

14.2 UN proper shipping name

ADR, ADN, IMDG, IATA Void

14.3 Transport hazard class(es)

ADR, ADN, IMDG, IATA

Class Void

14.4 Packing group

ADR, IMDG, IATA Void

14.5 Environmental hazards:

Marine pollutant: No

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable

UN "Model Regulation":

Void

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poisons Act

Regulated explosives precursors

None of the ingredients is listed.

Regulated poisons

None of the ingredients is listed.

Reportable explosives precursors

None of the ingredients is listed.

Reportable poisons

None of the ingredients is listed.

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 8)

Safety data sheet according to UK REACH

Printing date 01.09.2026

Version number 11 (replaces version 10)

Revision: 25.08.2026

Trade name **DesignCoat NX 85 seidenmatt**

(Contd. of page 7)

· **Relevant phrases**

H226 Flammable liquid and vapour.
 H301 Toxic if swallowed.
 H302 Harmful if swallowed.
 H310 Fatal in contact with skin.
 H312 Harmful in contact with skin.
 H314 Causes severe skin burns and eye damage.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H330 Fatal if inhaled.
 H332 Harmful if inhaled.
 H335 May cause respiratory irritation.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.
 EUH071 Corrosive to the respiratory tract.

· **Contact:** chemikalieninfo@murexin.com (+43 02622/27401)

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 ICAO: International Civil Aviation Organisation
 ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 ATE: Acute toxicity estimate values
 Flam. Liq. 3: Flammable liquids – Category 3
 Acute Tox. 3: Acute toxicity – Category 3
 Acute Tox. 4: Acute toxicity – Category 4
 Acute Tox. 2: Acute toxicity – Category 2
 Skin Corr. 1B: Skin corrosion/irritation – Category 1B
 Skin Corr. 1C: Skin corrosion/irritation – Category 1C
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 Skin Sens. 1: Skin sensitisation – Category 1
 Skin Sens. 1A: Skin sensitisation – Category 1A
 Skin Sens. 1B: Skin sensitisation – Category 1B
 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

· *** Data compared to the previous version altered.**

GB