

Safety data sheet according to UK REACH

Printing date 06.05.2026

Version number 7 (replaces version 6)

Revision: 06.05.2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name** *DesignCoat PU 300 Komp. B*
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** *Hardening agent/ Curing agent*
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
MUREXIN GmbH
Franz v. Furtenbachstr. 1
A-2700 Wiener Neustadt
Tel.: +43 (0)2622/27401
- **Informing department:** *chemikalieninfo@murexin.com*
- **1.4 Emergency telephone number:**
UK National poisons Emergency number.: +44 (0) 870 600 6266

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS08 health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Carc. 2 H351 Suspected of causing cancer.
STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.
Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2 H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.
STOT SE 3 H335 May cause respiratory irritation.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS07 GHS08

- **Signal word** *Danger*
- **Hazard-determining components of labelling:**
Reaction mass of 4,4'-methylenediphenyl diisocyanate and O-(p-isocyanate benzyl)phenyl isocyanate diphenylmethanediisocyanate, isomers and homologues
- **Hazard statements**
H332 Harmful if inhaled.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

(Contd. on page 2)

Safety data sheet according to UK REACH

Printing date 06.05.2026

Version number 7 (replaces version 6)

Revision: 06.05.2026

Trade name **DesignCoat PU 300 Komp. B**

(Contd. of page 1)

*H317 May cause an allergic skin reaction.**H351 Suspected of causing cancer.**H335 May cause respiratory irritation.**H373 May cause damage to organs through prolonged or repeated exposure.***Precautionary statements***P101 If medical advice is needed, have product container or label at hand.**P102 Keep out of reach of children.**P103 Read carefully and follow all instructions.**P260 Do not breathe dust/fume/gas/mist/vapours/spray.**P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.**P284 [In case of inadequate ventilation] wear respiratory protection.**P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.**P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.**P501 Dispose of contents/container in accordance with local/regional/national/international regulations.***Additional information:***Contains isocyanates. May produce an allergic reaction.**As from 24 August 2023 adequate training is required before industrial or professional use. Handling this product may cause allergic reactions in people who are already sensitized to diisocyanates. If you have asthma, eczema, or skin problems, avoid contact with the product, including skin contact.***2.3 Other hazards****Results of PBT and vPvB assessment***• PBT: Not applicable**• vPvB: Not applicable*

SECTION 3: Composition/information on ingredients

3.2 Mixtures*• Description: Mixture consisting of the following components with harmless additives.***Dangerous components:**

EC number: 905-806-4 Reg.nr.: 01-2119457015-45-xxx	Reaction mass of 4,4'-methylenediphenyl diisocyanate and O-(p-isocyanate benzyl)phenyl isocyanate ⚠ Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373 ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1B, H317; STOT SE 3, H335	50-100%
CAS: 9016-87-9	diphenylmethanediisocyanate, isomeres and homologues Consisting of: 101-68-8 diphenylmethane-4,4'-diisocyanate (37.5%); 5873-54-1 Diphenylmethane-2,4'-diisocyanate (3%); 2536-05-2 diphenylmethane-2,2'-diisocyanate (0.5%) ⚠ Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373 ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335 EUH204 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 % Resp. Sens. 1; H334: C ≥ 0.1 % STOT SE 3; C ≥ 5 %	25-50%

GB

(Contd. on page 3)

Safety data sheet according to UK REACH

Printing date 06.05.2026

Version number 7 (replaces version 6)

Revision: 06.05.2026

Trade name DesignCoat PU 300 Komp. B

(Contd. of page 2)

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· **General information**

Instantly remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation**

Use a respiration bag or breathing device.

Supply fresh air and call for doctor for safety reasons.

In case of unconsciousness bring patient into stable side position for transport.

· **After skin contact**

Instantly wash with water and soap and rinse thoroughly.

Instantly rinse with water.

If skin irritation continues, consult a doctor.

· **After eye contact**

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

· **After swallowing** *In case of persistent symptoms consult doctor.*

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

Medical supervision for at least 48 hours

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· **Suitable extinguishing agents** *Use fire fighting measures that suit the environment.*

· 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

Hydrogen cyanide (HCN)

Formation of poisonous gases during heating or in fires.

· 5.3 Advice for firefighters

· **Protective equipment:**

Wear self-contained breathing apparatus.

Do not inhale explosion gases or combustion gases.

Put on breathing apparatus.

· **Additional information**

Collect contaminated fire fighting water separately. It must not enter drains.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Keep people at a distance and stay on the windward side.

Particular danger of slipping on leaked/spilled product.

Put on breathing apparatus.

Wear protective clothing.

· 6.2 Environmental precautions:

Do not allow to enter the ground/soil.

Keep dirty washing water for appropriate disposal.

Do not allow product to reach sewage system or water bodies.

· 6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable containers.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

(Contd. on page 4)

Safety data sheet according to UK REACH

Printing date 06.05.2026

Version number 7 (replaces version 6)

Revision: 06.05.2026

Trade name DesignCoat PU 300 Komp. B

(Contd. of page 3)

6.4 Reference to other sections

- See Section 7 for information on safe handling
- See Section 8 for information on personal protection equipment.
- See Section 13 for information on disposal.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Keep containers tightly sealed.
- Ensure good ventilation/exhaustion at the workplace.
- Open and handle container with care.
- Prevent formation of aerosols.
- Information about protection against explosions and fires:** Keep breathing equipment ready.

7.2 Conditions for safe storage, including any incompatibilities

- Storage**
- Requirements to be met by storerooms and containers:** Store only in the original container.
- Information about storage in one common storage facility:** Store away from foodstuffs.
- Further information about storage conditions:**
 - Protect from humidity and keep away from water.
 - Protect from frost.
 - Keep container tightly sealed.
- Storage class 10**
- 7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

- Components with critical values that require monitoring at the workplace:**

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

WEL	Short-term value: 0.07 mg/m ³ Long-term value: 0.02 mg/m ³ Sen; as -NCO
-----	---

- Additional information:** The lists that were valid during the compilation were used as basis.

8.2 Exposure controls

- Appropriate engineering controls** No further data; see section 7.
- Individual protection measures, such as personal protective equipment**
- General protective and hygienic measures**
 - The usual precautionary measures should be adhered to in handling the chemicals.
 - Keep away from foodstuffs, beverages and food.
 - Instantly remove any soiled and impregnated garments.
 - Wash hands during breaks and at the end of the work.
 - Store protective clothing separately.
 - Avoid contact with the eyes and skin.
- Breathing equipment:**
 - Filter P3.
 - In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.
- Hand protection**
 - Protective gloves.
 - The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
- Material of gloves**
 - Butyl rubber, BR
 - Fluorocarbon rubber (Viton)

(Contd. on page 5)

Safety data sheet according to UK REACH

Printing date 06.05.2026

Version number 7 (replaces version 6)

Revision: 06.05.2026

Trade name DesignCoat PU 300 Komp. B

(Contd. of page 4)

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· **Penetration time of glove material**

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye/face protection** Face protection

· **Body protection:** Protective work clothing.

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Physical state**

Liquid

· **Colour:**

Brown

· **Smell:**

Not characteristic

· **Odour threshold:**

Not determined

· **Melting point/freezing point:**

5 °C

· **Boiling point or initial boiling point and boiling range**

>300 °C

· **Flammability**

Not applicable

· **Lower and upper explosion limit**

· **Lower:**

Not determined

· **Upper:**

Not determined

· **Flash point:**

>200 °C

· **Decomposition temperature:**

Not determined

· **pH**

Mixture is non-soluble (in water).

· **Viscosity:**

· **Kinematic viscosity at 20 °C**

70-130 mm²/s

· **dynamic:**

Not determined

· **Solubility**

· **Water:**

Not miscible or difficult to mix

· **Partition coefficient n-octanol/water (log value)**

Not determined

· **Steam pressure at 20 °C:**

>0 hPa

· **Density and/or relative density**

· **Density at 20 °C**

1.2 g/cm³

· **Relative density**

Not determined

· **Vapour density**

Not determined

· **9.2 Other information**

· **Appearance:**

· **Form:**

Fluid

· **Important information on protection of health and environment, and on safety.**

· **Self-inflammability:**

Product is not selfigniting.

· **Explosive properties:**

Product is not explosive.

· **Solvent content:**

· **Solids content:**

0.0 %

· **Change in condition**

· **Evaporation rate**

Not determined

· **Information with regard to physical hazard classes**

· **Explosives**

Void

· **Flammable gases**

Void

· **Aerosols**

Void

(Contd. on page 6)

Safety data sheet according to UK REACH

Printing date 06.05.2026

Version number 7 (replaces version 6)

Revision: 06.05.2026

Trade name DesignCoat PU 300 Komp. B

(Contd. of page 5)

· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Danger of bursting
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** Keep away from strongly acidic and alkaline materials
- **10.6 Hazardous decomposition products:** None

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Harmful if inhaled.

· LD/LC50 values that are relevant for classification:

Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

Oral	LD50	>100,000 mg/kg (rat)
Dermal	LD50	>9,400 mg/kg (rabbit)
Inhalative	LC50/4 h	0.49 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Carcinogenicity** Suspected of causing cancer.
- **STOT-single exposure** May cause respiratory irritation.
- **STOT-repeated exposure** May cause damage to organs through prolonged or repeated exposure.
- **11.2 Information on other hazards**

· Endocrine disrupting properties

None of the ingredients is listed.

GB

(Contd. on page 7)

Safety data sheet according to UK REACH

Printing date 06.05.2026

Version number 7 (replaces version 6)

Revision: 06.05.2026

Trade name DesignCoat PU 300 Komp. B

(Contd. of page 6)

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

EC 50/24h	>1,000 mg/l (G)
EC 50	>100 mg/l (Belebtschlamm)
LC50	>1,000 mg/l (Brachydanio rerio (Zebrabärbling))

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

EC 50	>100 mg/l (F2) (OECD 209 Activated Sludge, Respiration Inhibition)
	>1,000 mg/l (G) (OECD 202 Acute Immobilisation Tet)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable
- **vPvB:** Not applicable
- **12.6 Endocrine disrupting properties**
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**
Water hazard class (Germany) 1 (Self-assessment): slightly hazardous for water.
Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

After prior treatment product has to be landfilled or incinerated under adherence to the regulations pertaining to the disposal of especially hazardous waste.
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncleaned packagings:

Recommendation:

Non contaminated packagings can be used for recycling.
Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN number or ID number

· **ADR, ADN, IMDG, IATA** Void

14.2 UN proper shipping name

· **ADR, ADN, IMDG, IATA** Void

14.3 Transport hazard class(es)

· **ADR, ADN, IMDG, IATA**

· **Class** Void

14.4 Packing group

· **ADR, IMDG, IATA** Void

(Contd. on page 8)

Safety data sheet according to UK REACH

Printing date 06.05.2026

Version number 7 (replaces version 6)

Revision: 06.05.2026

Trade name DesignCoat PU 300 Komp. B

(Contd. of page 7)

· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Not applicable
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable
· UN "Model Regulation":	Void

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Poisons Act**

· **Regulated explosives precursors**

None of the ingredients is listed.

· **Regulated poisons**

None of the ingredients is listed.

· **Reportable explosives precursors**

None of the ingredients is listed.

· **Reportable poisons**

None of the ingredients is listed.

· **Directive 2012/18/EU**

- **Named dangerous substances - ANNEX I** None of the ingredients is listed.

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer.
- H373 May cause damage to organs through prolonged or repeated exposure.
- EUH204 Contains isocyanates. May produce an allergic reaction.

- **Contact:** chemikalieninfo@murexin.com (+43 02622/27401)

· **Abbreviations and acronyms:**

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic

(Contd. on page 9)

**Safety data sheet
according to UK REACH**

Printing date 06.05.2026

Version number 7 (replaces version 6)

Revision: 06.05.2026

Trade name DesignCoat PU 300 Komp. B

(Contd. of page 8)

*vPvB: very Persistent and very Bioaccumulative**Acute Tox. 4: Acute toxicity – Category 4**Skin Irrit. 2: Skin corrosion/irritation – Category 2**Eye Irrit. 2: Serious eye damage/eye irritation – Category 2**Resp. Sens. 1: Respiratory sensitisation – Category 1**Skin Sens. 1: Skin sensitisation – Category 1**Skin Sens. 1B: Skin sensitisation – Category 1B**Carc. 2: Carcinogenicity – Category 2**STOT SE 3: Specific target organ toxicity (single exposure) – Category 3**STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2**** Data compared to the previous version altered.**

GB