

Safety data sheet according to UK REACH

Printing date 16.06.2026

Version number 6

Revision: 16.06.2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name** *DesignCoat PU 40 Komp. A*
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** *Polurethane Seal*
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
MUREXIN GmbH
Franz v. Furtenbachstr. 1
A-2700 Wiener Neustadt
Tel.: +43 (0)2622/27401
- **Informing department:** *chemikalieninfo@murexin.com*
- **1.4 Emergency telephone number:**
UK National poisons Emergency number.: +44 (0) 870 600 6266

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS07

- **Signal word** *Warning*
- **Hazard-determining components of labelling:**
*1,2-benzisothiazol-3(2H)-one [EC no. 220-120-9]
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)
4-morpholinecarbaldehyde*
- **Hazard statements**
H317 May cause an allergic skin reaction.
- **Precautionary statements**
*P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read carefully and follow all instructions.
P261 Avoid breathing mist/vapours/spray.
P280 Wear protective gloves.
P302+P352 IF ON SKIN: Wash with plenty of water.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.*
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** *Not applicable*

(Contd. on page 2)

Safety data sheet according to UK REACH

Printing date 16.06.2026

Version number 6

Revision: 16.06.2026

Trade name **DesignCoat PU 40 Komp. A**

(Contd. of page 1)

· **vPvB:** Not applicable

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description:** Mixture consisting of the following components with harmless additives.

· **Dangerous components:**

CAS: 57-55-6 EINECS: 200-338-0 Reg.nr.: 01-2119456809-23-xxxx	Propylene glycol substance with a Community workplace exposure limit	0.5-1%
CAS: 112-34-5 EINECS: 203-961-6 Reg.nr.: 01-2119475104-44	2-(2-butoxyethoxy)ethanol ⚠ Eye Irrit. 2, H319	0.5-1%
CAS: 4394-85-8 EINECS: 224-518-3	4-morpholinecarbaldehyde ⚠ Skin Sens. 1B, H317	≥0.1-<0.5%
CAS: 2634-33-5 EINECS: 220-120-9	1,2-benzisothiazol-3(2H)-one [EC no. 220-120-9] ⚠ Acute Tox. 2, H330 ⚠ Eye Dam. 1, H318 ⚠ Aquatic Acute 1, H400 ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317 ATE: LD50 oral: 450 mg/kg LC50/4 h inhalative: 0.21 mg/l Specific concentration limit: Skin Sens. 1A;H317: C ≥ 0.036 %	<0.1%
CAS: 55965-84-9	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) ⚠ Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox. 2, H330 ⚠ Skin Corr. 1C, H314 ⚠ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100) ⚠ Skin Sens. 1A, H317 EUH071 Specific concentration limits: Skin Corr. 1C;H314: C ≥ 0.6 % Skin Irrit. 2; H315: 0.06 % ≤ C < 0.6 % Eye Dam. 1; H318: C ≥ 0.6 % Eye Irrit. 2; H319: 0.06 % ≤ C < 0.6 % Skin Sens. 1A; H317: C ≥ 0.0015 %	≥0.00025-<0.0025%

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· **General information** Instantly remove any clothing soiled by the product.

· **After inhalation** Supply fresh air; consult doctor in case of symptoms.

· **After skin contact**

Instantly wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· **After eye contact** Rinse opened eye for several minutes under running water.

· **After swallowing** In case of persistent symptoms consult doctor.

(Contd. on page 3)

Safety data sheet according to UK REACH

Printing date 16.06.2026

Version number 6

Revision: 16.06.2026

Trade name DesignCoat PU 40 Komp. A

(Contd. of page 2)

- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** Use fire fighting measures that suit the environment.
- **5.2 Special hazards arising from the substance or mixture**
No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective clothing.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or water bodies.
Dilute with much water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** Store only in the original container.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class** 12
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**

- **Components with critical values that require monitoring at the workplace:**

57-55-6 Propylene glycol

WEL	Long-term value: 474* 10** mg/m ³ , 150* ppm *total vapour and particulates **particulates
-----	--

(Contd. on page 4)

Safety data sheet according to UK REACH

Printing date 16.06.2026

Version number 6

Revision: 16.06.2026

Trade name DesignCoat PU 40 Komp. A

(Contd. of page 3)

112-34-5 2-(2-butoxyethoxy)ethanol

WEL	Short-term value: 101.2 mg/m ³ , 15 ppm Long-term value: 67.5 mg/m ³ , 10 ppm
-----	--

· **Additional information:** The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

· **Appropriate engineering controls** No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures**

The usual precautionary measures should be adhered to in handling the chemicals.

Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

· **Breathing equipment:** Not necessary if room is well-ventilated.

· **Hand protection**

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

Use gloves of stable material (e.g. Nitrile) - if necessary tricoted to improve the wearability.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye/face protection** Safety glasses recommended during refilling.

· **Body protection:** Protective work clothing.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· **General Information**

· **Physical state**

Liquid

· **Colour:**

Various colours

· **Smell:**

Odourless

· **Odour threshold:**

Not determined

· **Melting point/freezing point:**

Not determined

· **Boiling point or initial boiling point and boiling range**

100 °C (7732-18-5 water, distilled, conductivity or of similar purity)

· **Flammability**

Not applicable

· **Lower and upper explosion limit**

· **Lower:**

Not determined

· **Upper:**

Not determined

· **Flash point:**

>100 °C

· **Decomposition temperature:**

Not determined

· **pH at 20 °C**

8

· **Viscosity:**

· **Kinematic viscosity**

Not determined

· **dynamic:**

Not determined

· **Solubility**

· **Water:**

Not determined

· **Partition coefficient n-octanol/water (log value)**

Not determined

· **Steam pressure at 20 °C:**

23 hPa (7732-18-5 water, distilled, conductivity or of similar purity)

(Contd. on page 5)

Safety data sheet according to UK REACH

Printing date 16.06.2026

Version number 6

Revision: 16.06.2026

Trade name DesignCoat PU 40 Komp. A

(Contd. of page 4)

- **Density and/or relative density**
- **Density at 20 °C** 1.2 g/cm³
- **Relative density** Not determined
- **Vapour density** Not determined

- **9.2 Other information**
- **Appearance:**
- **Form:** Fluid
- **Important information on protection of health and environment, and on safety.**
- **Self-inflammability:** Product is not selfigniting.
- **Explosive properties:** Product is not explosive.
- **Change in condition**
- **Evaporation rate** Not determined

- **Information with regard to physical hazard classes**
- **Explosives** Void
- **Flammable gases** Void
- **Aerosols** Void
- **Oxidising gases** Void
- **Gases under pressure** Void
- **Flammable liquids** Void
- **Flammable solids** Void
- **Self-reactive substances and mixtures** Void
- **Pyrophoric liquids** Void
- **Pyrophoric solids** Void
- **Self-heating substances and mixtures** Void
- **Substances and mixtures, which emit flammable gases in contact with water** Void
- **Oxidising liquids** Void
- **Oxidising solids** Void
- **Organic peroxides** Void
- **Corrosive to metals** Void
- **Desensitised explosives** Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** None

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:

57-55-6 Propylene glycol

Oral	LD50	22,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)

(Contd. on page 6)

Safety data sheet according to UK REACH

Printing date 16.06.2026

Version number 6

Revision: 16.06.2026

Trade name DesignCoat PU 40 Komp. A

(Contd. of page 5)

4394-85-8 4-morpholinecarbaldehyde

Dermal	LD50	>18,300 mg/kg (rabbit)
--------	------	------------------------

2634-33-5 1,2-benzisothiazol-3(2H)-one [EC no. 220-120-9]

Oral	LD50	450 mg/kg (ATE)
------	------	-----------------

Inhalative	LC50/4 h	0.21 mg/l (ATE)
------------	----------	-----------------

- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction) -**
- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

7447-41-8	lithium chloride	List III
-----------	------------------	----------

SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

57-55-6 Propylene glycol

LC50/96h	40,613 mg/l (Oncorhynchus mykiss (Regenbogenforelle))
----------	---

LC50	40,613 mg/l (Oncorhynchus mykiss (Regenbogenforelle))
------	---

2634-33-5 1,2-benzisothiazol-3(2H)-one [EC no. 220-120-9]

EC 50/48h	3.27 mg/l (Daphnie)
-----------	---------------------

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable
- **vPvB:** Not applicable
- **12.6 Endocrine disrupting properties**
For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**
Water hazard class (Germany) 2 (Self-assessment): hazardous for water.
Do not allow product to reach ground water, water bodies or sewage system.
Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**

- **Recommendation**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- **Uncleaned packagings:**

- **Recommendation:** Disposal must be made according to official regulations.

- **Recommended cleaning agent:** Water, if necessary with cleaning agent.

SECTION 14: Transport information

- **14.1 UN number or ID number**

- **ADR, IMDG, IATA**

Void

(Contd. on page 7)

Safety data sheet according to UK REACH

Printing date 16.06.2026

Version number 6

Revision: 16.06.2026

Trade name DesignCoat PU 40 Komp. A

(Contd. of page 6)

· 14.2 UN proper shipping name · ADR, IMDG, IATA	Void
· 14.3 Transport hazard class(es) · ADR, ADN, IMDG, IATA · Class	Void
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user	Not applicable
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable
· UN "Model Regulation":	Void

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Poisons Act**

· **Regulated explosives precursors**

None of the ingredients is listed.

· **Regulated poisons**

None of the ingredients is listed.

· **Reportable explosives precursors**

None of the ingredients is listed.

· **Reportable poisons**

1310-58-3	potassium hydroxide	17% of total caustic alkalinity
-----------	---------------------	---------------------------------

- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H310 Fatal in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- EUH071 Corrosive to the respiratory tract.

(Contd. on page 8)

Safety data sheet according to UK REACH

Printing date 16.06.2026

Version number 6

Revision: 16.06.2026

Trade name DesignCoat PU 40 Komp. A

(Contd. of page 7)

· **Contact:** chemikalieninfo@murexin.com (+43 02622/27401)

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 2: Acute toxicity – Category 2

Skin Corr. 1C: Skin corrosion/irritation – Category 1C

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

Skin Sens. 1B: Skin sensitisation – Category 1B

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

· *** Data compared to the previous version altered.**

GB