Printing date 04.05.2023 Version number 1 Revision: 04.05.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name DICHTUNGSSCHLÄMME DS 28
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Thickener pulps
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

MUREXIN GmbH

Franz v. Furtenbachstr. 1 A-2700 Wiener Neustadt Tel.: +43 (0)2622/27401

- · Informing department: chemikalieninfo@murexin.com
- · 1.4 Emergency telephone number:

UK National poisons Emergency number.: +44 (0) 870 600 6266

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



corrosion

Eye Dam. 1 H318 Causes serious eye damage.



Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H335 May cause respiratory irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms





GHS05 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

Cement portland, Low-chromate according to EU-VO 1907/2006 (REACH)

Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage. H335 May cause respiratory irritation.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

(Contd. on page 2)

Printing date 04.05.2023 Version number 1 Revision: 04.05.2023

Trade name DICHTUNGSSCHLÄMME DS 28

(Contd. of page 1)

P362+P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description:

Mixture consisting of the following components with harmless additives. Zement-Mörtelmischung

Dangerous components:

CAS: 65997-15-1 EINECS: 266-043-4

Cement portland, Low-chromate according to EU-VO 1907/2006 25-50%

(REACH)

📀 Eye Dam. 1, H318

Skin Irrit. 2, H315; STOT SE 3, H335

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information Instantly remove any clothing soiled by the product.
- · After inhalation

In case of unconsciousness bring patient into stable side position for transport.

Supply fresh air; consult doctor in case of symptoms.

After skin contact

Instantly wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

- · After eye contact Rinse opened eye for several minutes under running water. Then consult doctor.
- After swallowing

Rinse out mouth and then drink plenty of water.

In case of persistent symptoms consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents Use fire fighting measures that suit the environment.
- 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective clothing.
- · 6.2 Environmental precautions: Do not allow product to reach sewage system or water bodies.

(Contd. on page 3)

Printing date 04.05.2023 Version number 1 Revision: 04.05.2023

Trade name DICHTUNGSSCHLÄMME DS 28

(Contd. of page 2)

6.3 Methods and material for containment and cleaning up:

Use neutralising agent.

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Thorough dedusting.

Keep containers tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of dust.

- · Information about protection against explosions and fires: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- · Requirements to be met by storerooms and containers: Store only in the original container.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions:

Keep container tightly sealed.

Store under dry conditions.

- · Storage class 11
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with critical values that require monitoring at the workplace:

65997-15-1 Cement portland, Low-chromate according to EU-VO 1907/2006 (REACH)

WEL Long-term value: 10* 4** mg/m³
*inhalable dust **respirable dust

- · Additional information: The lists that were valid during the compilation were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures

The usual precautionary measures should be adhered to in handling the chemicals.

Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air. Filter P2.

· Hand protection

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 4)

Printing date 04.05.2023 Version number 1 Revision: 04.05.2023

Trade name DICHTUNGSSCHLÄMME DS 28

(Contd. of page 3)

· Material of gloves

Use gloves of stable material (e.g. Nitrile) - if necessary tricoted to improve the wearability. The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye/face protection Gauze goggles
- · Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state

· Colour: According to product specification

· Smell: Not distinguishable · Odour threshold: Not determined. · Melting point/freezing point: Not determined

Boiling point or initial boiling point and

boiling range Not determined · Flammability Not determined. · Flash point: >100 °C

Decomposition temperature: Not determined.

pH at 20 °C 11.4

Viscosity:

· Kinematic viscosity Not applicable. Not applicable. dynamic:

Solubility

Soluble Water:

· Partition coefficient n-octanol/water (log

Not determined. value) Steam pressure: Not applicable.

Density and/or relative density

1.3 g/cm3 Density at 20 °C Not determined. Relative density Not applicable. Vapour density

9.2 Other information

Appearance:

· Form: Powder

· Important information on protection of health and environment, and on safety.

· Self-inflammability: Product is not selfigniting.

Explosive properties:

Product is not explosive. · Solvent content:

100.0 %

· Solids content: · Change in condition

· Evaporation rate Not applicable.

· Information with regard to physical hazard

classes · Explosives Void · Flammable gases Void · Aerosols Void Void Oxidising gases Gases under pressure Void

(Contd. on page 5)

Printing date 04.05.2023 Version number 1 Revision: 04.05.2023

Trade name DICHTUNGSSCHLÄMME DS 28

		(Contd. of page 4)
· Flammable liquids	Void	
· Flammable solids	Void	
· Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
· Substances and mixtures, which emit		
flammable gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
· Organic peroxides	Void	
Corrosive to metals	Void	
· Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- · Conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: None

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye damage.
- · STOT-single exposure May cause respiratory irritation.
- 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

(Contd. on page 6)

Printing date 04.05.2023 Version number 1 Revision: 04.05.2023

Trade name DICHTUNGSSCHLÄMME DS 28

(Contd. of page 5)

Water hazard class (Germany) 1 (Self-assessment): slightly hazardous for water. Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- Recommended cleaning agent: Water, if necessary with cleaning agent.

SECTION 14: Transport information	
14.1 UN number or ID number ADR, IMDG, IATA	Void
14.2 UN proper shipping name ADR, IMDG, IATA	Void
14.3 Transport hazard class(es)	
· ADR, ADN, IMDG, IATA · Class	Void
14.4 Packing group ADR, IMDG, IATA	Void
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user	Not applicable.
14.7 Maritime transport in bulk according IMO instruments	ng to Not applicable.
UN "Model Regulation":	Void

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

(Contd. on page 7)

Printing date 04.05.2023 Version number 1 Revision: 04.05.2023

Trade name DICHTUNGSSCHLÄMME DS 28

(Contd. of page 6)

· Contact: chemikalieninfo@murexin.com (+43 02622/27401)

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

* Data compared to the previous version altered.