Revision: 23.09.2021

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.09.2021

Version number 3 (replaces version 2)

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name DURLIN HOLZLASUR HL 2500
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Wood protection glazing
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MUREXIN GmbH

Franz v. Furtenbachstr. 1 A-2700 Wiener Neustadt Tel.: +43 (0)2622/27401

- · Informing department: chemikalieninfo@murexin.com
- · 1.4 Emergency telephone number:

UK National poisons Emergency number.: +44 (0) 870 600 6266

## SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



GHS07

- · Signal word Warning
- · Hazard-determining components of labelling:

Hydrotreated heavy Naphtha

· Hazard statements

H336 May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P271 Use only outdoors or in a well-ventilated area.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

Contains 2-butanone oxime, cobalt(II) 2-ethylhexanoate. May produce an allergic reaction.

- 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.

(Contd. on page 2)

Printing date 23.09.2021 Version number 3 (replaces version 2) Revision: 23.09.2021

### Trade name DURLIN HOLZLASUR HL 2500

· vPvB: Not applicable.

(Contd. of page 1)

## **SECTION 3: Composition/information on ingredients**

- · 3.2 Mixtures
- · Description: Mixture consisting of the following components with harmless additives.

Dangerous components:		
EC number: 919-857-5	Hydrotreated heavy Naphtha  Flam. Liq. 3, H226  Asp. Tox. 1, H304  TSTOT SE 3, H336	25-50%
CAS: 96-29-7 EINECS: 202-496-6	2-butanone oxime Acute Tox. 3, H301 Carc. 1B, H350; STOT SE 1, H370; STOT RE 2, H373 Eye Dam. 1, H318 Acute Tox. 4, H312; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H336 ATE: LD50 oral: 100 mg/kg LD50 dermal: 1,100 mg/kg	<0.5%
CAS: 136-52-7 EINECS: 205-250-6 Reg.nr.: 01-2119524678-2	cobalt(II) 2-ethylhexanoate  Acute Tox. 4, H302; Skin Sens. 1, H317	<0.5%

## SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After skin contact Instantly wash with water and soap and rinse thoroughly.
- · After eye contact Rinse opened eye for several minutes under running water.
- · After swallowing In case of persistent symptoms consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

## SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

- · 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

## SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Wear protective clothing.
- · 6.2 Environmental precautions: Do not allow product to reach sewage system or water bodies.
- **6.3 Methods and material for containment and cleaning up:**Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose of contaminated material as waste according to item 13.

(Contd. on page 3)

(Contd. of page 2)

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.09.2021 Version number 3 (replaces version 2) Revision: 23.09.2021

### Trade name DURLIN HOLZLASUR HL 2500

· 6.4 Reference to other sections

No dangerous materials are released.

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

## SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling No special precautions necessary if used correctly.
- · Information about protection against explosions and fires: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage
- · Requirements to be met by storerooms and containers: Store only in the original container.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class 10
- · 7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with critical values that require monitoring at the workplace:

## 136-52-7 cobalt(II) 2-ethylhexanoate

WEL Long-term value: 0.1 mg/m3

as Co; Carc, Sen

- · Additional information: The lists that were valid during the compilation were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures

The usual precautionary measures should be adhered to in handling the chemicals.

Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

- · Breathing equipment: Breathing protection recommended.
- · Hand protection Protective gloves.
- · Material of gloves

Use gloves of stable material (e.g. Nitrile) - if necessary tricoted to improve the wearability.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye/face protection Safety glasses recommended during refilling.
- · Body protection: Protective work clothing.

## SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information

· Colour: According to product specification

· Smell: Type specific

· Melting point/freezing point: n.b. °C

(Contd. on page 4)

Printing date 23.09.2021 Version number 3 (replaces version 2) Revision: 23.09.2021

### Trade name DURLIN HOLZLASUR HL 2500

(Contd. of page 3)

· Lower and up	pper exp	losion l	imit
----------------	----------	----------	------

· Lower: 0.6 Vol %
· Upper: 7.0 Vol %
· Flash point: 62 °C

· **Self-inflammability:** Product is not selfigniting.

· Viscosity:

· Kinematic viscosity at 20 °C 18 s (DIN 53211/4)

· Solubility

• Water: immiscible
• Steam pressure at 20 °C: 0.17 mbar

· Density and/or relative density

Density at 20 °C 0.9 g/cm³

· 9.2 Other information

· Appearance:

Form: Fluid Important information on protection of health

and environment, and on safety.

Ignition temperature: >230 °C

• Explosive properties: Product is not explosive.

## · Information with regard to physical hazard

classes Void · Explosives Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void Flammable liquids Void Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void Pyrophoric solids Void Self-heating substances and mixtures Void Substances and mixtures, which emit flammable gases in contact with water

flammable gases in contact with water

Oxidising liquids
Oxidising solids
Organic peroxides
Corrosive to metals
Ovoid
Desensitised explosives
Void

## SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: None

GB

Printing date 23.09.2021 Version number

Version number 3 (replaces version 2)

### Trade name DURLIN HOLZLASUR HL 2500

(Contd. of page 4)

Revision: 23.09.2021

## SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values that are relevant for classification:

#### 96-29-7 2-butanone oxime

Oral | LD50 | 100 mg/kg (ATE) Dermal | LD50 | 1,100 mg/kg (ATE)

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

## SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class (Germany) 1 (Self-assessment): slightly hazardous for water.

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

## SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

GB

Printing date 23.09.2021 Version number 3 (replaces version 2) Revision: 23.09.2021

Trade name DURLIN HOLZLASUR HL 2500

(Contd. of page 5)

14.1 UN number or ID number		
ADR, ADN, IMDG, IATA	Void	
14.2 UN proper shipping name		
ADR, ADN, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA		
Class	Void	
14.4 Packing group		
ADR, IMDG, IATA	Void	
14.5 Environmental hazards:		
Marine pollutant:	No	
14.6 Special precautions for user	Not applicable.	
14.7 Maritime transport in bulk accordi	ng to	
IMO instruments	Not applicable.	

## **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### · Relevant phrases

H226 Flammable liquid and vapour.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H336 May cause drowsiness or dizziness.

H350 May cause cancer.

H370 Causes damage to organs.

H373 May cause damage to organs through prolonged or repeated exposure.

- · Contact: chemikalieninfo@murexin.com (+43 02622/27401)
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

(Contd. on page 7)

Printing date 23.09.2021

Version number 3 (replaces version 2)

### Trade name DURLIN HOLZLASUR HL 2500

(Contd. of page 6)

Revision: 23.09.2021

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids — Category 3 Acute Tox. 3: Acute toxicity — Category 4 Skin Irrit. 2: Skin corrosion/irritation — Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation – Category 1 Carc. 1B: Carcinogenicity – Category 1B

STOT SE 1: Specific target organ toxicity (single exposure) – Category 1 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

GB

<sup>\*</sup> Data compared to the previous version altered.