Printing date 23.09.2021

Revision: 23.09.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- [•] 1.1 Product identifier
- · Trade name DURLIN MALERLACK KHX 50 SEIDENMATT
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- · Application of the substance / the mixture Lacquer
- · 1.3 Details of the supplier of the safety data sheet
- *Manufacturer/Supplier:* MUREXIN GmbH Franz v. Furtenbachstr. 1 A-2700 Wiener Neustadt Tel.: +43 (0)2622/27401
- · Informing department: chemikalieninfo@murexin.com
- 1.4 Emergency telephone number:
- UK National poisons Emergency number.: +44 (0) 870 600 6266

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture
 Classification according to Regulation (EC) No 1272/2008

flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



STOT SE 3 H336 May cause drowsiness or dizziness.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the CLP regulation.
- Hazard pictograms



· Signal word Warning

· Hazard statements

H226 Flammable liquid and vapour.

- H336 May cause drowsiness or dizziness.
- Precautionary statements
- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P103 Read carefully and follow all instructions.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- P501 Dispose of contents/container in accordance with local/regional/national/ international regulations.

(Contd. on page 2)

GB

Printing date 23.09.2021

Version number 6 (replaces version 5)

Revision: 23.09.2021

Trade name DURLIN MALERLACK KHX 50 SEIDENMATT

(Contd. of page 1)

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Contains 2-butanone oxime, phthalic anhydride, cobalt(II) 2-ethylhexanoate. May produce an allergic reaction.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture consisting of the following components with harmless additives.

· Dangerous components:	Nonhtha (natroloum) budratroated boous	10 250/
CAS: 64742-48-9 EINECS: 265-150-3 Reg.nr.: 01-2119457273-39	Naphtha (petroleum), hydrotreated heavy Flam. Liq. 3, H226 Asp. Tox. 1, H304	10-25%
EC number: 918-481-9 Reg.nr.: 01-2119457273-39- xxxx	NAPHTA (petroleum), hydrotreated heavy	2.5-5%
CAS: 96-29-7 EINECS: 202-496-6	 2-butanone oxime Acute Tox. 3, H301 Carc. 1B, H350; STOT SE 1, H370; STOT RE 2, H373 Eye Dam. 1, H318 Acute Tox. 4, H312; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H336 ATE: LD50 oral: 100 mg/kg LD50 dermal: 1,100 mg/kg 	0.5-1%
CAS: 85-44-9 EINECS: 201-607-5	 <i>phthalic anhydride</i> № Resp. Sens. 1, H334 <i>Eye Dam.</i> 1, H318 ↑ Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335 	<0.5%
CAS: 136-52-7 EINECS: 205-250-6 Reg.nr.: 01-2119524678-29	cobalt(II) 2-ethylhexanoate	<0.5%

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- After skin contact Instantly wash with water and soap and rinse thoroughly.
- After eye contact
- Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.
- · After swallowing Drink copious amounts of water and provide fresh air. Instantly call for doctor.
- 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.

• **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

(Contd. on page 3)

Printing date 23.09.2021

Version number 6 (replaces version 5)

Revision: 23.09.2021

Trade name DURLIN MALERLACK KHX 50 SEIDENMATT

(Contd. of page 2)

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

Suitable extinguishing agents

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

- For safety reasons unsuitable extinguishing agents Water with a full water jet.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or water bodies.

Prevent material from reaching sewage system, holes and cellars.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling Keep containers tightly sealed.

- Information about protection against explosions and fires:
- Keep ignition sources away Do not smoke.

Protect against electrostatic charges.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage

• Requirements to be met by storerooms and containers: Store only in the original container.

- Information about storage in one common storage facility:
- Do not store together with reducing agents, heavy-metal compounds, acids and alkalis.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

• Components with critical values that require monitoring at the workplace:

136-52-7 cobalt(II) 2-ethylhexanoate

WEL Long-term value: 0.1 mg/m³

as Co; Carc, Sen

· Additional information: The lists that were valid during the compilation were used as basis.

[•] 8.2 Exposure controls

• Appropriate engineering controls No further data; see item 7.

(Contd. on page 4)

⁻ GB

Printing date 23.09.2021

Version number 6 (replaces version 5)

Revision: 23.09.2021

Trade name DURLIN MALERLACK KHX 50 SEIDENMATT

Self-reactive substances and mixtures

(Contd. of page 3) · Individual protection measures, such as personal protective equipment General protective and hygienic measures The usual precautionary measures should be adhered to in handling the chemicals. Keep away from foodstuffs, beverages and food. Instantly remove any soiled and impregnated garments. Wash hands during breaks and at the end of the work. · Breathing equipment: Use breathing protection in case of insufficient ventilation. · Hand protection Protective gloves. · Material of gloves Use gloves of stable material (e.g. Nitrile) - if necessary tricoted to improve the wearability. · Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. Eye/face protection Safety glasses · Body protection: Protective work clothing. SECTION 9: Physical and chemical properties · 9.1 Information on basic physical and chemical properties · General Information · Colour: According to product specification Characteristic · Smell: · Boiling point or initial boiling point and 107 °C boiling range Lower and upper explosion limit 0.6 Vol % · Lower: 7.0 Vol % · Upper: 36 °C · Flash point: · Self-inflammability: Product is not selfigniting. · Viscosity: · dynamic at 20 °C: 1500 mPas Solubility immiscible Water: Steam pressure at 20 °C: 1 hPa Density and/or relative density Density at 20 °C 1.3 g/cm³ · 9.2 Other information · Appearance: · Form: Fluid · Important information on protection of health and environment, and on safety. · Ignition temperature: 240 °C · Explosive properties: Product is not explosive. However, formation of explosive air/steam mixtures is possible. · Information with regard to physical hazard classes · Explosives Void Flammable gases Void · Aerosols Void Oxidising gases Void Gases under pressure Void · Flammable liquids Flammable liquid and vapour. Void · Flammable solids

Void

(Contd. on page 5)

[–] GB

Printing date 23.09.2021

Version number 6 (replaces version 5)

Revision: 23.09.2021

Trade name DURLIN MALERLACK KHX 50 SEIDENMATT

		(Contd. of page 4
· Pyrophoric liquids	Void	
· Pyrophoric solids	Void	
· Self-heating substances and mixtures	Void	
[·] Substances and mixtures, which emit		
flammable gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
· Corrosive to metals	Void	
· Desensitised explosives	Void	

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

10.2 Chemical stability

· Conditions to be avoided: No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions No dangerous reactions known

• 10.4 Conditions to avoid No further relevant information available.

- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: None

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:

64742-48-9 Naphtha (petroleum), hydrotreated heavy

Oral LD50 >2,000 mg/kg (rat)

Dermal LD50 >2,000 mg/kg (rabbit)

NAPHTA (petroleum), hydrotreated heavy

Oral LD50 >2,000 mg/kg (rat)

Dermal LD50 >2,000 mg/kg (rabbit)

96-29-7 2-butanone oxime

Oral LD50 100 mg/kg (ATE)

Dermal LD50 1,100 mg/kg (ATE)

Skin corrosion/irritation Based on available data, the classification criteria are not met.

· Serious eye damage/irritation Based on available data, the classification criteria are not met.

· Germ cell mutagenicity Based on available data, the classification criteria are not met.

• Carcinogenicity Based on available data, the classification criteria are not met.

- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- STOT-single exposure
- May cause drowsiness or dizziness.

• STOT-repeated exposure Based on available data, the classification criteria are not met.

- · Aspiration hazard Based on available data, the classification criteria are not met.
- [.] 11.2 Information on other hazards

• Endocrine disrupting properties

None of the ingredients is listed.

(Contd. on page 6)

GR

Printing date 23.09.2021

Version number 6 (replaces version 5)

Revision: 23.09.2021

Trade name DURLIN MALERLACK KHX 50 SEIDENMATT

(Contd. of page 5)

	^r oxicity tic toxicity:
-	-
	2-48-9 Naphtha (petroleum), hydrotreated heavy
	>100 mg/l (Pseudokirchneriella subcapitata (Alge))
LC50	>100 mg/l (Oncorhynchus mykiss (Regenbogenforelle))
NAPH	ITA (petroleum), hydrotreated heavy
IC 50	>100 mg/l (Pseudokirchneriella subcapitata (Alge))
LC50	>100 mg/l (Oncorhynchus mykiss (Regenbogenforelle))
12.2 F	Persistence and degradability No further relevant information available.
12.3 E	Bioaccumulative potential No further relevant information available.
12.4 N	<i>lobility in soil</i> No further relevant information available.
12.5 F	Results of PBT and vPvB assessment
	Not applicable.
	: Not applicable.
	Endocrine disrupting properties
	formation on endocrine disrupting properties see section 11.
	Other adverse effects
	ional ecological information:
	ral notes:
Water	hazard class (Germany) 1 (Self-assessment): slightly hazardous for water.

Water hazard class (Germany) 1 (Self-assessment): slightly hazardous for water. Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

· Recommendation: Disposal must be made according to official regulations.

14.1 UN number or ID number		
ADR, ADN, IMDG	Void	
ΙΑΤΑ	UN1263	
14.2 UN proper shipping name		
ADR, ADN, IMDG	Void	
IATA	PAINT	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG		
Class	Void	

Printing date 23.09.2021

Version number 6 (replaces version 5)

Revision: 23.09.2021

Trade name DURLIN MALERLACK KHX 50 SEIDENMATT

		(Contd. of page
ΙΑΤΑ		
V Class	3 Flammable liquids.	
Label	3	
14.4 Packing group		
ADR, IMDG	Void	
IATA	<i>III</i>	
14.5 Environmental hazards:		
Marine pollutant:	No	
14.6 Special precautions for user	Not applicable.	
14.7 Maritime transport in bulk accordi	ing to	
IMO instruments	Not applicable.	
UN "Model Regulation":	Void	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P5c FLAMMABLE LIQUIDS

• Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H226 Flammable liquid and vapour.
- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H350 May cause cancer.
- H370 Causes damage to organs.
- H373 May cause damage to organs through prolonged or repeated exposure.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Contact: chemikalieninfo@murexin.com (+43 02622/27401)

(Contd. on page 8)

GB

Printing date 23.09.2021

Version number 6 (replaces version 5)

Revision: 23.09.2021

Trade name DURLIN MALERLACK KHX 50 SEIDENMATT

(Contd. of page	э7
· Abbreviations and acronyms:	
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulatio	on
Concerning the International Transport of Dangerous Goods by Rail)	
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)	
ICAO: International Civil Aviation Organisation	
ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)	
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concern	ninę
the International Carriage of Dangerous Goods by Road)	
IMDG: International Maritime Code for Dangerous Goods	
IATA: International Air Transport Association	
GHS: Globally Harmonised System of Classification and Labelling of Chemicals	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
Flam. Liq. 3: Flammable liquids – Category 3	
Acute Tox. 3: Acute toxicity – Category 3	
Acute Tox. 4: Acute toxicity – Category 4	
Skin Irrit. 2: Skin corrosion/irritation – Category 2	
Eye Dam. 1: Serious eye damage/eye irritation – Category 1	
Resp. Sens. 1: Respiratory sensitisation – Category 1	
Skin Sens. 1: Skin sensitisation – Category 1	
Carc. 1B: Carcinogenicity – Category 1B	
STOT SE 1: Specific target organ toxicity (single exposure) – Category 1	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2	
Asp. Tox. 1: Aspiration hazard – Category 1	
• * Data compared to the previous version altered.	
	-0