Printing date 23.09.2021 Version number 4 (replaces version 3) Revision: 23.09.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name DURLIN VENTILACK VLX 50
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Lacquer
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MUREXIN GmbH

Franz v. Furtenbachstr. 1 A-2700 Wiener Neustadt Tel.: +43 (0)2622/27401

- · Informing department: chemikalieninfo@murexin.com
- · 1.4 Emergency telephone number:

UK National poisons Emergency number.: +44 (0) 870 600 6266

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



STOT SE 3 H336 May cause drowsiness or dizziness.

- 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 GHS07

- · Signal word Warning
- · Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P243 Take action to prevent static discharges.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

(Contd. on page 2)

Printing date 23.09.2021 Version n

Version number 4 (replaces version 3)

Trade name DURLIN VENTILACK VLX 50

(Contd. of page 1)

Revision: 23.09.2021

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Contains 2-butanone oxime, phthalic anhydride, cobalt(II) 2-ethylhexanoate. May produce an allergic reaction.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- Description: Mixture consisting of the following components with harmless additives.

D		
Dangerous components:		
CAS: 64742-48-9 EINECS: 265-150-3 Reg.nr.: 01-2119457273-39	Naphtha (petroleum), hydrotreated heavy Flam. Liq. 3, H226 Asp. Tox. 1, H304	10-25%
CAS: 68551-17-7	alkanes, C10-13-iso- ♦ Asp. Tox. 1, H304	5-10%
CAS: 96-29-7 EINECS: 202-496-6	2-butanone oxime Acute Tox. 3, H301 Carc. 1B, H350; STOT SE 1, H370; STOT RE 2, H373 Eye Dam. 1, H318 Acute Tox. 4, H312; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H336 ATE: LD50 oral: 100 mg/kg LD50 dermal: 1,100 mg/kg	0.5-1%
CAS: 85-44-9 EINECS: 201-607-5	phthalic anhydride Resp. Sens. 1, H334 Eye Dam. 1, H318 Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	<0.5%
CAS: 136-52-7 EINECS: 205-250-6 Reg.nr.: 01-2119524678-29	cobalt(II) 2-ethylhexanoate Acute Tox. 4, H302; Skin Sens. 1, H317	<0.5%

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information Instantly remove any clothing soiled by the product.
- · After skin contact Instantly wash with water and soap and rinse thoroughly.
- After eye contact Rinse opened eye for several minutes under running water.
- · After swallowing In case of persistent symptoms consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**No further relevant information available.
- · Danger Danger of pulmonary oedema.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

GB

Printing date 23.09.2021 Version number 4 (replaces version 3) Revision: 23.09.2021

Trade name DURLIN VENTILACK VLX 50

(Contd. of page 2)

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

- · For safety reasons unsuitable extinguishing agents Water with a full water jet.
- · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained breathing apparatus.
- Additional information

Cool endangered containers with water spray jet.

Collect contaminated fire fighting water separately. It must not enter drains.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

Wear protective clothing.

6.2 Environmental precautions:

Do not allow product to reach sewage system or water bodies.

Prevent material from reaching sewage system, holes and cellars.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Keep containers tightly sealed.
- · Information about protection against explosions and fires:

Fumes can combine with air to form an explosive mixture.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- Requirements to be met by storerooms and containers: Store only in the original container.
- Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidising agents.

· Further information about storage conditions:

Store container in a well ventilated position.

Keep container tightly sealed.

- · Storage class 3
- · 7.3 Specific end use(s) No further relevant information available.

GB

Printing date 23.09.2021 Version number 4 (replaces version 3) Revision: 23.09.2021

Trade name DURLIN VENTILACK VLX 50

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with critical values that require monitoring at the workplace:

136-52-7 cobalt(II) 2-ethylhexanoate

WEL Long-term value: 0.1 mg/m³ as Co; Carc, Sen

- · Additional information: The lists that were valid during the compilation were used as basis.
- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see item 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures

Do not eat or drink while working.

The usual precautionary measures should be adhered to in handling the chemicals.

Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

- · Breathing equipment: Not required.
- · Hand protection Protective gloves.
- · Material of gloves

Use gloves of stable material (e.g. Nitrile) - if necessary tricoted to improve the wearability.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye/face protection Safety glasses recommended during refilling.
- · Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information

· Colour: According to product specification

· Smell: Type specific

· Melting point/freezing point: n.b. °C

· Boiling point or initial boiling point and

boiling range Not determined

· Lower and upper explosion limit

Lower: 0.6 Vol %
 Upper: 7.0 Vol %
 Flash point: 36 °C

· **Self-inflammability:** Product is not selfigniting.

· Viscosity:

· dynamic at 20 °C: 1500 mPas

· Solubility

· Water: immiscible · Steam pressure at 20 °C: 1 hPa

Density and/or relative density

Density at 20 °C 1.3 g/cm³

· 9.2 Other information

· Appearance:

· Form: Fluid

(Contd. on page 5)

Printing date 23.09.2021 Version number 4 (replaces version 3) Revision: 23.09.2021

Trade name DURLIN VENTILACK VLX 50

(Contd. of page 4)

· Important information on protection of health
and environment, and on safety.

235 °C · Ignition temperature:

· Explosive properties: Product is not explosive. However, formation of

explosive air/steam mixtures is possible.

· Solvent separation test <3 %

· Information with regard to physical hazard classes

· Explosives Void · Flammable gases Void · Aerosols Void Oxidising gases Void · Gases under pressure Void

· Flammable liquids

Flammable liquid and vapour. Flammable solids Void Self-reactive substances and mixtures Void · Pyrophoric liquids Void Pyrophoric solids Void Self-heating substances and mixtures Void Substances and mixtures, which emit flammable gases in contact with water Void Oxidising liquids Void Oxidising solids Void · Organic peroxides Void · Corrosive to metals Void Desensitised explosives Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:					
64742-4	742-48-9 Naphtha (petroleum), hydrotreated heavy				
Oral	LD50	>2,000 mg/kg (rat)			
Dermal	LD50	>2,000 mg/kg (rabbit)			
96-29-7	96-29-7 2-butanone oxime				
Oral	LD50	100 mg/kg (ATE)			
Dermal	LD50	1,100 mg/kg (ATE)			

· Skin corrosion/irritation Based on available data, the classification criteria are not met.

(Contd. on page 6)

Printing date 23.09.2021 Version number 4 (replace

Version number 4 (replaces version 3) Revision: 23.09.2021

Trade name DURLIN VENTILACK VLX 50

(Contd. of page 5)

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) -
- 11.2 Information on other hazards
- Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

64742-48-9 Naphtha (petroleum), hydrotreated heavy

IC 50 >100 mg/l (Pseudokirchneriella subcapitata (Alge))

LC50 >100 mg/l (Oncorhynchus mykiss (Regenbogenforelle))

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class (Germany) 1 (Self-assessment): slightly hazardous for water.

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

- · 14.1 UN number or ID number
- · ADR, ADN

Void

· IMDG, IATA

UN1263

(Contd. on page 7)

Printing date 23.09.2021 Version number 4 (replaces version 3) Revision: 23.09.2021

Trade name DURLIN VENTILACK VLX 50

		(Contd. of pag
14.2 UN proper shipping name		
ADR, ADN	Void	
IMDG, IATA	PAINT	
14.3 Transport hazard class(es)		
ADR, ADN		
Class	Void	
IMDG, IATA		
Class	3 Flammable liquids.	
Label	3	
14.4 Packing group		
ADR	Void	
IMDG, IATA	III	
14.5 Environmental hazards:		
Marine pollutant:	No	
14.6 Special precautions for user	Not applicable.	
EMS Number:	F-E,S-E	
Stowage Category	A	
<u> </u>	ing to	
14.7 Maritime transport in bulk accordi IMO instruments		
INO INSTRUMENTS	Not applicable.	
UN "Model Regulation":	Void	

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

(Contd. on page 8)

Printing date 23.09.2021

Version number 4 (replaces version 3)

Trade name DURLIN VENTILACK VLX 50

(Contd. of page 7)

Revision: 23.09.2021

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H350 May cause cancer.

H370 Causes damage to organs.

H373 May cause damage to organs through prolonged or repeated exposure.

· Contact: chemikalieninfo@murexin.com (+43 02622/27401)

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Carc. 1B: Carcinogenicity - Category 1B

STOT SE 1: Specific target organ toxicity (single exposure) - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

* Data compared to the previous version altered.

GB