Printing date 28.01.2025 Version number 6 Revision: 28.01.2025

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name EMULPLAST BIO MALERFARBE KA 1500
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Dispersion
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MUREXIN GmbH

Franz v. Furtenbachstr. 1 A-2700 Wiener Neustadt Tel.: +43 (0)2622/27401

- · Informing department: chemikalieninfo@murexin.com
- · 1.4 Emergency telephone number:

UK National poisons Emergency number.: +44 (0) 870 600 6266

### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



Skin Sens. 1 H317 May cause an allergic skin reaction.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms



GHS07

- · Signal word Warning
- · Hazard-determining components of labelling:

2-Methyl-2H-isothiazol-3-one [EC no. 220-239-6]

1,2-benzisothiazol-3(2H)-one [EC no. 220-120-9]

· Hazard statements

H317 May cause an allergic skin reaction.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.
P261 Avoid breathing mist/vapours/spray.
P280 Wear protective gloves / eye protection.
P302+P352 IF ON SKIN: Wash with plenty of water.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.

(Contd. on page 2)

Printing date 28.01.2025 Version number 6 Revision: 28.01.2025

#### Trade name EMULPLAST BIO MALERFARBE KA 1500

· vPvB: Not applicable.

(Contd. of page 1)

#### SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · **Description:** Mixture consisting of the following components with harmless additives.

· Dangerous compoi	nents:	
CAS: 1317-65-3 EINECS: 215-279-6	Calciumcarbonat	25-50%
	substance with a Community workplace exposure limit	
CAS: 1332-58-7	kaolin	2.5-5%
	substance with a Community workplace exposure limit	
CAS: 2634-33-5	1,2-benzisothiazol-3(2H)-one [EC no. 220-120-9] <0.1	<0.1%
EINECS: 220-120-9	Acute Tox. 2, H330 Eye Dam. 1, H318 Aquatic Acute 1, H400 Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317 ATE: LD50 oral: 450 mg/kg LC50/4 h inhalative: 0.21 mg/l Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.036 %	
CAS: 2682-20-4 EINECS: 220-239-6	2-Methyl-2H-isothiazol-3-one [EC no. 220-239-6]  Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330  Skin Corr. 1B, H314; Eye Dam. 1, H318  Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1)  Skin Sens. 1A, H317  EUH071  Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.0015 %	<0.025%

### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information No special measures required.
- · After skin contact

Instantly wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

- · After eye contact Rinse opened eye for several minutes under running water.
- After swallowing

Rinse out mouth and then drink plenty of water.

In case of persistent symptoms consult doctor.

- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- · **4.3 Indication of any immediate medical attention and special treatment needed**No further relevant information available.

### SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents Use fire fighting measures that suit the environment.
- 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

(Contd. on page 3)

Printing date 28.01.2025 Version number 6 Revision: 28.01.2025

#### Trade name EMULPLAST BIO MALERFARBE KA 1500

(Contd. of page 2)

- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

#### SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective clothing.
- 6.2 Environmental precautions:

Do not allow product to reach sewage system or water bodies.

Dilute with much water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· 6.4 Reference to other sections

No dangerous materials are released.

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

## SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling No special measures required.
- · Information about protection against explosions and fires: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage
- · Requirements to be met by storerooms and containers: Store only in the original container.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Protect from frost.

Keep container tightly sealed.

- · Storage class 12
- · 7.3 Specific end use(s) No further relevant information available.

# SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Components with critical values that require monitoring at the workplace:

## 1317-65-3 Calciumcarbonat

WEL Long-term value: 10\* 4\*\* mg/m³
\*inhalable dust; \*\*respirable

1332-58-7 kaolin

WEL Long-term value: 2 mg/m<sup>3</sup>

- · Additional information: The lists that were valid during the compilation were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures

The usual precautionary measures should be adhered to in handling the chemicals.

Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

· Breathing equipment: Only during spraying without adequate removal by suction.

(Contd. on page 4)

Printing date 28.01.2025 Version number 6 Revision: 28.01.2025

#### Trade name EMULPLAST BIO MALERFARBE KA 1500

(Contd. of page 3)

#### · Hand protection

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Use gloves of stable material (e.g. Nitrile) - if necessary tricoted to improve the wearability.

#### · Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye/face protection Safety glasses
- · Body protection: Protective work clothing.

· 9.1 Information on basic physic	al and chemical properties
-----------------------------------	----------------------------

· General Information

· Colour: White

· Smell: Characteristic

· Boiling point or initial boiling point and

boiling range 100 °C (7732-18-5 water, distilled, conductivity or

of similar purity)

· Lower and upper explosion limit

Lower: Not determined.
Upper: Not determined.
Flash point: Not applicable

· pH at 20 °C

· Viscosity:

dynamic at 20 °C: 15800 mPas

· Solubility

· Water: Partly miscible

• Steam pressure at 20 °C: 23 hPa (7732-18-5 water, distilled, conductivity or

of similar purity)

· Density and/or relative density

· Density at 20 °C 1.5 g/cm³

#### · 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health

and environment, and on safety.

Self-inflammability: Product is not selfigniting.
 Explosive properties: Product is not explosive.

# Information with regard to physical hazard

classes · Explosives Void · Flammable gases Void Void · Aerosols · Oxidising gases Void Gases under pressure Void · Flammable liquids Void · Flammable solids Void Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void

(Contd. on page 5)

Printing date 28.01.2025 Version number 6 Revision: 28.01.2025

#### Trade name EMULPLAST BIO MALERFARBE KA 1500

		(Contd. of page 4
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit		
flammable gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

## SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- · Conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: None

# **SECTION 11: Toxicological information**

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	values tha	t are relevant for classification:
1317-65-3	Calciumo	carbonat
Oral	LD50	>5,000 mg/kg (rat)
2634-33-5	1,2-benzi	sothiazol-3(2H)-one [EC no. 220-120-9]
Oral	LD50	450 mg/kg (ATE)
Inhalative	LC50/4 h	0.21 mg/l (ATE)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) -
- 11.2 Information on other hazards
- Endocrine disrupting properties

None of the ingredients is listed.

### **SECTION 12: Ecological information**

· 12.1 Toxicity

· Aquatic toxicity:	
1317-65-3 Calciumcarbonat	
EC 50/48h >1,000 mg/l (G)	

(Contd. on page 6)

Printing date 28.01.2025 Version number 6 Revision: 28.01.2025

#### Trade name EMULPLAST BIO MALERFARBE KA 1500

	(Contd. of page 5)
EC 50	289 mg/l (Desmodesmus subspicatus)
LC50	>10,000 mg/l (Oncorhynchus mykiss (Regenbogenforelle))
2634-33-5	1,2-benzisothiazol-3(2H)-one [EC no. 220-120-9]
EC 50/48h	3.27 mg/l (Daphnie)

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class (Germany) 2 (Self-assessment): hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

# SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation Smaller quantities can be disposed with household garbage.
- · Uncleaned packagings:
- Recommendation:

Disposal must be made according to official regulations.

Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

· Recommended cleaning agent: Water, if necessary with cleaning agent.

14.1 UN number or ID number		
ADR, ADN, IMDG, IATA	Void	
14.2 UN proper shipping name		
ADR, ADN, IMDG, IATA	Void	
· · · ·	7 0.0	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA		
Class	Void	
14.4 Packing group		
ADR, IMDG, IATA	Void	
14.5 Environmental hazards:		
Marine pollutant:	No	
14.6 Special precautions for user	Not applicable.	
14.7 Maritime transport in bulk accordi	ng to	
IMO instruments	Not applicable.	
UN "Model Regulation":	Void	

Printing date 28.01.2025 Version number 6 Revision: 28.01.2025

#### Trade name EMULPLAST BIO MALERFARBE KA 1500

(Contd. of page 6)

## SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- Regulated explosives precursors

None of the ingredients is listed.

Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

1310-73-2 sodium hydroxide

12% of total caustic alkalinity

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases
- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H311 Toxic in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H330 Fatal if inhaled.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- EUH071 Corrosive to the respiratory tract.
- · Contact: chemikalieninfo@murexin.com (+43 02622/27401)
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 4: Acute toxicity - Category 4

Acute Tox. 2: Acute toxicity - Category 2

Skin Corr. 1B: Skin corrosion/irritation - Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

(Contd. on page 8)

Printing date 28.01.2025 Version number 6 Revision: 28.01.2025

### Trade name EMULPLAST BIO MALERFARBE KA 1500

(Contd. of page 7)

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1A: Skin sensitisation – Category 1A

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

\* Data compared to the previous version altered.

GB -