Printing date 24.09.2021

Version number 4 (replaces version 3)

Revision: 24.09.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

[•] 1.1 Product identifier

- · Trade name ENERGY FURIOSO SILIKONHARZPUTZ
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- · Application of the substance / the mixture Construction chemicals
- · 1.3 Details of the supplier of the safety data sheet

• Manufacturer/Supplier: MUREXIN GmbH Franz v. Furtenbachstr. 1 A-2700 Wiener Neustadt Tel.: +43 (0)2622/27401

- · Informing department: chemikalieninfo@murexin.com
- 1.4 Emergency telephone number:
- UK National poisons Emergency number.: +44 (0) 870 600 6266

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

- [•] Classification according to Regulation (EC) No 1272/2008
- Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

- [•] Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the CLP regulation.
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements
- H412 Harmful to aquatic life with long lasting effects.
- Precautionary statements
- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P103 Read carefully and follow all instructions.
- P273 Avoid release to the environment.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- · Additional information:
- Contains 2-octyl-2H-isothiazol-3-one. May produce an allergic reaction.
- [•] 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- **Description:** Mixture consisting of the following components with harmless additives.

(Contd. on page 2)

GB

Printing date 24.09.2021

Version number 4 (replaces version 3)

Revision: 24.09.2021

Trade name ENERGY FURIOSO SILIKONHARZPUTZ

	(Conto	d. of page
Dangerous compo	nents:	
CAS: 7727-43-7	barium sulphate, natural	10-25
EINECS: 231-784-4	substance with a Community workplace exposure limit	
CAS: 26530-20-1	2-octyl-2H-isothiazol-3-one	<0.5%
EINECS: 247-761-7	Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330	
	Skin Corr. 1, H314; Eye Dam. 1, H318	
	Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410	
	(M=100)	
	EUH071	
	ATE: LD50 oral: 125 mg/kg	
	LD50 dermal: 311 mg/kg	
	LC50/4 h inhalative: 0.27 mg/l	
	Specific concentration limit: Skin Sens. 1A; H317: C \geq 0.0015 %	
CAS: 55965-84-9	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3: 1)	
	Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331 Skin Corr. 1B, H314	
	Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100)	
	() Skin Sens. 1A, H317	
	Specific concentration limits: Skin Corr. 1C; H314: C \geq 0.6 %	
	Skin Irrit. 2; H315: 0.06 % ≤ C < 0.6 %	
	Eye Dam. 1; H318: C ≥ 0.6 %	
	Éye Irrit. 2; H319: 0.06 % ≤ C < 0.6 %	
	Skin Sens. 1A; H317: C ≥ 0.0015 %	

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information
- Personal protection for the First Aider.
- Instantly remove any clothing soiled by the product.
- · After inhalation Supply fresh air; consult doctor in case of symptoms.
- · After skin contact
- If skin irritation continues, consult a doctor.
- Instantly wash with water and soap and rinse thoroughly.
- After eye contact
- Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor. After swallowing
- Rinse out mouth and then drink plenty of water.
- In case of persistent symptoms consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- [·] 5.1 Extinguishing media
- Suitable extinguishing agents
- Use fire fighting measures that suit the environment.

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

(Contd. on page 3)

Printing date 24.09.2021

Version number 4 (replaces version 3)

Revision: 24.09.2021

(Contd. of page 2)

Trade name ENERGY FURIOSO SILIKONHARZPUTZ

• **5.2 Special hazards arising from the substance or mixture** Can be released in case of fire

Nitrogen oxides (NOx)

Carbon monoxide (CO)

· 5.3 Advice for firefighters

· Protective equipment: No special measures required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Wear protective clothing. Particular danger of slipping on leaked/spilled product.
6.2 Environmental precautions: Do not allow to enter drainage system, surface or ground water. Inform respective authorities in case product reaches water or sewage system. Dilute with much water.
6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose of contaminated material as waste according to item 13.
6.4 Reference to other sections

No dangerous materials are released.

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling No special precautions necessary if used correctly. • Information about protection against explosions and fires: No special measures required.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage

· Requirements to be met by storerooms and containers: Store only in the original container.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions:
- Protect from frost.

Protect from heat and direct sunlight.

Keep container tightly sealed.

· Storage class 12

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with critical values that require monitoring at the workplace:

7727-43-7 barium sulphate, natural

WEL Long-term value: 10* 4** mg/m³

*inhalable dust **respirable dust

• Additional information: The lists that were valid during the compilation were used as basis.

[•] 8.2 Exposure controls

· Appropriate engineering controls No further data; see item 7.

· Individual protection measures, such as personal protective equipment

General protective and hygienic measures

The usual precautionary measures should be adhered to in handling the chemicals.

(Contd. on page 4)

GB

Printing date 24.09.2021

Version number 4 (replaces version 3)

Revision: 24.09.2021

Trade name ENERGY FURIOSO SILIKONHARZPUTZ

	(Contd. of page
Keep away from foodstuffs, beverages and foo	d.
Instantly remove any soiled and impregnated g	
Wash hands during breaks and at the end of th	e work.
Breathing equipment:	
Only during spraying without adequate removal	by suction.
Filter P2.	
 Hand protection Protective gloves. Material of gloves Nitrile rubber, NBR 	
· Penetration time of glove material	
	out by the manufacturer of the protective gloves ar
has to be observed.	
• Eye/face protection Safety glasses	
• Body protection: Protective work clothing.	
SECTION 9: Physical and chemical prop	perties
· 9.1 Information on basic physical and chem	
· General Information	
· Colour:	Different according to colour
· Smell:	Characteristic
[.] Boiling point or initial boiling point and	
boiling range	Not determined
• Lower and upper explosion limit	
· Lower:	Not determined.
· Upper:	Not determined.
· Flash point:	Not applicable
· Self-inflammability:	Product is not selfigniting.
Decomposition temperature:	Not determined.
· pH at 20 °C	8.5
· Solubility · Water:	completely mixable
Partition coefficient n-octanol/water (log	completely mixable
value)	Not determined.
· Steam pressure at 20 °C:	23 hPa
· Density and/or relative density	
· Density at 20 °C	1.9 g/cm³
Relative density	Not determined.
· Vapour density	Not determined.
9.2 Other information	
· Appearance:	Destu
· Form:	Pasty
 Important information on protection of healt and onvironment, and on safety. 	
and environment, and on safety. • Explosive properties:	Product is not explosive.
· Solvent content:	1 100001 13 1101 EXPIDSIVE.
· Water:	29.9 %
· Solids content:	50.0 %
· Change in condition	
· Evaporation rate	Not determined.
Information with regard to physical hazar	rd
Information with regard to physical hazar classes	
· Information with regard to physical hazar classes · Explosives	Void
 Information with regard to physical hazar classes Explosives Flammable gases 	Void Void
· Information with regard to physical hazar classes · Explosives	Void

(Contd. on page 5)

[,] GB

Printing date 24.09.2021

Version number 4 (replaces version 3)

Revision: 24.09.2021

Trade name ENERGY FURIOSO SILIKONHARZPUTZ

		(Contd. of page 4
Gases under pressure	Void	
Flammable liquids	Void	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit		
flammable gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: Strong acids and bases and strong oxidizing agents
- · 10.6 Hazardous decomposition products: None

SECTION 11: Toxicological information

• **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008** • **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:

26530-20-1	2-octyl-2H-isothiazol-3-one	

	-	
Oral	LD50	125 mg/kg (ATE)
Dermal	LD50	311 mg/kg (ATE)
link alativa	I CEO/A h	0.27 ma/((ATE))

Inhalative LC50/4 h 0.27 mg/l (ATE)

· Skin corrosion/irritation Based on available data, the classification criteria are not met.

· Serious eye damage/irritation Based on available data, the classification criteria are not met.

· Germ cell mutagenicity Based on available data, the classification criteria are not met.

· Carcinogenicity Based on available data, the classification criteria are not met.

• Reproductive toxicity Based on available data, the classification criteria are not met.

- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

· Additional toxicological information:

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) -

· 11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

• Aquatic toxicity: No further relevant information available.

(Contd. on page 6)

⁻ GB

Printing date 24.09.2021

Version number 4 (replaces version 3)

Revision: 24.09.2021

Trade name ENERGY FURIOSO SILIKONHARZPUTZ

 12.2 Persistence and degradability No further relevant information available. 12.3 Bioaccumulative potential No further relevant information available. 12.4 Mobility in soil No further relevant information available. 12.5 Results of PBT and vPvB assessment PBT: Not applicable. vPvB: Not applicable. 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11. 12.7 Other adverse effects Remark: Harmful to fish Additional available information: 	(Contd. of page 5)
· Additional ecological information:	
General notes:	
Harmful to aquatic organisms	
Water danger class (Germany) 3 (Self-assessment): extremely hazardous for water.	
Do not allow product to reach ground water, water bodies or sewage system quantities.	n, even in small
Danger to drinking water if even extremely small quantities leak into soil.	

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

• Recommendation: Disposal must be made according to official regulations.

• Recommended cleaning agent: Water, if necessary with cleaning agent.

SECTION 14: Transport informatio	n	
· 14.1 UN number or ID number · ADR, ADN, IMDG, IATA	Void	
• 14.2 UN proper shipping name • ADR, ADN, IMDG, IATA	Void	
· 14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA Class	Void	
• 14.4 Packing group • ADR, IMDG, IATA	Void	
14.5 Environmental hazards: Marine pollutant:	No	
14.6 Special precautions for user	Not applicable.	
14.7 Maritime transport in bulk accord IMO instruments	ing to Not applicable.	
UN "Model Regulation":	Void	

(Contd. on page 7)

Printing date 24.09.2021

Version number 4 (replaces version 3)

Revision: 24.09.2021

Trade name ENERGY FURIOSO SILIKONHARZPUTZ

(Contd. of page 6)

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · National regulations
- Other regulations, limitations and prohibitive regulations
- EU limit value for this product : < 40 g/l VOC (EU Directive 2004/42/EG)
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H301 Toxic if swallowed.
- H311 Toxic in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H330 Fatal if inhaled.
- H331 Toxic if inhaled.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

EUH071 Corrosive to the respiratory tract.

· Contact: chemikalieninfo@murexin.com (+43 02622/27401)

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European Inventory of Existing Commercial Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 2: Acute toxicity - Category 2

- Skin Corr. 1: Skin corrosion/irritation Category 1
- Skin Corr. 1B: Skin corrosion/irritation Category 1B
- Eye Dam. 1: Serious eye damage/eye irritation Category 1
- Skin Sens. 1A: Skin sensitisation Category 1A

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

** Data compared to the previous version altered.

GB