Printing date 05.09.2024 Version number 29 Revision: 05.09.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name EP-FEUCHTIGKEITSSPERRE 2K EP 170 KOMP. A
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Epoxy resin
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

MUREXIN GmbH

Franz v. Furtenbachstr. 1 A-2700 Wiener Neustadt Tel.: +43 (0)2622/27401

- · Informing department: chemikalieninfo@murexin.com
- · 1.4 Emergency telephone number:

UK National poisons Emergency number.: +44 (0) 870 600 6266

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms





GHS07 GHS09

- · Signal word Warning
- · Hazard-determining components of labelling:

Epichlorhydrin-bisphenol A resin

oxirane, mono[(C12-14-alkyloxy)methyl] derivs

· Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.
P261 Avoid breathing mist/vapours/spray.
P273 Avoid release to the environment.

(Contd. on page 2)

Printing date 05.09.2024 Version number 29 Revision: 05.09.2024

Trade name EP-FEUCHTIGKEITSSPERRE 2K EP 170 KOMP. A

(Contd. of page 1)

P280 Wear protective gloves / eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Additional information:

Contains epoxy constituents. May produce an allergic reaction.

- 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description:

Mixture consisting of the following components with harmless additives.

Epoxidharz auf Basis Bisphenol-A, enthält Kresylglycidylether

Dangerous components:		
CAS: 25068-38-6 NLP: 500-033-5 Reg.nr.: 01-2119456619-26- 0XXX	Epichlorhydrin-bisphenol A resin Aquatic Chronic 2, H411 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 EUH205 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5% Eye Irrit. 2; H319: C ≥ 5 %	50-100%
CAS: 68609-97-2 EINECS: 271-846-8	oxirane, mono[(C12-14-alkyloxy)methyl] derivs •• Skin Irrit. 2, H315; Skin Sens. 1, H317	10-25%

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information Instantly remove any clothing soiled by the product.
- · After inhalation

Supply fresh air and call for doctor for safety reasons.

In case of unconsciousness bring patient into stable side position for transport.

· After skin contact

Instantly wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

- · After swallowing Seek immediate medical advice.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents

Use fire fighting measures that suit the environment.

(Contd. on page 3)

Printing date 05.09.2024 Version number 29 Revision: 05.09.2024

Trade name EP-FEUCHTIGKEITSSPERRE 2K EP 170 KOMP. A

(Contd. of page 2)

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

· 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective clothing.
- 6.2 Environmental precautions:

Do not allow to enter the ground/soil.

Do not allow product to reach sewage system or water bodies.

Inform respective authorities in case product reaches water or sewage system.

Dilute with much water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep containers tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- · Requirements to be met by storerooms and containers:

Provide floor trough without outlet.

Store only in the original container.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions:

Protect from frost.

Keep container tightly sealed.

- · Storage class 10
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Components with critical values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the compilation were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.

(Contd. on page 4)

Printing date 05.09.2024 Version number 29 Revision: 05.09.2024

Trade name EP-FEUCHTIGKEITSSPERRE 2K EP 170 KOMP. A

(Contd. of page 3)

· Individual protection measures, such as personal protective equipment

General protective and hygienic measures

The usual precautionary measures should be adhered to in handling the chemicals.

Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

Breathing equipment:

Filter A/P2.

In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.

· Hand protection

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

Nitrile rubber, NBR

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eve/face protection Tightly sealed safety glasses.
- · Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical state
Colour:
Smell:
Fluid
Yellowish
Mild

· Odour threshold: Not determined.

· Boiling point or initial boiling point and

boiling range >200 °C (25068-38-6 Epichlorhydrin-bisphenol A

resin)

· Flammability Not applicable.

· Lower and upper explosion limit

· Lower: Not determined. · Upper: Not determined.

• Flash point: >150 °C (25068-38-6 Epichlorhydrin-bisphenol A

resin)

· Auto-ignition temperature: >268 °C (68609-97-2 oxirane, mono[(C12-14-

alkyloxy)methyl] derivs)

· **Decomposition temperature:** Not determined.

• **pH** Mixture is non-soluble (in water).

· Viscosity:

Kinematic viscositydynamic at 20 °C:Not determined.1,100 mPas

· Solubility

· Water: Not determined.

· Partition coefficient n-octanol/water (log

value) Not determined.

Steam pressure at 20 °C: 0 hPa (68609-97-2 oxirane, mono[(C12-14-

alkyloxy)methyl] derivs)

(Contd. on page 5)

Printing date 05.09.2024 Version number 29 Revision: 05.09.2024

Trade name EP-FEUCHTIGKEITSSPERRE 2K EP 170 KOMP. A

(Contd. of page 4) · Density and/or relative density · Density at 20 °C 1.1 g/cm3 · Relative density Not determined. · Vapour density Not determined. · 9.2 Other information · Appearance: · Form: Fluid · Important information on protection of health and environment, and on safety. · Self-inflammability: Product is not selfigniting. · Explosive properties: Product is not explosive. · Change in condition · Evaporation rate Not determined. · Information with regard to physical hazard classes · Explosives Void · Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void · Flammable liquids Void Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void Self-heating substances and mixtures Void

Void

Void

Void

Void

Void

Void

SECTION 10: Stability and reactivity

· Substances and mixtures, which emit

flammable gases in contact with water

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability

· Oxidising liquids

· Oxidising solids

· Organic peroxides

Corrosive to metals

· Desensitised explosives

- · Conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions Reacts with alkali, amines and strong acids
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Poisonous gases/vapours

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:				
25068-38-6 Epichlorhydrin-bisphenol A resin				
Oral	LD50	19,800 mg/kg (rabbit)		
		11,400 mg/kg (rat)		

(Contd. on page 6)

Printing date 05.09.2024 Version number 29 Revision: 05.09.2024

Trade name EP-FEUCHTIGKEITSSPERRE 2K EP 170 KOMP. A

Dermal LD50 20,000 mg/kg (rabbit)

Skin corrosion/irritation Causes skin irritation.
Serious eye damage/irritation Causes serious eye irritation.
Additional toxicological information:
CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) 11.2 Information on other hazards

· Endocrine disrupting properties				
128-37-0	Butylated hydroxytoluene	List II		
556-67-2	octamethylcyclotetrasiloxane	List II; III		
	Decamethylcyclopentasiloxan	List II		
540-97-6	Dodecamethylcyclohexasiloxan	List II		

SECTION 12: Ecological information

· 12.1 Toxicity

• • •				
· Aquatic toxicity:				
25068-38-6 Epichlorhydrin-bisphenol A resin				
EC 50	11 mg/l (Desmodesmus subspicatus)			
	1.8 mg/l (G)			
IC 50	100 mg/l (bacteria)			
LC50	2 mg/l (Oncorhynchus mykiss (Regenbogenforelle)) (semistatisch, 96h)			
	25068- EC 50 IC 50			

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Toxic for aquatic organisms

Also poisonous for fish and plankton in water bodies.

Water hazard class (Germany) 2 (Self-assessment): hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must be specially treated under adherence to official regulations.

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleaning agent: Water, if necessary with cleaning agent.

GF

Printing date 05.09.2024 Version number 29 Revision: 05.09.2024

Trade name EP-FEUCHTIGKEITSSPERRE 2K EP 170 KOMP. A

(Contd. of page 6)

SECTION 14: Transport information	n
14.1 UN number or ID number	4440000
ADR, IMDG, IATA	UN3082
14.2 UN proper shipping name ADR	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epichlorhydrin
IMDG	bisphenol A resin) ENVIRONMENTALLY HAZARDOUS SUBSTANCE LIQUID, N.O.S. (Epichlorhydrin-bisphenol A resin,
IATA	MARINE POLLUTANT ENVIRONMENTALLY HAZARDOUS SUBSTANCE LIQUID, N.O.S. (Epichlorhydrin-bisphenol A resin)
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class	9 Miscellaneous dangerous substances an articles.
Label	9
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards:	Product contains environmentally hazardou substances: Epichlorhydrin-bisphenol A resin
Marine pollutant:	Yes Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
Special marking (IATA):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Miscellaneous dangerous substances an articles.
Kemler Number:	90
EMS Number:	F-A,S-F
Stowage Category	A
14.7 Maritime transport in bulk accordance in the second limbol second l	ing to Not applicable.
Transport/Additional information:	
'	
Limited quantities (LQ)	5L
Transport category	3
Tunnel restriction code	(-)
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S
	(EPICHLORHYDRIN-BISPHENOL A RESIN), 9, III

Printing date 05.09.2024 Version number 29 Revision: 05.09.2024

Trade name EP-FEUCHTIGKEITSSPERRE 2K EP 170 KOMP. A

(Contd. of page 7)

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category E2 Hazardous to the Aquatic Environment
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

EUH205 Contains epoxy constituents. May produce an allergic reaction.

- · Contact: chemikalieninfo@murexin.com (+43 02622/27401)
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

* Data compared to the previous version altered.