Printing date 24.05.2023

Revision: 24.05.2023

SECTION 1: I	Identification of the substance/mixture and of the company/undertaking
· 1.1 Product ide	entifier
· Trade name El	POXY BASISBESCHICHTUNG EP 2 KOMP. A
	dentified uses of the substance or mixture and uses advised against
No further relev	vant information available.
• Application of	the substance / the mixture Coating
	the supplier of the safety data sheet
· Manufacturer/	
MUREXIN Gmb	
Franz v. Furten A-2700 Wiener	
Tel.: +43 (0)262	
	artment: chemikalieninfo@murexin.com
	y telephone number:
	isons Emergency number.: +44 (0) 870 600 6266
·	
SECTION 2.	Hazards identification
	ion of the substance or mixture
	according to Regulation (EC) No 1272/2008
envirol	nment
	innen.
Aquatic Chronic	c 2 H411 Toxic to aquatic life with long lasting effects.
Aqualic Chionic	
Skin Irrit. 2	H315 Causes skin irritation.
Eye Irrit. 2	H319 Causes serious eye irritation.
Skin Sens. 1	H317 May cause an allergic skin reaction.
· 2.2 Label elem	
	ording to Regulation (EC) No 1272/2008
	classified and labelled according to the GB CLP regulation.
· Hazard pictogi	
GHS07 GHS0	19
o: , , , , , , , , , , , , , , , , , , ,	
[.] Signal word W	rarning
	nining components of labelling:
	ypropoxy)phenyl]propane
	(C12-14-alkyloxy)methyl] derivs xypropoxy)butane
	oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol
	xypropoxy)hexane
Hazard statem	
H315 Causes s	
	serious eye irritation.
H319 Causes s	se an ailergic skin reaction.
H319 Causes s H317 May caus	
H319 Causes s H317 May caus H411 Toxic to a	aquatic life with long lasting effects.
H319 Causes s H317 May caus	aquatic life with long lasting effects. • statements
H319 Causes s H317 May caus H411 Toxic to a • Precautionary	aquatic life with long lasting effects.

Printing date 24.05.2023

Version number 7 (replaces version 6)

Revision: 24.05.2023

Trade name EPOXY BASISBESCHICHTUNG EP 2 KOMP. A

	(Contd. of page 1)
P103	Read carefully and follow all instructions.
P261	Avoid breathing mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves / eye protection.
P305+P351+P	2338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P501	Dispose of contents/container in accordance with local/regional/national/ international regulations.
· Additional inf	-
Contains epox	y constituents. May produce an allergic reaction.
2.3 Other haz	ards
· Results of PB	T and vPvB assessment
· PBT: Not appl	icable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture consisting of the following components with harmless additives.

CAS: 1675-54-3	bis[4-(2,3-epoxypropoxy)phenyl]propane	25-50%
EINECS: 216-823-5	 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 EUH205 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5% Skin Irrit. 2; H315: C ≥ 5 % 	
CAS: 7727-43-7 EINECS: 231-784-4	barium sulphate, natural substance with a Community workplace exposure limit	10-25%
CAS: 100-51-6 EINECS: 202-859-9 Reg.nr.: 01-2119492630-38- xxxxx	Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	2.5-5%
CAS: 68609-97-2 EINECS: 271-846-8	oxirane, mono[(C12-14-alkyloxy)methyl] derivs Skin Irrit. 2, H315; Skin Sens. 1, H317	2.5-5%
CAS: 2425-79-8 EINECS: 219-371-7 Reg.nr.: 01-2119494060-45- 0005	1,4-bis(2,3-epoxypropoxy)butane Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	1-2.5%
CAS: 64742-47-8 EINECS: 265-149-8	Distillates (petroleum), hydrotreated light Flam. Liq. 3, H226 Asp. Tox. 1, H304	1-2.5%
CAS: 9003-36-5 NLP: 500-006-8 Reg.nr.: 01-2119454392-40- 0001	formaldehyde, oligomeric reaction products with 1- chloro-2,3-epoxypropane and phenol Aquatic Chronic 2, H411 Skin Irrit. 2, H315; Skin Sens. 1, H317 EUH205	<i>≥</i> 0.5-<19
CAS: 933999-84-9 EC number: 618-939-5 Reg.nr.: 01-2119463471-41	1,6-bis(2,3-epoxypropoxy)hexane Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 Aquatic Chronic 3, H412	<i>≥</i> 0.5-<19

(Contd. on page 3)

Printing date 24.05.2023

Version number 7 (replaces version 6)

Revision: 24.05.2023

Trade name EPOXY BASISBESCHICHTUNG EP 2 KOMP. A

(Contd. of page 2)

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information Instantly remove any clothing soiled by the product.

· After inhalation

Supply fresh air; consult doctor in case of symptoms.

In case of unconsciousness bring patient into stable side position for transport.

- After skin contact Instantly wash with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor.
- After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

 After swallowing In case of persistent symptoms consult doctor.

Rinse out mouth and then drink plenty of water.

• **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

• **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- [·] 5.1 Extinguishing media
- · Suitable extinguishing agents Use fire fighting measures that suit the environment.
- 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective clothing.
- · 6.2 Environmental precautions:
- Do not allow product to reach sewage system or water bodies.
- Inform respective authorities in case product reaches water or sewage system. Do not allow to enter the ground/soil.

• **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose of contaminated material as waste according to item 13. Ensure adequate ventilation.

- 6.4 Reference to other sections
- See Section 7 for information on safe handling
- See Section 8 for information on personal protection equipment.
- See Section 13 for information on disposal.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling
- Ensure good ventilation/exhaustion at the workplace.
- Prevent formation of aerosols.

· Information about protection against explosions and fires: No special measures required.

(Contd. on page 4)

GB

Printing date 24.05.2023

Version number 7 (replaces version 6)

Revision: 24.05.2023

Trade name EPOXY BASISBESCHICHTUNG EP 2 KOMP. A

(Contd. of page 3)

- 7.2 Conditions for safe storage, including any incompatibilities
- · Storage

• Requirements to be met by storerooms and containers: Store only in the original container.

- · Information about storage in one common storage facility:
- Store away from foodstuffs.

Do not store together with reducing agents, heavy-metal compounds, acids and alkalis.

- Further information about storage conditions: Keep container tightly sealed.
- · Storage class 10
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with critical values that require monitoring at the workplace:

7727-43-7 barium sulphate, natural

WEL Long-term value: 10* 4** mg/m³

*inhalable dust **respirable dust

· Additional information: The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures

The usual precautionary measures should be adhered to in handling the chemicals.

Keep away from foodstuffs, beverages and food. Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Avoid contact with the skin.

Breathing equipment:

In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air. Filter A/P2.

- · Hand protection Protective gloves.
- Material of gloves Butvl rubber. BR

Nitrile rubber. NBR

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection Safety glasses

Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

 9.1 Information on basic physical and chemical properties · General Information · Physical state Fluid · Colour: Different according to colour Characteristic · Smell: Not determined • Melting point/freezing point: · Boiling point or initial boiling point and boiling range >200 °C (25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)) (Contd. on page 5)

Printing date 24.05.2023

Version number 7 (replaces version 6)

Revision: 24.05.2023

Trade name EPOXY BASISBESCHICHTUNG EP 2 KOMP. A

		(Contd. of page
Flash point:	141 °C	
pH	Not determined.	
Viscosity:		
Kinematic viscosity	Not determined.	
dynamic at 20 °C:	7,000-11,000 mPas	
Solubility		
Water:	Unsoluble	
Steam pressure:	Not determined.	
Density and/or relative density		
Density at 20 °C	1.8 g/cm³	
Vapour density	Not determined.	
9.2 Other information		
Appearance:		
Form:	Pasty	
Important information on protection of hea		
and environment, and on safety.	1111	
Self-inflammability:	Product is not selfigniting.	
Explosive properties:	Product is not explosive.	
Change in condition	Troduct is not explosive.	
Evaporation rate	Not determined.	
•		
Information with regard to physical haz	ard	
classes		
Explosives	Void	
Flammable gases	Void	
Aerosols	Void	
Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Void	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit		
flammable gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

· Conditions to be avoided: No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions No dangerous reactions known

· 10.4 Conditions to avoid No further relevant information available.

· 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products: None

(Contd. on page 6)

GB

Printing date 24.05.2023

Version number 7 (replaces version 6)

Revision: 24.05.2023

Trade name EPOXY BASISBESCHICHTUNG EP 2 KOMP. A

(Contd. of page 5)

	ormation on hazard classes as defined in Regulation (EC) No 1272/2008	3
	exicity Based on available data, the classification criteria are not met. • Values that are relevant for classification:	
	-3 bis[4-(2,3-epoxypropoxy)phenyl]propane	
	LD50 >2,000 mg/kg (rat)	
	LD50 >2,000 mg/kg (rat)	
	S Benzyl alcohol	
	LD50 1,230 mg/kg (rat)	
	LD50 2,000 mg/kg (rbt)	
	-8 1,4-bis(2,3-epoxypropoxy)butane	
Oral	LD50 2,000 mg/kg (rat)	
Dermal	LD50 >2,000 mg/kg (rat)	
9003-36-	5 formaldehyde, oligomeric reaction products with 1-chloro-2,3-epox phenol	ypropane an
Oral	LD50 >5,000 mg/kg (rat)	
	LD50 >2,000 mg/kg (rat)	
Serious Causes : Germ ce Carcino Reprodu STOT-si STOT-re Aspirati Additior CMR eff	skin irritation. eye damage/irritation serious eye irritation. ell mutagenicity Based on available data, the classification criteria are not m genicity Based on available data, the classification criteria are not met. Inctive toxicity Based on available data, the classification criteria are not met ingle exposure Based on available data, the classification criteria are not m epeated exposure Based on available data, the classification criteria are not m epeated exposure Based on available data, the classification criteria are not m on hazard Based on available data, the classification criteria are not nal toxicological information: ects (carcinogenity, mutagenicity and toxicity for reproduction) - ormation on other hazards	et. et.
	ne disrupting properties	
	Butylated hydroxytoluene	List II
556-67-2	octamethylcyclotetrasiloxane	List II; I
	Decamethylcyclopentasiloxan	List II
	Dodecamethylcyclohexasiloxan	List II

SECTION 12: Ecological information

· Aquat	c toxicity:	
9003-3	6-5 formaldehyde, oligomeric reaction products with 1-chloro-2,3-ep phenol	oxypropane and
EC 50	1.8 mg/l (Desmodesmus subspicatus)	
	1.6 mg/l (G)	
IC 50	>100 mg/l (bacteria)	
LC50	0.55 mg/l (Lepomis macrochirus (Fisch))	
· 12.3 B	ersistence and degradability No further relevant information available. ioaccumulative potential No further relevant information available. obility in soil No further relevant information available.	(Contd on page 7)

(Contd. on page 7)

⁻ GB

Printing date 24.05.2023

Version number 7 (replaces version 6)

Revision: 24.05.2023

Trade name EPOXY BASISBESCHICHTUNG EP 2 KOMP. A

(Contd. of page 6)

- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- 12.6 Endocrine disrupting properties
- For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:
- Harmful to aquatic organisms
- Water hazard class (Germany) 2 (Self-assessment): hazardous for water.
- Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

• Recommendation: Disposal must be made according to official regulations.

14.1 UN number or ID number ADR, IMDG, IATA	UN3082
14.2 UN proper shipping name	
ADR	3082 ENVIRONMENTALLY HAZARDOU SUBSTANCE, LIQUID, N.O.S. (bis[4-(2,3 epoxypropoxy)phenyl]propane)
IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE LIQUID, N.O.S. (bis[4-(2,3-epoxypropoxy)pheny propane, formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol), MARINE POLLUTANT
ΙΑΤΑ	ENVIRONMENTALLY HAZARDOUS SUBSTANCE LIQUID, N.O.S. (bis[4-(2,3-epoxypropoxy)pheny propane)
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class	9 Miscellaneous dangerous substances and articles.
Label	9
14.4 Packing group	
ADR, IMDG, IATA	///

Printing date 24.05.2023

Version number 7 (replaces version 6)

Revision: 24.05.2023

Trade name EPOXY BASISBESCHICHTUNG EP 2 KOMP. A

	(Contd. of page
14.5 Environmental hazards:	Product contains environmentally hazardou substances: bis[4-(2,3-epoxypropoxy)phenyl propane
Marine pollutant:	No
Special marking (ADR):	Symbol (fish and tree) Symbol (fish and tree)
Special marking (IATA):	Symbol (fish and tree)
• 14.6 Special precautions for user	Warning: Miscellaneous dangerous substances and articles.
Kemler Number:	90
EMS Number:	F-A,S-F
Stowage Category	A
14.7 Maritime transport in bulk accordi	ing to
IMO instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Transport category	3
Tunnel restriction code	(-)
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOU SUBSTANCE, LIQUID, N.O.S. (BIS[4-(2,3 EPOXYPROPOXY)PHENYL]PROPANE), 9, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category E2 Hazardous to the Aquatic Environment
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

EUH205 Contains epoxy constituents. May produce an allergic reaction.

· Contact: chemikalieninfo@murexin.com (+43 02622/27401)

(Contd. on page 9)

GB

Printing date 24.05.2023

Version number 7 (replaces version 6)

Revision: 24.05.2023

Trade name EPOXY BASISBESCHICHTUNG EP 2 KOMP. A

	bbreviations and acronyms:
	D: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulat
	oncerning the International Transport of Dangerous Goods by Rail)
ICA	AO: International Civil Aviation Organisation
	DR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concer
	e International Carriage of Dangerous Goods by Road)
IML	DG: International Maritime Code for Dangerous Goods
IA1	TA: International Air Transport Association
GH	HS: Globally Harmonised System of Classification and Labelling of Chemicals
ΕIN	NECS: European Inventory of Existing Commercial Chemical Substances
ELI	INCS: European List of Notified Chemical Substances
CA	AS: Chemical Abstracts Service (division of the American Chemical Society)
LC	250: Lethal concentration, 50 percent
LD	050: Lethal dose, 50 percent
ΡВ	3T: Persistent, Bioaccumulative and Toxic
vP۱	VB: very Persistent and very Bioaccumulative
Fla	am. Liq. 3: Flammable liquids – Category 3
Acı	rute Tox. 4: Acute toxicity – Category 4
Ski	in Irrit. 2: Skin corrosion/irritation – Category 2
Eye	re Irrit. 2: Serious eye damage/eye irritation – Category 2
Ski	in Sens. 1: Skin sensitisation – Category 1
Asp	p. Tox. 1: Aspiration hazard – Category 1
Aqı	uatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aqı	uatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
÷ -	Data compared to the previous version altered.