Printing date 11.05.2023 Version number 41 Revision: 11.05.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name EPOXY-BASISHARZ EP 70 BM KOMP.B
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Hardening agent/ Curing agent
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

MUREXIN GmbH

Franz v. Furtenbachstr. 1 A-2700 Wiener Neustadt Tel.: +43 (0)2622/27401

- · Informing department: chemikalieninfo@murexin.com
- · 1.4 Emergency telephone number:

UK National poisons Emergency number.: +44 (0) 870 600 6266

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.



corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.



environment

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



Skin Sens. 1

H317 May cause an allergic skin reaction.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms









GHS05 GHS07 GHS08 GHS09

- · Signal word Danger
- · Hazard-determining components of labelling:

Liquid Epoxy Resin-Isophoronediamine adduct 4-nonylphenol, branched m-phenylenebis(methylamine)

· Hazard statements

H314 Causes severe skin burns and eye damage.

(Contd. on page 2)

Printing date 11.05.2023 Version number 41 Revision: 11.05.2023

Trade name EPOXY-BASISHARZ EP 70 BM KOMP.B

(Contd. of page 1)

H317 May cause an allergic skin reaction.

H361 Suspected of damaging fertility or the unborn child. H410 Very toxic to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P260 Do not breathe dusts or mists.

P280 Wear protective gloves / eye protection / face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor. P310

P362+P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture consisting of the following components with harmless additives.

CAS: 100-51-6	Benzyl alcohol	25-50%
EINECS: 202-859-9 Reg.nr.: 01-2119492630-38- xxxxx	Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	
CAS: 38294-64-3	Liquid Epoxy Resin-Isophoronediamine adduct	25-50%
NLP: 500-101-4	Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Chronic 3, H412	
CAS: 1477-55-0	m-phenylenebis(methylamine)	≥10-<25%
EINECS: 216-032-5	Skin Corr. 1B, H314; Eye Dam. 1, H318 Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1, H317 Aquatic Chronic 3, H412	
CAS: 84852-15-3	4-nonylphenol, branched	≥3-<5%
EINECS: 284-325-5	Repr. 2, H361fd Skin Corr. 1B, H314 Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Acute Tox. 4, H302	

SVHC

84852-15-3 4-nonylphenol, branched

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information Instantly remove any clothing soiled by the product.
- · After inhalation

Take affected persons into the open air and position comfortably

(Contd. on page 3)

Printing date 11.05.2023 Version number 41 Revision: 11.05.2023

Trade name EPOXY-BASISHARZ EP 70 BM KOMP.B

(Contd. of page 2)

Supply fresh air and call for doctor for safety reasons.

In case of unconsciousness bring patient into stable side position for transport.

· After skin contact

Instantly wash with water and soap and rinse thoroughly.

Seek medical treatment.

- · After eye contact Rinse opened eye for several minutes under running water. Then consult doctor.
- · After swallowing Drink copious amounts of water and provide fresh air. Instantly call for doctor.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

5.2 Special hazards arising from the substance or mixture

Formation of poisonous gases during heating or in fires.

- 5.3 Advice for firefighters
- · Protective equipment: Put on breathing apparatus.
- Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Put on breathing apparatus.

Wear protective clothing.

6.2 Environmental precautions:

Do not allow to enter the ground/soil.

Do not allow product to reach sewage system or water bodies.

Inform respective authorities in case product reaches water or sewage system.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent.

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep containers tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Open and handle container with care.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: Keep breathing equipment ready.
- 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- · Requirements to be met by storerooms and containers:

Provide floor trough without outlet.

(Contd. on page 4)

Printing date 11.05.2023 Version number 41 Revision: 11.05.2023

Trade name EPOXY-BASISHARZ EP 70 BM KOMP.B

(Contd. of page 3)

Store only in the original container.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions:

Protect from frost.

Keep container tightly sealed.

- · Storage class 8 A
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- Components with critical values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- Additional information: The lists that were valid during the compilation were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures

The usual precautionary measures should be adhered to in handling the chemicals.

Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Breathing equipment:

Filter A/P2.

In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.

· Hand protection

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

Butyl rubber, BR

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye/face protection Safety glasses
- · Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information

Physical state
Colour:
Smell:
Odour threshold:
Fluid
Yellowish
Amine-like
Not determined.

Melting point/freezing point:

It is technically not possible to determine a value.

· Boiling point or initial boiling point and

boiling range >190 °C

(Contd. on page 5)

(Contd. of page 4)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.05.2023 Version number 41 Revision: 11.05.2023

Trade name EPOXY-BASISHARZ EP 70 BM KOMP.B

Not applicable

· Flammability Not applicable.

· Lower and upper explosion limit

Lower: 1.3 Vol %
Upper: 13 Vol %
Flash point: >90 °C
Auto-ignition temperature: 380 °C

· **Decomposition temperature:** Not determined.

• **pH** Mixture is non-soluble (in water).

· Viscosity:

• Kinematic viscosity
• dynamic at 20 °C:

Not determined.
190 mPas

· Solubility

· Water: Not miscible or difficult to mix

· Partition coefficient n-octanol/water (log

value) Not determined.

· Steam pressure at 20 °C: 0.1 hPa

· Density and/or relative density

· Density at 20 °C 1 g/cm³

Relative densityVapour densityNot determined.Not determined.

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health

and environment, and on safety.

Self-inflammability: Product is not selfigniting.
 Explosive properties: Product is not explosive.

Change in condition

· Evaporation rate Not determined.

· Information with regard to physical hazard classes

· Explosives Void Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void

flammable gases in contact with water

Oxidising liquids
Oxidising solids
Organic peroxides
Corrosive to metals
Desensitised explosives
Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- · Conditions to be avoided: No decomposition if used according to specifications.

(Contd. on page 6)

Printing date 11.05.2023 Version number 41 Revision: 11.05.2023

Trade name EPOXY-BASISHARZ EP 70 BM KOMP.B

(Contd. of page 5)

- 10.3 Possibility of hazardous reactions Reacts with acids, alkalis and oxidizing agents
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: Poisonous gases/vapours

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity

· LD/LC50 values that are relevant for classification:

100-51-6 Benzyl alcohol

Oral LD50 1,230 mg/kg (rat)
Dermal LD50 2,000 mg/kg (rbt)

- · Skin corrosion/irritation Causes severe skin burns and eye damage.
- Reproductive toxicity Suspected of damaging fertility or the unborn child.
- 11.2 Information on other hazards
- · Endocrine disrupting properties

84852-15-3 4-nonylphenol, branched

List I

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Also poisonous for fish and plankton in water bodies.

Water danger class (Germany) 3 (Self-assessment): extremely hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into soil.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must be specially treated under adherence to official regulations.

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)

Printing date 11.05.2023 Version number 41 Revision: 11.05.2023

Trade name EPOXY-BASISHARZ EP 70 BM KOMP.B

(Contd. of page 6)

- · Uncleaned packagings: · Recommendation: Disposal must be made according to official regulations.

14.1 UN number or ID number ADR, IMDG, IATA	UN1760
14.2 UN proper shipping name ADR	1760 CORROSIVE LIQUID, N.O.S. (Bisphenol A EpichlorhydrinIsophorondiamin Copolymer, r phenylenebis(methylamine)), ENVIRONMENTALL HAZARDOUS
IMDG	CORROSIVE LIQUID, N.O.S. (Bisphenol A EpichlorhydrinIsophorondiamin Copolymer, r phenylenebis(methylamine)), MARIN POLLUTANT
IATA	CORROSIVE LIQUID, N.O.S. (Bisphenol A EpichlorhydrinIsophorondiamin Copolymer, I phenylenebis(methylamine))
14.3 Transport hazard class(es)	
ADR, IMDG	
The state of the s	
Class Label	8 Corrosive substances. 8
IATA	
Class	8 Corrosive substances.
Label	8
14.4 Packing group ADR, IMDG, IATA	II .
14.5 Environmental hazards:	Product contains environmentally hazardot substances: 4-nonylphenol, branched
Marine pollutant:	Yes Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user Kemler Number: EMS Number:	<i>Warning: Corrosive substances.</i> 80 F-A,S-B
Stowage Category Stowage Code	B SW2 Clear of living quarters.
14.7 Maritime transport in bulk according IMO instruments	ng to Not applicable.
	(Contd. on page

Printing date 11.05.2023 Version number 41 Revision: 11.05.2023

Trade name EPOXY-BASISHARZ EP 70 BM KOMP.B

	(Contd. of page 7)
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Transport category · Tunnel restriction code	1L 2 E
· UN "Model Regulation":	UN 1760 CORROSIVE LIQUID, N.O.S. (B I S P H E N O L A - EPICHLORHYDRINISOPHORONDIAMIN C O P O L Y M E R , M - PHENYLENEBIS(METHYLAMINE)), 8, II, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category E1 Hazardous to the Aquatic Environment
- Qualifying quantity (tonnes) for the application of lower-tier requirements 100 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- · National regulations
- · Substances of very high concern (SVHC) according to UK REACH

84852-15-3 4-nonylphenol, branched

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H302 Harmful if swallowed.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- · Contact: chemikalieninfo@murexin.com (+43 02622/27401)
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 9)

Printing date 11.05.2023 Version number 41 Revision: 11.05.2023

Trade name EPOXY-BASISHARZ EP 70 BM KOMP.B

(Contd. of page 8)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation - Category 1B Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Dain: 1. Serious eye damage/eye irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1 Repr. 2: Reproductive toxicity – Category 2

Repr. 2: Reproductive toxicity - Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

* Data compared to the previous version altered.