Printing date 13.12.2024

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### <sup>•</sup> 1.1 Product identifier

- · Trade name EPOXY BESCHICHTUNG EP 3 KOMP. A
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- · Application of the substance / the mixture Epoxy coating
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier: MUREXIN GmbH Franz v. Furtenbachstr. 1 A-2700 Wiener Neustadt Tel.: +43 (0)2622/27401
- · Informing department: chemikalieninfo@murexin.com
- 1.4 Emergency telephone number:
- UK National poisons Emergency number.: +44 (0) 870 600 6266

#### SECTION 2: Hazards identification

2.1 Classification of the substance or mixture
 Classification according to Regulation (EC) No 1272/2008

health hazard

Repr. 1B

H360F May damage fertility.

to environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
Skin Sens. 1	H317	May cause an allergic skin reaction.

#### · 2.2 Label elements

• Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation. • Hazard pictograms



· Signal word Danger

• Hazard-determining components of labelling: Bisphenol A epoxy resin oxirane, mono[(C12-14-alkyloxy)methyl] derivs Bisphenol F diglycidyl ether, mixture of isomers

· Hazard statements

- H315 Causes skin irritation.
- H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H360F May damage fertility.

(Contd. on page 2)

Printing date 13.12.2024

Version number 9 (replaces version 8)

Revision: 13.12.2024

# Trade name EPOXY BESCHICHTUNG EP 3 KOMP. A

	(Contd. of page 1)
H411 Toxic to	aquatic life with long lasting effects.
Precautionary	statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.
P261	Avoid breathing mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P3	38 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P501	Dispose of contents/container in accordance with local/regional/national/ international regulations.
Additional info	irmation:
Restricted to pro	ofessional users.
Contains epoxy	constituents. May produce an allergic reaction.
2.3 Other haza	
<b>Results of PB1</b>	「and vPvB assessment
PBT: Not applic	able.
vPvB: Not appli	

# SECTION 3: Composition/information on ingredients

# <sup>.</sup> 3.2 Mixtures

# · Description:

Mixture consisting of the following components with harmless additives. Füllstoffhaltiges Epoxidharz, enthält Bisphenol A-Epichlorhydrin-

Dangerous components:		
CAS: 1675-54-3 EINECS: 216-823-5	<ul> <li>Bisphenol A epoxy resin</li> <li>Aquatic Chronic 2, H411</li> <li>Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1B, H317</li> <li>EUH205</li> <li>Specific concentration limits: Eye Irrit. 2; H319: C ≥5 % Skin Irrit. 2; H315: C ≥ 5 %</li> </ul>	25-50%
CAS: 7727-43-7 EINECS: 231-784-4	barium sulphate, natural substance with a Community workplace exposure limit	10-25%
CAS: 68609-97-2 EINECS: 271-846-8 Reg.nr.: 01-2119485289-22- XXXX	oxirane, mono[(C12-14-alkyloxy)methyl] derivs Repr. 1B, H360F Skin Irrit. 2, H315; Skin Sens. 1, H317	<i>≥</i> 5-<10%
EC number: 701-263-0 Reg.nr.: 01-2119454392-40- 0003	Bisphenol F diglycidyl ether, mixture of isomers Consisting of: 9003-36-5 Bisphenol-F- epichlorohydrin resin Aquatic Chronic 2, H411 Skin Irrit. 2, H315; Skin Sens. 1A, H317	<i>≥</i> 5-<10%
CAS: 100-51-6 EINECS: 202-859-9 Reg.nr.: 01-2119492630-38- xxxxx	Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	2.5-5%
CAS: 64742-47-8 EINECS: 265-149-8	Distillates (petroleum), hydrotreated light Flam. Liq. 3, H226 Asp. Tox. 1, H304	1-2.5%

Printing date 13.12.2024

Version number 9 (replaces version 8)

Revision: 13.12.2024

#### Trade name EPOXY BESCHICHTUNG EP 3 KOMP. A

	Discharge A community	(Contd. of page 2)
CAS: 1675-54-3	Bisphenol A epoxy resin	<i>≥</i> 0.1-<0.25%
EINECS: 216-823-5	<ul> <li>Aquatic Chronic 2, H411</li> <li>Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317</li> <li>EUH205</li> <li>Specific concentration limits: Eye Irrit. 2; H319: C ≥5 % Skin Irrit. 2; H315: C ≥ 5 %</li> </ul>	

# SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information Instantly remove any clothing soiled by the product.

#### · After inhalation

- Supply fresh air and call for doctor for safety reasons.
- In case of unconsciousness bring patient into stable side position for transport.

#### After skin contact

If skin irritation continues, consult a doctor.

Instantly wash with water and soap and rinse thoroughly.

- · After eye contact Rinse opened eye for several minutes under running water. Then consult doctor.
- · After swallowing In case of persistent symptoms consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- Suitable extinguishing agents

Use fire fighting measures that suit the environment.

- CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.
- 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- <sup>•</sup> 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

### SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective clothing.
- 6.2 Environmental precautions:
- Do not allow to enter the ground/soil.
- Do not allow product to reach sewage system or water bodies.

Inform respective authorities in case product reaches water or sewage system. Dilute with much water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

*6.4 Reference to other sections* See Section 7 for information on safe handling See Section 8 for information on personal protection equipment.

(Contd. on page 4)

G

Printing date 13.12.2024

Version number 9 (replaces version 8)

Revision: 13.12.2024

#### Trade name EPOXY BESCHICHTUNG EP 3 KOMP. A

See Section 13 for information on disposal.

(Contd. of page 3)

# SECTION 7: Handling and storage

**7.1 Precautions for safe handling** Keep containers tightly sealed. Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

· Information about protection against explosions and fires: No special measures required.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage

• Requirements to be met by storerooms and containers: Store only in the original container.

· Information about storage in one common storage facility: Store away from foodstuffs.

• Further information about storage conditions: Keep container tightly sealed.

· Storage class 6.1 C

· 7.3 Specific end use(s) No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

#### · 8.1 Control parameters

• Components with critical values that require monitoring at the workplace:

#### 7727-43-7 barium sulphate, natural

WEL Long-term value: 10\* 4\*\* mg/m<sup>3</sup>

\*inhalable dust \*\*respirable dust

• Additional information: The lists that were valid during the compilation were used as basis.

#### · 8.2 Exposure controls

• Appropriate engineering controls No further data; see section 7.

- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures

The usual precautionary measures should be adhered to in handling the chemicals.

Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

- Avoid contact with the eyes and skin.
- Breathing equipment:

Filter A/P2.

In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.

- · Hand protection Protective gloves.
- · Material of gloves

Nitrile rubber, NBR

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye/face protection Safety glasses recommended during refilling.
- · **Body protection:** Protective work clothing.

(Contd. on page 5)

Printing date 13.12.2024

Version number 9 (replaces version 8)

Revision: 13.12.2024

# Trade name EPOXY BESCHICHTUNG EP 3 KOMP. A

(Contd. of page 4)

9.1 Information on basic physical and chem	nical properties
General Information	
Physical state	Fluid
Colour:	Different according to colour
Smell:	Mild
Odour threshold:	Not determined.
Melting point/freezing point:	Not determined
Boiling point or initial boiling point and	
boiling range	2,230 °C
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	Not determined.
Upper:	Not determined.
	>100 °C
Flash point:	
Decomposition temperature:	Not determined. Mixture is non polor/opretie
pH Viacositur	Mixture is non-polar/aprotic.
Viscosity:	Not data waina d
Kinematic viscosity	Not determined.
dynamic:	Not determined.
Solubility	
Water:	Not determined.
Partition coefficient n-octanol/water (log	
value)	Not determined.
Steam pressure at 20 °C:	>0 hPa (1675-54-3 Bisphenol A epoxy resin)
Density and/or relative density	
Density at 20 °C	1.6 g/cm <sup>3</sup>
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Fluid
Important information on protection of hea	
and environment, and on safety.	
Self-inflammability:	Product is not selfigniting.
Explosive properties:	
	Product is not explosive.
Change in condition	Not determined.
Evaporation rate	
Information with regard to physical haza	ard
classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit	Void
flammable gases in contact with water	Void
nammable gases in contact with water	
Oxidising liquids	Void

(Contd. on page 6)

Printing date 13.12.2024

Version number 9 (replaces version 8)

Revision: 13.12.2024

#### Trade name EPOXY BESCHICHTUNG EP 3 KOMP. A

		(Contd. of page 5)
· Organic peroxides	Void	
· Corrosive to metals	Void	
Desensitised explosives	Void	

# SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

· Conditions to be avoided: No decomposition if used according to specifications.

• 10.3 Possibility of hazardous reactions No dangerous reactions known

• 10.4 Conditions to avoid No further relevant information available.

• **10.5 Incompatible materials:** No further relevant information available.

· 10.6 Hazardous decomposition products: None

# SECTION 11: Toxicological information

 $^{\cdot}$  11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:

#### 1675-54-3 Bisphenol A epoxy resin

Oral LD50 >2,000 mg/kg (rat)

Dermal LD50 >2,000 mg/kg (rat)

# 100-51-6 Benzyl alcohol

Oral LD50 1,230 mg/kg (rat)

Dermal LD50 2,000 mg/kg (rabbit)

# 1675-54-3 Bisphenol A epoxy resin

Oral LD50 >2,000 mg/kg (rat)

Dermal LD50 >2,000 mg/kg (rat)

· Skin corrosion/irritation Causes skin irritation.

Serious eye damage/irritation Causes serious eye irritation.

- · Reproductive toxicity May damage fertility.
- · Additional toxicological information:

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) -

11.2 Information on other hazards

· Endocrine disrupting properties

128-37-0 Butylated hydroxytoluene

List II

# SECTION 12: Ecological information

#### · 12.1 Toxicity

· Aquatic toxicity: No further relevant information available.

• **12.2 Persistence and degradability** No further relevant information available.

• **12.3 Bioaccumulative potential** No further relevant information available.

• 12.4 Mobility in soil No further relevant information available.

· 12.5 Results of PBT and vPvB assessment

• **PBT:** Not applicable.

• vPvB: Not applicable.

· 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

12.7 Other adverse effects

• Remark: Toxic for fish

(Contd. on page 7)

GB

Printing date 13.12.2024

Version number 9 (replaces version 8)

Revision: 13.12.2024

# Trade name EPOXY BESCHICHTUNG EP 3 KOMP. A

(Contd. of page 6)

# · Additional ecological information:

· General notes:

Toxic for aquatic organisms

Also poisonous for fish and plankton in water bodies.

Water hazard class (Germany) 2 (Self-assessment): hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

### SECTION 13: Disposal considerations

#### · 13.1 Waste treatment methods

· Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

Recommendation:

Disposal must be made according to official regulations.

- Dispose of packaging according to regulations on the disposal of packagings.
- · Recommended cleaning agent: Water, if necessary with cleaning agent.

# SECTION 14: Transport information

· 14.1 UN number or ID number · ADR, IMDG, IATA	UN3082	
<ul> <li>14.2 UN proper shipping name</li> <li>ADR</li> </ul>	3082 ENVIRONMENTALLY HAZARDOU SUBSTANCE, LIQUID, N.O.S. (Bisphenol A epox resin, Bisphenol F diglycidyl ether, mixture o	
·IMDG	isomers) ENVIRONMENTALLY HAZARDOUS SUBSTANCE LIQUID, N.O.S. (Bisphenol A epoxy resir Bisphenol F diglycidyl ether, mixture of isomers	
·IATA	MARINE POLLUTANT ENVIRONMENTALLY HAZARDOUS SUBSTANCI LIQUID, N.O.S. (Bisphenol A epoxy resin Bisphenol F diglycidyl ether, mixture of isomers)	
· 14.3 Transport hazard class(es)		
· ADR, IMDG, IATA		
· Class · Label	9 Miscellaneous dangerous substances and articles. 9	
	9	
· 14.4 Packing group · ADR, IMDG, IATA	III	
· 14.5 Environmental hazards:	Product contains environmentally hazardou substances: Bisphenol A epoxy resin	
· Marine pollutant:	Yes Symbol (fish and tree)	
· Special marking (ADR):	Symbol (fish and tree)	
	(Contd. on page	

GB

Printing date 13.12.2024

Version number 9 (replaces version 8)

Revision: 13.12.2024

#### Trade name EPOXY BESCHICHTUNG EP 3 KOMP. A

	(Contd. of page
· Special marking (IATA):	Symbol (fish and tree)
<sup>•</sup> 14.6 Special precautions for user	Warning: Miscellaneous dangerous substances and articles.
· Kemler Number:	90
· EMS Number:	F-A,S-F
· Stowage Category	Α
· 14.7 Maritime transport in bulk accord	ing to
IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Transport category	3
· Tunnel restriction code	(-)
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL ) EPOXY RESIN, BISPHENOL F DIGLYCIDY ETHER, MIXTURE OF ISOMERS), 9, III

### **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poisons Act

#### · Regulated explosives precursors

None of the ingredients is listed.

#### · Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

### Reportable poisons

None of the ingredients is listed.

#### · Directive 2012/18/EU

- Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category E2 Hazardous to the Aquatic Environment
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.

(Contd. on page 9)

Printing date 13.12.2024

Version number 9 (replaces version 8)

Revision: 13.12.2024

# Trade name EPOXY BESCHICHTUNG EP 3 KOMP. A

(Contd. of page 8	8)
H360F May damage fertility.	
H411 Toxic to aquatic life with long lasting effects.	
EUH205 Contains epoxy constituents. May produce an allergic reaction.	
Lonzoo comains epoxy construction. May produce an aneight reaction.	
<ul> <li>Contact: chemikalieninfo@murexin.com (+43 02622/27401)</li> </ul>	
Abbreviations and acronyms:	
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulation	
Concerning the International Transport of Dangerous Goods by Rail)	13
ICAO: International Civil Aviation Organisation	
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concernin	na
the International Carriage of Dangerous Goods by Road)	'9
IMDG: International Maritime Code for Dangerous Goods	
IATA: International Air Transport Association	
GHS: Globally Harmonised System of Classification and Labelling of Chemicals	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
Flam. Liq. 3: Flammable liquids – Category 3	
Acute Tox. 4: Acute toxicity – Category 4	
Skin Irrit. 2: Skin corrosion/irritation – Category 2	
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2	
Skin Sens. 1: Skin sensitisation – Category 1	
Skin Sens. 1A: Skin sensitisation – Category 1A	
Skin Sens. 1B: Skin sensitisation – Category 1B	
Repr. 1B: Reproductive toxicity – Category 1B	
Asp. Tox. 1: Aspiration hazard – Category 1	
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2	
* * Data compared to the previous version altered.	
	GB —