Printing date 10.08.2023 Version number 8 (replaces version 7) Revision: 10.08.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name EPOXY-BESCHICHTUNG EP 3 KOMP. B
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Hardening agent/ Curing agent
- · 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

MUREXIN GmbH

Franz v. Furtenbachstr. 1 A-2700 Wiener Neustadt Tel.: +43 (0)2622/27401

- · Informing department: chemikalieninfo@murexin.com
- · 1.4 Emergency telephone number:

UK National poisons Emergency number.: +44 (0) 870 600 6266

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



environment

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



Acute Tox. 4 H302 Harmful if swallowed.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms







GHS05 GHS07 GHS09

- · **Signal word** Danger
- · Hazard-determining components of labelling:

Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-, reaction products with bisphenol A diglycidyl ether homopolymer

3-aminomethyl-3,5,5-trimethylcyclohexylamine

Benzyl alcohol

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine

(Contd. on page 2)

Printing date 10.08.2023 Version number 8 (replaces version 7) Revision: 10.08.2023

Trade name EPOXY-BESCHICHTUNG EP 3 KOMP. B

(Contd. of page 1)

· Hazard statements

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H410 Very toxic to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.
P261 Avoid breathing mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- Description: Mixture consisting of the following components with harmless additives.

CAS: 100-51-6	Benzyl alcohol	25-50%	
EINECS: 202-859-9 Reg.nr.: 01-2119492630-38- xxxxx	1 Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319		
CAS: 2855-13-2 EINECS: 220-666-8	3-aminomethyl-3,5,5-trimethylcyclohexylamine Skin Corr. 1B, H314; Eye Dam. 1, H318 Acute Tox. 4, H302; Skin Sens. 1A, H317 ATE: LD50 oral: 1,030 mg/kg Specific concentration limit: Skin Sens. 1A; H317: C ≥0.001 %	25-50%	
CAS: 68609-08-5 EC number: 614-657-1	Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-, reaction products with bisphenol A diglycidyl ether homopolymer Skin Corr. 1B, H314; Eye Dam. 1, H318 Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1A, H317 Aquatic Chronic 3, H412		
CAS: 10563-29-8 EINECS: 234-148-4	N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine ↑ Acute Tox. 4, H312	5-10%	
CAS: 61788-46-3 EINECS: 262-977-1	Amines, coco alkyl STOT RE 2, H373; Asp. Tox. 1, H304 Skin Corr. 1B, H314 Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=10) Acute Tox. 4, H302; STOT SE 3, H335	≥1-<2.5%	

- GE

Printing date 10.08.2023 Version number 8 (replaces version 7) Revision: 10.08.2023

Trade name EPOXY-BESCHICHTUNG EP 3 KOMP. B

(Contd. of page 2)

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information

Instantly remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation

Take affected persons into the open air and position comfortably

Supply fresh air and call for doctor for safety reasons.

In case of unconsciousness bring patient into stable side position for transport.

· After skin contact

Instantly wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

- · After eye contact Rinse opened eye for several minutes under running water. Then consult doctor.
- · After swallowing Drink copious amounts of water and provide fresh air. Instantly call for doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**No further relevant information available.
- · **4.3 Indication of any immediate medical attention and special treatment needed**No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents Use fire fighting measures that suit the environment.
- 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Wear protective clothing.
- · 6.2 Environmental precautions:

Do not allow to enter the ground/soil.

Do not allow product to reach sewage system or water bodies.

Inform respective authorities in case product reaches water or sewage system.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent.

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep containers tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)

Printing date 10.08.2023 Version number 8 (replaces version 7) Revision: 10.08.2023

Trade name EPOXY-BESCHICHTUNG EP 3 KOMP. B

(Contd. of page 3)

Prevent formation of aerosols.

- Information about protection against explosions and fires: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- Requirements to be met by storerooms and containers:

Provide floor trough without outlet.

Store only in the original container.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class 8 A
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Components with critical values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the compilation were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures

The usual precautionary measures should be adhered to in handling the chemicals.

Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

Breathing equipment:

Filter A/P2.

In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.

· Hand protection

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

Nitrile rubber, NBR

Fluorocarbon rubber (Viton)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye/face protection Tightly sealed safety glasses.
- Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Physical state

· Colour:

Yellowish

Fluid

· Smell:

Amine-like

(Contd. on page 5)

Printing date 10.08.2023 Version number 8 (replaces version 7) Revision: 10.08.2023

Trade name EPOXY-BESCHICHTUNG EP 3 KOMP. B

(Contd. of page 4) Not determined. · Odour threshold: · Melting point/freezing point: Not determined · Boiling point or initial boiling point and boiling range >200 °C · Flammability Not applicable. · Lower and upper explosion limit · Lower: 1.2 Vol % · Upper: 13 Vol % >100 °C · Flash point: 250 °C · Auto-ignition temperature: · Decomposition temperature: Not determined. · pH Mixture is non-soluble (in water). Viscosity: Kinematic viscosity Not determined. · dynamic at 20 °C: 500 mPas Solubility · Water: Not miscible or difficult to mix · Partition coefficient n-octanol/water (log Not determined. value) 0.1 hPa · Steam pressure at 20 °C: Density and/or relative density 1 g/cm³ Density at 20 °C Not determined. Relative density · Vapour density Not determined. · 9.2 Other information · Appearance: · Form: Fluid · Important information on protection of health and environment, and on safety. · Self-inflammability: Product is not selfigniting. · Explosive properties: Product is not explosive. · Change in condition · Evaporation rate Not determined. · Information with regard to physical hazard classes

Void

0/43363	
· Explosives	Void
Flammable gases	Void
Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit	
flammable gases in contact with water	Void
· Oxidising liquids	Void
Oxidising solids	Void
· Organic peroxides	Void
Corrosive to metals	Void

· Desensitised explosives

Printing date 10.08.2023 Version number 8 (replaces version 7) Revision: 10.08.2023

Trade name EPOXY-BESCHICHTUNG EP 3 KOMP. B

(Contd. of page 5)

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

Corrosive gases/vapours

Poisonous gases/vapours

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity Harmful if swallowed.

· LD/LC5	· LD/LC50 values that are relevant for classification:					
100-51-	100-51-6 Benzyl alcohol					
Oral	LD50	1,230 mg/kg (rat)				
Dermal	LD50	2,000 mg/kg (rbt)				
2855-13	2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine					
Oral	LD50	1,030 mg/kg (ATE)				

- · Skin corrosion/irritation Causes severe skin burns and eye damage.
- · Serious eye damage/irritation Causes serious eye damage.
- 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine

EC 50 37 mg/l (Acartia Tonsa) (DIN 38412 (72h))

42 mg/l (G) (DIN 38412 24h)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB:** Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- 12.7 Other adverse effects
- · Remark: Very toxic for fish
- Additional ecological information:
- General notes:

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

Water danger class (Germany) 3 (Self-assessment): extremely hazardous for water.

(Contd. on page 7)

Printing date 10.08.2023

Version number 8 (replaces version 7)

Trade name EPOXY-BESCHICHTUNG EP 3 KOMP. B

(Contd. of page 6)

Revision: 10.08.2023

Do not allow product to reach ground water, water bodies or sewage system, even in small

Danger to drinking water if even extremely small quantities leak into soil.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

After prior treatment product has to be landfilled or incinerated under adherence to the regulations pertaining to the disposal of especially hazardous waste.

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN number or ID number	
ADR, IMDG, IATA	UN2735
14.2 UN proper shipping name	
ADR	2735 AMINES, LIQUID, CORROSIVE, N.O. (Amines, coco alkyl), ENVIRONMENTAL. HAZARDOUS
IMDG, IATA	AMINES, LIQUID, CORROSIVE, N.O.S. (Amine coco alkyl)
14.3 Transport hazard class(es)	
ADR	
<u> </u>	
Class	8 Corrosive substances.
Label IMDG, IATA	8
Class Label	8 Corrosive substances. 8
14.4 Packing group ADR, IMDG, IATA	II
14.5 Environmental hazards: Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Corrosive substances.
Kemler Number:	80
EMS Number:	F-A,S-B
Segregation groups Stowage Category	(SGG18) Alkalis A

Printing date 10.08.2023 Version number 8 (replaces version 7) Revision: 10.08.2023

Trade name EPOXY-BESCHICHTUNG EP 3 KOMP. B

	(Contd. of page 7
· Segregation Code	SG35 Stow "separated from" SGG1-acids
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
Transport category	2
Tunnel restriction code	E
· UN "Model Regulation":	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (AMINES, COCO ALKYL), 8, 11, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category E1 Hazardous to the Aquatic Environment
- Qualifying quantity (tonnes) for the application of lower-tier requirements 100 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

· Contact: chemikalieninfo@murexin.com (+43 02622/27401)

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

(Contd. on page 9)

Printing date 10.08.2023 Version number 8 (replaces version 7) Revision: 10.08.2023

Trade name EPOXY-BESCHICHTUNG EP 3 KOMP. B

(Contd. of page 8)

Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1B: Skin corrosion/irritation - Category 1B

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation - Category 1A

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.