Printing date 24.01.2024

Revision: 24.01.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

[•] 1.1 Product identifier

- · Trade name EPOXY TOPCOAT EP 100 TC KOMP.A
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- · Application of the substance / the mixture Coating
- 1.3 Details of the supplier of the safety data sheet
- *Manufacturer/Supplier:* MUREXIN GmbH Franz v. Furtenbachstr. 1 A-2700 Wiener Neustadt Tel.: +43 (0)2622/27401
- · Informing department: chemikalieninfo@murexin.com
- 1.4 Emergency telephone number:
- UK National poisons Emergency number.: +44 (0) 870 600 6266

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture
 Classification according to Regulation (EC) No 1272/2008



Skin Irrit. 2	H315 Causes skin irritation.
Eye Irrit. 2	H319 Causes serious eye irritation.
Skin Sens. 1	H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

- [•] Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the GB CLP regulation.
- · Hazard pictograms



· Signal word Warning

- · Hazard-determining components of labelling:
- bis[4-(2,3-epoxypropoxy)phenyl]propane
- Bisphenol F diglycidyl ether, mixture of isomers
- 1,6-bis(2,3-epoxypropoxy)hexane
- 4-morpholinecarbaldehyde
- Hazard statements
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H317 May cause an allergic skin reaction.
- H412 Harmful to aquatic life with long lasting effects.
- Precautionary statements
- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P103 Read carefully and follow all instructions.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P273 Avoid release to the environment.

(Contd. on page 2)

Printing date 24.01.2024

Version number 6

Revision: 24.01.2024

Trade name EPOXY TOPCOAT EP 100 TC KOMP.A

	(Contd. of page 1)			
P280	Wear protective gloves / eye protection / face protection.			
P305+P351+P3	338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact			
	lenses, if present and easy to do. Continue rinsing.			
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.			
P501	Dispose of contents/container in accordance with local/regional/national/ international regulations.			
· Additional information:				
Contains epoxy constituents. May produce an allergic reaction.				
2.3 Other hazards				
· Results of PBT and vPvB assessment				
· PBT: Not applicable.				

• **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture consisting of the following components with harmless additives.

 Dangerous components: 		
CAS: 1675-54-3 EINECS: 216-823-5	 bis[4-(2,3-epoxypropoxy)phenyl]propane ♦ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 EUH205 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5% Skin Irrit. 2; H315: C ≥ 5 % 	50-100%
EC number: 701-263-0 Reg.nr.: 01-2119454392-40- 0003	Bisphenol F diglycidyl ether, mixture of isomers Consisting of: 9003-36-5 formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol Aquatic Chronic 2, H411 Skin Irrit. 2, H315; Skin Sens. 1A, H317	<i>≥</i> 10-<25%
CAS: 933999-84-9 EC number: 618-939-5 Reg.nr.: 01-2119463471-41	 1,6-bis(2,3-epoxypropoxy)hexane Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 Aquatic Chronic 3, H412 	≥10-<25%
CAS: 4394-85-8 EINECS: 224-518-3	4-morpholinecarbaldehyde Skin Sens. 1B, H317	≥0.1-<0.5%

SECTION 4: First aid measures

[•] 4.1 Description of first aid measures

- · General information Instantly remove any clothing soiled by the product.
- · After inhalation
- Supply fresh air and call for doctor for safety reasons.
- In case of unconsciousness bring patient into stable side position for transport.
- · After skin contact
- Instantly wash with water and soap and rinse thoroughly.
- If skin irritation continues, consult a doctor.
- After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor. • After swallowing In case of persistent symptoms consult doctor.

- 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.

(Contd. on page 3)

GB

Printing date 24.01.2024

Version number 6

Revision: 24.01.2024

Trade name EPOXY TOPCOAT EP 100 TC KOMP.A

(Contd. of page 2)

• **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

[•] Suitable extinguishing agents

- CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.
- · 5.2 Special hazards arising from the substance or mixture
- Formation of toxic gases is possible during heating or in case of fire.
- 5.3 Advice for firefighters

· Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective clothing.
- 6.2 Environmental precautions:

Do not allow product to reach sewage system or water bodies. Inform respective authorities in case product reaches water or sewage system. Dilute with much water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections See Section 7 for information on safe handling See Section 8 for information on personal protection equipment. See Section 13 for information on disposal.

SECTION 7: Handling and storage

[•] 7.1 Precautions for safe handling

Keep containers tightly sealed. Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires: No special measures required.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage

· Requirements to be met by storerooms and containers: Store only in the original container.

• Information about storage in one common storage facility: Store away from foodstuffs.

• Further information about storage conditions: Keep container tightly sealed.

· Storage class 10

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- Components with critical values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Additional information: The lists that were valid during the compilation were used as basis.

(Contd. on page 4)

GB

Printing date 24.01.2024

Version number 6

Revision: 24.01.2024

Trade name EPOXY TOPCOAT EP 100 TC KOMP.A

	(Contd. of page
8.2 Exposure controls	
Appropriate engineering controls No furthe	
Individual protection measures, such as pe	ersonal protective equipment
General protective and hygienic measures	
The usual precautionary measures should be	
Keep away from foodstuffs, beverages and foo	
Instantly remove any soiled and impregnated	
Wash hands during breaks and at the end of t	he work.
Avoid contact with the eyes and skin.	
Breathing equipment:	
Filter A/P2.	an broathing filter apparetus. In seen of intensive
	se breathing filter apparatus. In case of intensive
longer exposure use breathing apparatus that	is independent of circulating air.
Hand protection	ion of the nonetration times, rates of diffusion and t
	ion of the penetration times, rates of diffusion and t
degradation Protective gloves.	
	e and resistant to the product/ the substance/ t
preparation.	
Material of gloves	
Butyl rubber, BR	
Nitrile rubber, NBR	
	only depend on the material, but also on further mai
of quality and varies from manufacturer to mai	
Penetration time of glove material	
The exact break trough time has to be found	out by the manufacturer of the protective aloves a
has to be observed.	out by the manufacturer of the protective gloves a
has to be observed.	
has to be observed. • Eye/face protection Safety glasses recomme	
has to be observed.	
has to be observed. • Eye/face protection Safety glasses recomme	
has to be observed. • Eye/face protection Safety glasses recomme	ended during refilling.
has to be observed. Eye/face protection Safety glasses recomme Body protection: Protective work clothing. SECTION 9: Physical and chemical pro	ended during refilling.
has to be observed. Eye/face protection Safety glasses recomme Body protection: Protective work clothing. SECTION 9: Physical and chemical pro 9.1 Information on basic physical and chemical formation General Information	ended during refilling.
has to be observed. Eye/face protection Safety glasses recomme Body protection: Protective work clothing.	ended during refilling.
has to be observed. Eye/face protection Safety glasses recomme Body protection: Protective work clothing. SECTION 9: Physical and chemical pro 9.1 Information on basic physical and chemical General Information Physical state Colour:	ended during refilling.
has to be observed. Eye/face protection Safety glasses recomme Body protection: Protective work clothing. SECTION 9: Physical and chemical pro 9.1 Information on basic physical and chemical General Information Physical state	ended during refilling.
has to be observed. Eye/face protection Safety glasses recomme Body protection: Protective work clothing. SECTION 9: Physical and chemical pro 9.1 Information on basic physical and chem General Information Physical state Colour: Smell: Odour threshold:	ended during refilling.
has to be observed. Eye/face protection Safety glasses recomme Body protection: Protective work clothing. SECTION 9: Physical and chemical pro 9.1 Information on basic physical and chem General Information Physical state Colour: Smell: Odour threshold: Melting point/freezing point:	ended during refilling.
has to be observed. Eye/face protection Safety glasses recomme Body protection: Protective work clothing. SECTION 9: Physical and chemical pro 9.1 Information on basic physical and chem General Information Physical state Colour: Smell: Odour threshold: Melting point/freezing point:	ended during refilling. pperties mical properties Fluid Yellowish Characteristic Not determined.
has to be observed. Eye/face protection Safety glasses recomme Body protection: Protective work clothing. SECTION 9: Physical and chemical pro- 9.1 Information on basic physical and chemical General Information Physical state Colour: Smell: Odour threshold: Melting point/freezing point: Boiling point or initial boiling point and boiling range	ended during refilling. perties mical properties Fluid Yellowish Characteristic Not determined. Not determined 191.5 °C (623-84-7 propane-1,2-diyl diacetate)
has to be observed. Eye/face protection Safety glasses recomme Body protection: Protective work clothing. SECTION 9: Physical and chemical pro- 9.1 Information on basic physical and chemical General Information Physical state Colour: Smell: Odour threshold: Melting point/freezing point: Boiling point or initial boiling point and boiling range Flammability	ended during refilling. pperties mical properties Fluid Yellowish Characteristic Not determined. Not determined
has to be observed. Eye/face protection Safety glasses recomme Body protection: Protective work clothing. SECTION 9: Physical and chemical pro- 9.1 Information on basic physical and chemical General Information Physical state Colour: Smell: Odour threshold: Melting point/freezing point: Boiling point or initial boiling point and boiling range Flammability	ended during refilling. perties mical properties Fluid Yellowish Characteristic Not determined. Not determined 191.5 °C (623-84-7 propane-1,2-diyl diacetate)
has to be observed. Eye/face protection Safety glasses recomme Body protection: Protective work clothing. SECTION 9: Physical and chemical pro 9.1 Information on basic physical and chemical General Information Physical state Colour: Smell: Odour threshold: Melting point/freezing point: Boiling point or initial boiling point and boiling range Flammability Lower and upper explosion limit	ended during refilling. pperties mical properties Fluid Yellowish Characteristic Not determined. Not determined 191.5 °C (623-84-7 propane-1,2-diyl diacetate) Not applicable. Not determined.
has to be observed. Eye/face protection Safety glasses recomme Body protection: Protective work clothing. SECTION 9: Physical and chemical pro 9.1 Information on basic physical and chemical General Information Physical state Colour: Smell: Odour threshold: Melting point/freezing point: Boiling point or initial boiling point and boiling range Flammability Lower and upper explosion limit Lower:	ended during refilling. perties mical properties Fluid Yellowish Characteristic Not determined. Not determined 191.5 °C (623-84-7 propane-1,2-diyl diacetate) Not applicable. Not determined. Not determined.
has to be observed. Eye/face protection Safety glasses recomme Body protection: Protective work clothing. SECTION 9: Physical and chemical pro 9.1 Information on basic physical and chemical General Information Physical state Colour: Smell: Odour threshold: Melting point/freezing point: Boiling point or initial boiling point and boiling range Flammability Lower and upper explosion limit Lower: Upper:	ended during refilling. pperties mical properties Fluid Yellowish Characteristic Not determined. Not determined 191.5 °C (623-84-7 propane-1,2-diyl diacetate) Not applicable. Not determined.
has to be observed. Eye/face protection Safety glasses recomme Body protection: Protective work clothing. SECTION 9: Physical and chemical pro 9.1 Information on basic physical and chem General Information Physical state Colour: Smell: Odour threshold: Melting point/freezing point: Boiling point or initial boiling point and boiling range Flammability Lower and upper explosion limit Lower: Upper: Flash point:	ended during refilling. perties mical properties Fluid Yellowish Characteristic Not determined. Not determined 191.5 °C (623-84-7 propane-1,2-diyl diacetate) Not applicable. Not determined. Not determined.
has to be observed. Eye/face protection Safety glasses recomme Body protection: Protective work clothing. SECTION 9: Physical and chemical pro 9.1 Information on basic physical and chem General Information Physical state Colour: Smell: Odour threshold: Melting point/freezing point: Boiling point or initial boiling point and boiling range Flammability Lower and upper explosion limit Lower: Upper: Flash point: Auto-ignition temperature:	ended during refilling. perties mical properties Fluid Yellowish Characteristic Not determined. Not determined 191.5 °C (623-84-7 propane-1,2-diyl diacetate) Not applicable. Not determined. Not determined. 87 °C (623-84-7 propane-1,2-diyl diacetate)
has to be observed. Eye/face protection Safety glasses recomme Body protection: Protective work clothing. SECTION 9: Physical and chemical pro 9.1 Information on basic physical and chem General Information Physical state Colour: Smell: Odour threshold: Melting point/freezing point: Boiling point or initial boiling point and boiling range Flammability Lower and upper explosion limit Lower: Upper: Flash point: Auto-ignition temperature: Decomposition temperature:	ended during refilling. perties mical properties Fluid Yellowish Characteristic Not determined. Not determined 191.5 °C (623-84-7 propane-1,2-diyl diacetate) Not applicable. Not determined. Not determined. 87 °C (623-84-7 propane-1,2-diyl diacetate) 471 °C (623-84-7 propane-1,2-diyl diacetate)
has to be observed. Eye/face protection Safety glasses recomme Body protection: Protective work clothing. SECTION 9: Physical and chemical pro 9.1 Information on basic physical and chem General Information Physical state Colour: Smell: Odour threshold: Melting point/freezing point: Boiling point or initial boiling point and boiling range Flammability Lower and upper explosion limit Lower: Upper: Flash point: Auto-ignition temperature: pecomposition temperature: pH at 20 °C Viscosity:	ended during refilling. perties mical properties Fluid Yellowish Characteristic Not determined. Not determined 191.5 °C (623-84-7 propane-1,2-diyl diacetate) Not applicable. Not determined. 87 °C (623-84-7 propane-1,2-diyl diacetate) 471 °C (623-84-7 propane-1,2-diyl diacetate) Not determined.
has to be observed. Eye/face protection Safety glasses recomme Body protection: Protective work clothing. SECTION 9: Physical and chemical pro 9.1 Information on basic physical and chem General Information Physical state Colour: Smell: Odour threshold: Melting point/freezing point: Boiling point or initial boiling point and boiling range Flammability Lower and upper explosion limit Lower: Upper: Flash point: Auto-ignition temperature: Decomposition temperature: pH at 20 °C Viscosity: Kinematic viscosity	ended during refilling. perties mical properties Fluid Yellowish Characteristic Not determined. Not determined 191.5 °C (623-84-7 propane-1,2-diyl diacetate) Not applicable. Not determined. 87 °C (623-84-7 propane-1,2-diyl diacetate) 471 °C (623-84-7 propane-1,2-diyl diacetate) Not determined.
has to be observed. Eye/face protection Safety glasses recomme Body protection: Protective work clothing. SECTION 9: Physical and chemical pro 9.1 Information on basic physical and chem General Information Physical state Colour: Smell: Odour threshold: Melting point/freezing point: Boiling point or initial boiling point and boiling range Flammability Lower and upper explosion limit Lower: Upper: Flash point: Auto-ignition temperature: Decomposition temperature: pH at 20 °C Viscosity: Kinematic viscosity	ended during refilling. perties mical properties Fluid Yellowish Characteristic Not determined. Not determined 191.5 °C (623-84-7 propane-1,2-diyl diacetate) Not applicable. Not determined. 87 °C (623-84-7 propane-1,2-diyl diacetate) 471 °C (623-84-7 propane-1,2-diyl diacetate) 471 °C (623-84-7 propane-1,2-diyl diacetate) Not determined. 6-8
has to be observed. Eye/face protection Safety glasses recomme Body protection: Protective work clothing. SECTION 9: Physical and chemical pro- 9.1 Information on basic physical and chemical General Information Physical state Colour: Smell: Odour threshold: Melting point/freezing point: Boiling point or initial boiling point and	ended during refilling. perties mical properties Fluid Yellowish Characteristic Not determined. Not determined 191.5 °C (623-84-7 propane-1,2-diyl diacetate) Not applicable. Not determined. 87 °C (623-84-7 propane-1,2-diyl diacetate) 471 °C (623-84-7 propane-1,2-diyl diacetate) 471 °C (623-84-7 propane-1,2-diyl diacetate) Not determined. 6-8 Not determined.
has to be observed. Eye/face protection Safety glasses recomme Body protection: Protective work clothing. SECTION 9: Physical and chemical pro 9.1 Information on basic physical and chem General Information Physical state Colour: Smell: Odour threshold: Melting point/freezing point: Boiling point or initial boiling point and boiling range Flammability Lower and upper explosion limit Lower: Upper: Flash point: Auto-ignition temperature: Decomposition temperature: pH at 20 °C Viscosity: Kinematic viscosity dynamic at 20 °C:	ended during refilling. perties mical properties Fluid Yellowish Characteristic Not determined. Not determined 191.5 °C (623-84-7 propane-1,2-diyl diacetate) Not applicable. Not determined. 87 °C (623-84-7 propane-1,2-diyl diacetate) 471 °C (623-84-7 propane-1,2-diyl diacetate) 471 °C (623-84-7 propane-1,2-diyl diacetate) Not determined. 6-8 Not determined.

Printing date 24.01.2024

Version number 6

Revision: 24.01.2024

Trade name EPOXY TOPCOAT EP 100 TC KOMP.A

	(Contd. of page
Partition coefficient n-octanol/water (log	
value)	Not determined.
Steam pressure at 20 °C:	0.8 hPa (Bisphenol F diglycidyl ether, mixture isomers)
Density and/or relative density	
Density at 20 °C	1.1 g/cm³
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Fluid
Important information on protection of hea	alth
and environment, and on safety.	
Self-inflammability:	Product is not selfigniting.
Explosive properties:	Product is not explosive.
Solvent content:	
Solids content:	0.4 %
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical haz	ard
classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Flammable solids Self-reactive substances and mixtures	Void Void
Self-reactive substances and mixtures	
Self-reactive substances and mixtures Pyrophoric liquids	Void
Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids	Void Void
Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures	Void Void Void
Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit	Void Void Void
Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water	Void Void Void Void
Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water Oxidising liquids	Void Void Void Void Void
Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water	Void Void Void Void Void Void
Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water Oxidising liquids Oxidising solids	Void Void Void Void Void Void Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

10.2 Chemical stability

· Conditions to be avoided: To avoid thermal decomposition do not overheat.

• 10.3 Possibility of hazardous reactions Reacts with amines

• **10.4 Conditions to avoid** No further relevant information available.

· 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products: None

(Contd. on page 6)

GB

Printing date 24.01.2024

Version number 6

Revision: 24.01.2024

Trade name EPOXY TOPCOAT EP 100 TC KOMP.A

(Contd. of page 5)

SECTION 11: Toxicological information

• **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008** • **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:

1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane

Oral LD50 >2,000 mg/kg (rat)

Dermal LD50 >2,000 mg/kg (rat)

4394-85-8 4-morpholinecarbaldehyde

Dermal LD50 >18,300 mg/kg (rabbit)

- Skin corrosion/irritation Causes skin irritation.
- Serious eye damage/irritation Causes serious eye irritation.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) -
- · 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Toxic for fish

· Additional ecological information:

· General notes:

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Water hazard class (Germany) 2 (Self-assessment): hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

[•] 13.1 Waste treatment methods

- Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleaning agent: Water, if necessary with cleaning agent.

(Contd. on page 7)

Printing date 24.01.2024

Version number 6

Revision: 24.01.2024

Trade name EPOXY TOPCOAT EP 100 TC KOMP.A

(Contd. of page 6)

14.1 UN number or ID number	
ADR, IMDG, IATA	UN3082
14.2 UN proper shipping name ADR	3082 ENVIRONMENTALLY HAZARDOL SUBSTANCE, LIQUID, N.O.S. (bis[4-(2, epoxypropoxy)phenyl]propane, Bisphenol diglycidyl ether, mixture of isomers)
IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANC LIQUID, N.O.S. (bis[4-(2,3-epoxypropoxy)phen propane, Bisphenol F diglycidyl ether, mixture isomers), MARINE POLLUTANT
ΙΑΤΑ	ENVIRONMENTALLY HAZARDOUS SUBSTANC LIQUID, N.O.S. (bis[4-(2,3-epoxypropoxy)phen propane, Bisphenol F diglycidyl ether, mixture isomers)
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class	9 Miscellaneous dangerous substances a articles.
Label	9
14.4 Packing group ADR, IMDG, IATA	<i>III</i>
14.5 Environmental hazards:	Product contains environmentally hazardo substances: bis[4-(2,3-epoxypropoxy)phen propane
Marine pollutant:	No Symbol (fish and tree)
Special marking (ADR): Special marking (IATA):	Symbol (fish and tree) Symbol (fish and tree)
14.6 Special precautions for user	Warning: Miscellaneous dangerous substances a articles.
Kemler Number: EMS Number:	90 F-A,S-F
Stowage Category	A
14.7 Maritime transport in bulk accord IMO instruments	i ng to Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ) Transport category	5L 3
Tunnel restriction code	(-)

30%

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.01.2024

Version number 6

Revision: 24.01.2024

Trade name EPOXY TOPCOAT EP 100 TC KOMP.A

(Contd. of page 7) • UN "Model Regulation": UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BIS[4-(2,3-EPOXYPROPOXY)PHENYL]PROPANE, BISPHENOL F DIGLYCIDYL ETHER, MIXTURE OF ISOMERS), 9, III

SECTION 15: Regulatory information

[•] 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

[.] Poisons Act

Regulated explosives precursors

7664-38-2 phosphoric acid

Regulated poisons

None of the ingredients is listed.

Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category E2 Hazardous to the Aquatic Environment
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

· National regulations

Additional classification according to Decree on Hazardous Materials, Annex II:

Carcinogenic hazardous material group III (dangerous)

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

EUH205 Contains epoxy constituents. May produce an allergic reaction.

• Contact: chemikalieninfo@murexin.com (+43 02622/27401)

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

(Contd. on page 9)

GB

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.01.2024

Version number 6

Revision: 24.01.2024

Trade name EPOXY TOPCOAT EP 100 TC KOMP.A

	(Contd. of page 8)
vPvB: very Persistent and very Bioaccumulative	
Skin Irrit. 2: Skin corrosion/irritation – Category 2	
Eve Irrit. 2: Serious eve damage/eve irritation – Category 2	
Śkin Sens. 1: Skin sensitisation – Category 1	
Skin Sens. 1A: Skin sensitisation – Category 1A	
Skin Sens. 1B: Skin sensitisation – Category 1B	
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2	
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3	

• * Data compared to the previous version altered.