Safety data sheet
according to UK REACH

Printing date 11.08.2025 Version number 5 (replaces version 4) Revision: 11.08.2025

*
SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name EPOXY - CLEARCOAT CC 200 KOMP. A**

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.

· **Application of the substance / the mixture** Coating

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**
MUREXIN GmbH
Franz v. Furtenbachstr. 1
A-2700 Wiener Neustadt
Tel.: +43 (0)2622/27401

· **Informing department:** chemikalieninfo@murexin.com

· **1.4 Emergency telephone number:**
UK National poisons Emergency number.: +44 (0) 870 600 6266

*
SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**

GHS08 health hazard

Repr. 1A H360F May damage fertility.

GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

GHS07

Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2 H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.

· **Hazard pictograms**

GHS07 GHS08 GHS09

· **Signal word** Danger

· **Hazard-determining components of labelling:**
Bisphenol A epoxy resin
1,6-bis(2,3-epoxypropoxy)hexane
Bisphenol F diglycidyl ether, mixture of isomers

· **Hazard statements**
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H360F May damage fertility.

(Contd. on page 2)

Safety data sheet
according to UK REACH

Printing date 11.08.2025 Version number 5 (replaces version 4) Revision: 11.08.2025

Trade name EPOXY - CLEARCOAT CC 200 KOMP. A

(Contd. of page 1)

H411 Toxic to aquatic life with long lasting effects.

· **Precautionary statements**

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Additional information:**
Restricted to professional users.
Contains epoxy constituents. May produce an allergic reaction.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

*
SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**

· **Description:** Mixture consisting of the following components with harmless additives.

· **Dangerous components:**

CAS: 1675-54-3 EINECS: 216-823-5	Bisphenol A epoxy resin Aquatic Chronic 2, H411 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 EUH205 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5% Skin Irrit. 2; H315: C ≥ 5 %	50-100%
Reg.nr.: 01-2119454392-40-0003	Bisphenol F diglycidyl ether, mixture of isomers Consisting of: 9003-36-5 Bisphenol-F-epichlorohydrin resin Aquatic Chronic 2, H411 Skin Irrit. 2, H315; Skin Sens. 1A, H317	≥10-<25%
CAS: 933999-84-9 Reg.nr.: 01-2119463471-41	1,6-bis(2,3-epoxypropoxy)hexane Repr. 1A, H360F Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 Aquatic Chronic 3, H412	≥10-<25%

*
SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **After inhalation**
Supply fresh air and call for doctor for safety reasons.
In case of unconsciousness bring patient into stable side position for transport.

· **After skin contact** Instantly wash with water and soap and rinse thoroughly.

· **After eye contact**
Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

(Contd. on page 3)

Safety data sheet
according to UK REACH

Printing date 11.08.2025 Version number 5 (replaces version 4) Revision: 11.08.2025

Trade name EPOXY - CLEARCOAT CC 200 KOMP. A

(Contd. of page 2)

· **After swallowing** In case of persistent symptoms consult doctor.
· **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
· **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

*
SECTION 5: Firefighting measures

· **5.1 Extinguishing media**
· **Suitable extinguishing agents** Use fire fighting measures that suit the environment.
· **5.2 Special hazards arising from the substance or mixture**
No further relevant information available.
· **5.3 Advice for firefighters**
· **Protective equipment:** No special measures required.

*
SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective clothing.
· **6.2 Environmental precautions:**
Do not allow product to reach sewage system or water bodies.
Inform respective authorities in case product reaches water or sewage system.
· **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of contaminated material as waste according to item 13.
· **6.4 Reference to other sections**
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

*
SECTION 7: Handling and storage

· **7.1 Precautions for safe handling** Keep containers tightly sealed.
· **Information about protection against explosions and fires:** No special measures required.

· **7.2 Conditions for safe storage, including any incompatibilities**
· **Storage**
· **Requirements to be met by storerooms and containers:** Store only in the original container.
· **Information about storage in one common storage facility:**
Do not store together with reducing agents, heavy-metal compounds, acids and alkalis.
· **Further information about storage conditions:** Keep container tightly sealed.
· **Storage class** 6.1 C
· **7.3 Specific end use(s)** No further relevant information available.

*
SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**
· **Components with critical values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
· **Additional information:** The lists that were valid during the compilation were used as basis.

· **8.2 Exposure controls**
· **Appropriate engineering controls** No further data; see section 7.

(Contd. on page 4)

Safety data sheet
according to UK REACH

Printing date 11.08.2025 Version number 5 (replaces version 4) Revision: 11.08.2025

Trade name EPOXY - CLEARCOAT CC 200 KOMP. A

(Contd. of page 3)

· **Individual protection measures, such as personal protective equipment**
· **General protective and hygienic measures**
The usual precautionary measures should be adhered to in handling the chemicals.
Keep away from foodstuffs, beverages and food.
Instantly remove any soiled and impregnated garments.
Wash hands during breaks and at the end of the work.
Avoid contact with the eyes and skin.
· **Breathing equipment:** Breathing protection recommended.
· **Hand protection** Protective gloves.
· **Material of gloves**
Nitrile rubber, NBR
Butyl rubber, BR
· **Penetration time of glove material**
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
· **Eye/face protection** Safety glasses
· **Body protection:** Protective work clothing.

*

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**	
· **General Information**	
· **Colour:**	Yellow
· **Smell:**	Characteristic
· **Boiling point or initial boiling point and boiling range**	>200 °C
· **Flash point:**	>100 °C
· **pH**	6-8
· **Viscosity:**	
· **dynamic at 20 °C:**	2300 mPas
· **Solubility**	
· **Water:**	not miscible
· **Steam pressure at 20 °C:**	< 5 hPa
· **Density and/or relative density**	
· **Density at 20 °C**	1.2 g/cm³

· **9.2 Other information**	
· **Appearance:**	
· **Form:**	Fluid
· **Important information on protection of health and environment, and on safety.**	
· **Self-inflammability:**	Product is not selfigniting.
· **Explosive properties:**	Product is not explosive.

· **Information with regard to physical hazard classes**	
· **Explosives**	Void
· **Flammable gases**	Void
· **Aerosols**	Void
· **Oxidising gases**	Void
· **Gases under pressure**	Void
· **Flammable liquids**	Void
· **Flammable solids**	Void
· **Self-reactive substances and mixtures**	Void
· **Pyrophoric liquids**	Void
· **Pyrophoric solids**	Void

(Contd. on page 5)

Safety data sheet
according to UK REACH

Printing date 11.08.2025 Version number 5 (replaces version 4) Revision: 11.08.2025

Trade name EPOXY - CLEARCOAT CC 200 KOMP. A

(Contd. of page 4)

· **Self-heating substances and mixtures**	Void
· **Substances and mixtures, which emit flammable gases in contact with water**	Void
· **Oxidising liquids**	Void
· **Oxidising solids**	Void
· **Organic peroxides**	Void
· **Corrosive to metals**	Void
· **Desensitised explosives**	Void

*

SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.
· **10.2 Chemical stability**
· **Conditions to be avoided:** No decomposition if used according to specifications.
· **10.3 Possibility of hazardous reactions** No dangerous reactions known
· **10.4 Conditions to avoid** No further relevant information available.
· **10.5 Incompatible materials:** No further relevant information available.
· **10.6 Hazardous decomposition products:** None

*

SECTION 11: Toxicological information

· **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
· **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values that are relevant for classification:**

1675-54-3 Bisphenol A epoxy resin

Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)

· **Primary irritant effect:**
· **Skin corrosion/irritation**
Causes skin irritation.
· **Serious eye damage/irritation**
Causes serious eye irritation.
· **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
· **Carcinogenicity** Based on available data, the classification criteria are not met.
· **Reproductive toxicity**
May damage fertility.
· **STOT-single exposure** Based on available data, the classification criteria are not met.
· **STOT-repeated exposure** Based on available data, the classification criteria are not met.
· **Aspiration hazard** Based on available data, the classification criteria are not met.
· **Additional toxicological information:**
· **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)** -
· **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

*

SECTION 12: Ecological information

· **12.1 Toxicity**
· **Aquatic toxicity:** No further relevant information available.
· **12.2 Persistence and degradability** No further relevant information available.
· **12.3 Bioaccumulative potential** No further relevant information available.
· **12.4 Mobility in soil** No further relevant information available.

(Contd. on page 6)

Safety data sheet
according to UK REACH

Printing date 11.08.2025 Version number 5 (replaces version 4) Revision: 11.08.2025

Trade name EPOXY - CLEARCOAT CC 200 KOMP. A

(Contd. of page 5)

· **12.5 Results of PBT and vPvB assessment**
· **PBT:** Not applicable.
· **vPvB:** Not applicable.
· **12.6 Endocrine disrupting properties**
The product does not contain substances with endocrine disrupting properties.
· **12.7 Other adverse effects**
· **Remark:** Toxic for fish
· **Additional ecological information:**
· **General notes:**
Toxic for aquatic organisms
Also poisonous for fish and plankton in water bodies.
Water hazard class (Germany) 2 (Self-assessment): hazardous for water.
Do not allow product to reach ground water, water bodies or sewage system.
Danger to drinking water if even small quantities leak into soil.

*
SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**
· **Recommendation**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**
· **Recommendation:** Disposal must be made according to official regulations.

*
SECTION 14: Transport information

· **14.1 UN number or ID number**	
· **ADR, IMDG, IATA**	UN3082
· **14.2 UN proper shipping name**	
· **ADR**	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A epoxy resin, Bisphenol F diglycidyl ether, mixture of isomers)
· **IMDG**	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A epoxy resin, Bisphenol F diglycidyl ether, mixture of isomers), MARINE POLLUTANT
· **IATA**	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A epoxy resin, Bisphenol F diglycidyl ether, mixture of isomers)
· **14.3 Transport hazard class(es)**	
· **ADR, IMDG, IATA**	
· **Class**	9 Miscellaneous dangerous substances and articles.
· **Label**	9
· **14.4 Packing group**	
· **ADR, IMDG, IATA**	III

(Contd. on page 7)

Safety data sheet
according to UK REACH

Printing date 11.08.2025 Version number 5 (replaces version 4) Revision: 11.08.2025

Trade name EPOXY - CLEARCOAT CC 200 KOMP. A

(Contd. of page 6)

· **14.5 Environmental hazards:**	Product contains environmentally hazardous substances: Bisphenol A epoxy resin
· **Marine pollutant:**	Yes Symbol (fish and tree)
· **Special marking (ADR):**	Symbol (fish and tree)
· **Special marking (IATA):**	Symbol (fish and tree)
· **14.6 Special precautions for user**	Warning: Miscellaneous dangerous substances and articles.
· **Kemler Number:**	90
· **EMS Number:**	F-A,S-F
· **Stowage Category**	A
· **14.7 Maritime transport in bulk according to IMO instruments**	Not applicable.
· **Transport/Additional information:**	
· **ADR**	
· **Limited quantities (LQ)**	5L
· **Transport category**	3
· **Tunnel restriction code**	(-)
· **UN "Model Regulation":**	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL A EPOXY RESIN, BISPHENOL F DIGLYCIDYL ETHER, MIXTURE OF ISOMERS), 9, III

*
SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
· **Poisons Act**

· **Regulated explosives precursors**
None of the ingredients is listed.

· **Regulated poisons**
None of the ingredients is listed.

· **Reportable explosives precursors**
None of the ingredients is listed.

· **Reportable poisons**
None of the ingredients is listed.

· **Directive 2012/18/EU**
· **Named dangerous substances - ANNEX I** None of the ingredients is listed.
· **Seveso category** E2 Hazardous to the Aquatic Environment
· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t
· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

*
SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**
H315 Causes skin irritation.

(Contd. on page 8)

Safety data sheet
according to UK REACH

Trade name EPOXY - CLEARCOAT CC 200 KOMP. A

(Contd. of page 7)

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H360F May damage fertility.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
EUH205 Contains epoxy constituents. May produce an allergic reaction.

· **Contact:** chemikalieninfo@murexin.com (+43 02622/27401)
· **Abbreviations and acronyms:**
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organisation
ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1A: Skin sensitisation – Category 1A
Repr. 1A: Reproductive toxicity – Category 1A
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· *** Data compared to the previous version altered.**