Printing date 16.09.2021 Version number 9 (replaces version 4) Revision: 16.09.2021

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name EPOXY-CLEARCOAT CC 200 KOMP B
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Hardening agent/ Curing agent
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

MUREXIN GmbH

Franz v. Furtenbachstr. 1 A-2700 Wiener Neustadt Tel.: +43 (0)2622/27401

- · Informing department: chemikalieninfo@murexin.com
- · 1.4 Emergency telephone number:

UK National poisons Emergency number.: +44 (0) 870 600 6266

## **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



environment

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



Acute Tox. 4 H302 Harmful if swallowed.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS05 GHS07 GHS09

- Signal word Danger
- · Hazard-determining components of labelling:

Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-, reaction products with bisphenol A diglycidyl ether homopolymer

3-aminomethyl-3,5,5-trimethylcyclohexylamine

Benzyl alcohol

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine

(Contd. on page 2)

Printing date 16.09.2021 Version number 9 (replaces version 4) Revision: 16.09.2021

#### Trade name EPOXY-CLEARCOAT CC 200 KOMP B

(Contd. of page 1)

#### · Hazard statements

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H410 Very toxic to aquatic life with long lasting effects.

#### Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P362+P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

## SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture consisting of the following components with harmless additives.

· Dangerous components:		
CAS: 100-51-6 EINECS: 202-859-9 Reg.nr.: 01-2119492630-38- xxxxx	Benzyl alcohol  O Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	25-50%
CAS: 2855-13-2 EINECS: 220-666-8	3-aminomethyl-3,5,5-trimethylcyclohexylamine Skin Corr. 1B, H314 Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317 Aquatic Chronic 3, H412	25-50%
CAS: 68609-08-5 EC number: 614-657-1	Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-, reaction products with bisphenol A diglycidyl ether homopolymer  Skin Corr. 1B, H314; Eye Dam. 1, H318 Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1A, H317 Aquatic Chronic 3, H412	25-50%
CAS: 10563-29-8 EINECS: 234-148-4	N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine	5-10%
CAS: 61788-46-3 EINECS: 262-977-1	Amines, coco alkyl  STOT RE 2, H373; Asp. Tox. 1, H304 Skin Corr. 1B, H314 Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=10) Acute Tox. 4, H302; STOT SE 3, H335	1-2.5%

GE

Printing date 16.09.2021 Version number 9 (replaces version 4) Revision: 16.09.2021

#### Trade name EPOXY-CLEARCOAT CC 200 KOMP B

(Contd. of page 2)

#### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information Instantly remove any clothing soiled by the product.
- · After inhalation

Take affected persons into the open air and position comfortably

Seek medical treatment in case of complaints.

In case of unconsciousness bring patient into stable side position for transport.

· After skin contact

If skin irritation continues, consult a doctor.

Instantly wash with water and soap and rinse thoroughly.

- · After eye contact Rinse opened eye for several minutes under running water. Then consult doctor.
- · After swallowing Drink copious amounts of water and provide fresh air. Instantly call for doctor.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents

Use fire fighting measures that suit the environment.

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

- For safety reasons unsuitable extinguishing agents Water with a full water jet.
- · 5.2 Special hazards arising from the substance or mixture

Formation of poisonous gases during heating or in fires.

- 5.3 Advice for firefighters
- · Protective equipment: Put on breathing apparatus.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

#### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Put on breathing apparatus.

Wear protective clothing.

6.2 Environmental precautions:

Do not allow to enter the ground/soil.

Do not allow product to reach sewage system or water bodies.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent.

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

### SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep containers tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)

Printing date 16.09.2021 Version number 9 (replaces version 4) Revision: 16.09.2021

#### Trade name EPOXY-CLEARCOAT CC 200 KOMP B

(Contd. of page 3)

Prevent formation of aerosols.

- Information about protection against explosions and fires: Keep breathing equipment ready.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- Requirements to be met by storerooms and containers:

Provide floor trough without outlet.

Store only in the original container.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class 8 A
- · 7.3 Specific end use(s) No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Components with critical values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the compilation were used as basis.
- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see item 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures

The usual precautionary measures should be adhered to in handling the chemicals.

Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air. Filter A/P2.

- · Hand protection Protective gloves.
- Material of gloves

Nitrile rubber, NBR

Fluorocarbon rubber (Viton)

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye/face protection Tightly sealed safety glasses.
- Body protection: Protective work clothing.

## SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour: Light yellow · Smell: Amine-like

· Boiling point or initial boiling point and

boiling range 205 °C

· Lower and upper explosion limit

Lower: 1.2 Vol %
 Upper: 13 Vol %
 Flash point: >100 °C

(Contd. on page 5)

Printing date 16.09.2021 Version number 9 (replaces version 4) Revision: 16.09.2021

#### Trade name EPOXY-CLEARCOAT CC 200 KOMP B

(Contd. of page 4)

· Self-inflammability: Product is not selfigniting.

Decomposition temperature: Not determined. Not determined. Not determined.

Viscosity:

dynamic at 20 °C: 500 mPas

· Solubility

· **Water:** Not miscible or difficult to mix

· Partition coefficient n-octanol/water (log

value) Not determined.

· Steam pressure at 20 °C: 0.1 hPa

· Density and/or relative density

Density at 20 °C 1 g/cm³

Relative densityVapour densityNot determined.Not determined.

· 9.2 Other information

· Appearance:

· Form: Liquid

Important information on protection of health

and environment, and on safety.

Ignition temperature: 250 °C

• Explosive properties: Product is not explosive.

Solvent content:

· Solids content: 0.0 %

· Change in condition

· Evaporation rate Not determined.

Information with regard to physical hazard

classes Void · Explosives Void Flammable gases · Aerosols Void · Oxidising gases Void · Gases under pressure Void Flammable liquids Void Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void Pyrophoric solids Void Self-heating substances and mixtures Void · Substances and mixtures, which emit Void

flammable gases in contact with water

Oxidising liquids
Oxidising solids
Organic peroxides
Corrosive to metals
Desensitised explosives
Void
Void
Void
Void
Void

### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 6)

Printing date 16.09.2021

Version number 9 (replaces version 4)

#### Trade name EPOXY-CLEARCOAT CC 200 KOMP B

(Contd. of page 5)

Revision: 16.09.2021

· 10.6 Hazardous decomposition products:

Corrosive gases/vapours Poisonous gases/vapours

### SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity

Harmful if swallowed.

LD/LC50 values that are relevant for classification:

#### 100-51-6 Benzyl alcohol

Oral LD50 1,230 mg/kg (rat) Dermal LD50 2,000 mg/kg (rbt)

Skin corrosion/irritation

Causes severe skin burns and eye damage.

- Serious eye damage/irritation
- Causes serious eye damage.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

## **SECTION 12: Ecological information**

- · 12.1 Toxicity
- Aquatic toxicity:

### 2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine

EC 50 37 mg/l (Pseudokirchneriella subcapitata (Alge)) (DIN 38412 (72h)) 42 mg/l (Daphnia magna (Großer Wasserfloh)) (DIN 38412 24h)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
- · Remark: Very toxic for fish
- · Additional ecological information:
- General notes:

Very toxic for aquatic organisms

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Water danger class (Germany) 3 (Self-assessment): extremely hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system, even in small quantities.

(Contd. on page 7)

Printing date 16.09.2021

Version number 9 (replaces version 4)

#### Trade name EPOXY-CLEARCOAT CC 200 KOMP B

(Contd. of page 6)

Revision: 16.09.2021

Danger to drinking water if even extremely small quantities leak into soil.

## SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

After prior treatment product has to be landfilled or incinerated under adherence to the regulations pertaining to the disposal of especially hazardous waste.

Can be deposited with household garbage after solidification following consultation with the operator of the waste disposal facility and the pertinent authorities and under adherence to the necessary technical regulations.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN number or ID number ADR, IMDG, IATA	UN2735
14.2 UN proper shipping name ADR IMDG, IATA	2735 AMINES, LIQUID, CORROSIVE, N.O. (Amines, coco alkyl), ENVIRONMENTALI HAZARDOUS AMINES, LIQUID, CORROSIVE, N.O.S. (Amine coco alkyl)
14.3 Transport hazard class(es)	coco aikyii
ADR	
Class	8 Corrosive substances.
Label	8
IMDG, IATA  Class	8 Corrosive substances.
Label	8
14.4 Packing group ADR, IMDG, IATA	II
14.5 Environmental hazards: Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user Kemler Number: EMS Number: Segregation groups	Warning: Corrosive substances. 80 F-A,S-B Alkalis
Stowage Category	A
Segregation Code	SG35 Stow "separated from" SGG1-acids

Printing date 16.09.2021 Version number 9 (replaces version 4) Revision: 16.09.2021

#### Trade name EPOXY-CLEARCOAT CC 200 KOMP B

	(Contd. of page 7
· 14.7 Maritime transport in bulk according IMO instruments	to Not applicable.
· Transport/Additional information:	
·ADR	
· Limited quantities (LQ)	1L
· Transport category	2
Tunnel restriction code	E
· UN "Model Regulation":	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (AMINES, COCO ALKYL), 8, II, ENVIRONMENTALLY HAZARDOUS

### SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category E1 Hazardous to the Aquatic Environment
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 100 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

· Contact: chemikalieninfo@murexin.com (+43 02622/27401)

#### · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - Category 4

(Contd. on page 9)

Printing date 16.09.2021

Version number 9 (replaces version 4)

#### Trade name EPOXY-CLEARCOAT CC 200 KOMP B

(Contd. of page 8)

Revision: 16.09.2021

Skin Corr. 1B: Skin corrosion/irritation - Category 1B Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1A: Skin sensitisation – Category 1A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

\* \* Data compared to the previous version altered.