Printing date 31.10.2023 Version number 42 Revision: 31.10.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name ESTRICHVERDÜBELUNG EV 15 KOMP. B
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Hardening agent/ Curing agent
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MUREXIN GmbH

Franz v. Furtenbachstr. 1 A-2700 Wiener Neustadt Tel.: +43 (0)2622/27401

- · Informing department: chemikalieninfo@murexin.com
- · 1.4 Emergency telephone number:

UK National poisons Emergency number.: +44 (0) 870 600 6266

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.



corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



environment

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



Skin Sens. 1

H317 May cause an allergic skin reaction.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms









GHS05 GHS07 GHS08 GHS09

- · Signal word Danger
- · Hazard-determining components of labelling:

Liquid Epoxy Resin-Isophoronediamine adduct

4-nonylphenol, branched

m-phenylenebis(methylamine)

(Contd. on page 2)

Printing date 31.10.2023 Version number 42 Revision: 31.10.2023

Trade name ESTRICHVERDÜBELUNG EV 15 KOMP. B

(Contd. of page 1)

· Hazard statements

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H361 Suspected of damaging fertility or the unborn child. H410 Very toxic to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P362+P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

Description: Mixture consisting of the following components with harmless additives.

Dangerous components:		
CAS: 100-51-6 EINECS: 202-859-9 Reg.nr.: 01-2119492630-38- xxxxx	Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	25-50%
CAS: 38294-64-3 NLP: 500-101-4	Liquid Epoxy Resin-Isophoronediamine adduct Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Chronic 3, H412	25-50%
CAS: 1477-55-0 EINECS: 216-032-5	m-phenylenebis(methylamine) Skin Corr. 1B, H314; Eye Dam. 1, H318 Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1, H317 Aquatic Chronic 3, H412	≥10-<25%
CAS: 84852-15-3 EINECS: 284-325-5	4-nonylphenol, branched Repr. 2, H361fd Skin Corr. 1B, H314 Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Acute Tox. 4, H302	≥3-<5%

·SVHC

84852-15-3 4-nonylphenol, branched

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information Instantly remove any clothing soiled by the product.

(Contd. on page 3)

(Contd. of page 2)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 31.10.2023 Version number 42 Revision: 31.10.2023

Trade name ESTRICHVERDÜBELUNG EV 15 KOMP. B

After inhalation
 Take affected persons into the open air and position comfortably

Supply fresh air and call for doctor for safety reasons.

In case of unconsciousness bring patient into stable side position for transport.

· After skin contact

Instantly wash with water and soap and rinse thoroughly.

Seek medical treatment.

- · After eye contact Rinse opened eye for several minutes under running water. Then consult doctor.
- After swallowing Drink copious amounts of water and provide fresh air. Instantly call for doctor.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

• **4.3 Indication of any immediate medical attention and special treatment needed**No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam. Use fire fighting measures that suit the environment.

5.2 Special hazards arising from the substance or mixture

Formation of poisonous gases during heating or in fires.

- 5.3 Advice for firefighters
- · Protective equipment: Put on breathing apparatus.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Put on breathing apparatus.

Wear protective clothing.

6.2 Environmental precautions:

Do not allow to enter the ground/soil.

Do not allow product to reach sewage system or water bodies.

Inform respective authorities in case product reaches water or sewage system.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent.

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep containers tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Open and handle container with care.

Prevent formation of aerosols.

Information about protection against explosions and fires: Keep breathing equipment ready.

(Contd. on page 4)

Printing date 31.10.2023 Version number 42 Revision: 31.10.2023

Trade name ESTRICHVERDÜBELUNG EV 15 KOMP. B

(Contd. of page 3)

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- Requirements to be met by storerooms and containers:

Provide floor trough without outlet.

Store only in the original container.

- Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Protect from frost.

Keep container tightly sealed.

- Storage class 8 A
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Components with critical values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the compilation were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures

The usual precautionary measures should be adhered to in handling the chemicals.

Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Breathing equipment:

Filter A/P2.

In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.

· Hand protection

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

Butyl rubber, BR

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eve/face protection Safety glasses
- **Body protection:** Protective work clothing.

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Physical state Fluid · Colour: Yellowish

(Contd. on page 5)

Printing date 31.10.2023 Version number 42 Revision: 31.10.2023

Trade name ESTRICHVERDÜBELUNG EV 15 KOMP. B

(Contd. of page 4) Amine-like · Smell: · Odour threshold: Not determined. · Boiling point or initial boiling point and >190 °C boiling range · Flammability Not applicable. Lower and upper explosion limit 1.3 Vol % · Lower: · Upper: 13 Vol % >90 °C · Flash point: 380 °C Auto-ignition temperature: · Decomposition temperature: Not determined. · pH Mixture is non-soluble (in water). · Viscosity: · Kinematic viscosity Not determined. · dynamic at 20 °C: 190 mPas · Solubility · Water: Not miscible or difficult to mix · Partition coefficient n-octanol/water (log Not determined. value) · Steam pressure at 20 °C: 0.1 hPa · Density and/or relative density 1 g/cm³ Density at 20 °C Not determined. Relative density Not determined. · Vapour density · 9.2 Other information · Appearance: · Form: Fluid · Important information on protection of health and environment, and on safety. · Self-inflammability: Product is not selfigniting. Explosive properties: Product is not explosive. · Change in condition · Evaporation rate Not determined.

> Void Void

· Information with regard to physical haz	ard
classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit	
flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void

Corrosive to metals

· Desensitised explosives

Printing date 31.10.2023 Version number 42 Revision: 31.10.2023

Trade name ESTRICHVERDÜBELUNG EV 15 KOMP. B

(Contd. of page 5)

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions Reacts with acids, alkalis and oxidizing agents
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Poisonous gases/vapours

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:				
100-51-	6 Benz	zyl alcohol		
Oral	LD50	1,230 mg/kg (rat)		
Dermal	LD50	2,000 mg/kg (rabbit)		

- · Skin corrosion/irritation Causes severe skin burns and eye damage.
- · Serious eye damage/irritation Causes serious eye damage.
- · Reproductive toxicity Suspected of damaging fertility or the unborn child.
- · 11.2 Information on other hazards
- * Endocrine disrupting properties

 84852-15-3 | 4-nonylphenol, branched | List I

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Also poisonous for fish and plankton in water bodies.

Water danger class (Germany) 3 (Self-assessment): extremely hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into soil.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must be specially treated under adherence to official regulations.

(Contd. on page 7)

Printing date 31.10.2023 Version number 42 Revision: 31.10.2023

Trade name ESTRICHVERDÜBELUNG EV 15 KOMP. B

(Contd. of page 6)

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

· 14.1 UN number or ID number	
· ADR, IMDG, IATA	UN1760
· 14.2 UN proper shipping name · ADR	1760 CORROSIVE LIQUID, N.O.S. (Bisphenol A EpichlorhydrinIsophorondiamin Copolymer, mphenylenebis(methylamine)), ENVIRONMENTALLY HAZARDOUS
· IMDG	CORROSIVE LIQUID, N.O.S. (Bisphenol A Epichlorhydrinlsophorondiamin Copolymer, mphenylenebis(methylamine)), MARINI POLLUTANT
·IATA	CORROSIVE LIQUID, N.O.S. (Bisphenol A EpichlorhydrinIsophorondiamin Copolymer, m phenylenebis(methylamine))
· 14.3 Transport hazard class(es)	
· ADR, IMDG	
· Class · Label	8 Corrosive substances. 8
·IATA	
Class	8 Corrosive substances.
· Label	8
· 14.4 Packing group · ADR, IMDG, IATA	II
· 14.5 Environmental hazards:	Product contains environmentally hazardou substances: 4-nonylphenol, branched
· Marine pollutant:	Yes Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)
· 14.6 Special precautions for user · Kemler Number:	Warning: Corrosive substances. 80
EMS Number:	F-A,S-B
· Stowage Category · Stowage Code	B SW2 Clear of living quarters.
· 14.7 Maritime transport in bulk accordir	

Printing date 31.10.2023 Version number 42 Revision: 31.10.2023

Trade name ESTRICHVERDÜBELUNG EV 15 KOMP. B

	(Contd. of page 7
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Transport category · Tunnel restriction code	1L 2 E
· UN "Model Regulation":	UN 1760 CORROSIVE LIQUID, N.O.S. (B I S P H E N O L A - EPICHLORHYDRINISOPHORONDIAMIN C O P O L Y M E R , M - PHENYLENEBIS(METHYLAMINE)), 8, II, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

- · Regulated poisons
- None of the ingredients is listed.
- · Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category E1 Hazardous to the Aquatic Environment
- Qualifying quantity (tonnes) for the application of lower-tier requirements 100 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- · National regulations
- Substances of very high concern (SVHC) according to UK REACH

84852-15-3 4-nonylphenol, branched

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H302 Harmful if swallowed.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

(Contd. on page 9)

Printing date 31.10.2023 Version number 42 Revision: 31.10.2023

Trade name ESTRICHVERDÜBELUNG EV 15 KOMP. B

(Contd. of page 8)

H412 Harmful to aquatic life with long lasting effects.

- · Contact: chemikalieninfo@murexin.com (+43 02622/27401)
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1B: Skin corrosion/irritation - Category 1B

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation - Category 1

Repr. 2: Reproductive toxicity - Category 2

Repr. 2: Reproductive toxicity - Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* * Data compared to the previous version altered.

GB