

Safety data sheet according to UK REACH

Printing date 17.10.2025

Version number 8 (replaces version 7)

Revision: 17.10.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name Epoxy Topcoat EP 100 TC Komp. A**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Coating
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
MUREXIN GmbH
Franz v. Furtenbachstr. 1
A-2700 Wiener Neustadt
Tel.: +43 (0)2622/27401
- **Informing department:** chemikalieninfo@murexin.com
- **1.4 Emergency telephone number:**
UK National poisons Emergency number.: +44 (0) 870 600 6266

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS08 health hazard

Repr. 1A H360F May damage fertility.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.
 Eye Irrit. 2 H319 Causes serious eye irritation.
 Skin Sens. 1 H317 May cause an allergic skin reaction.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS07 GHS08 GHS09

- **Signal word** Danger
- **Hazard-determining components of labelling:**
Bisphenol A epoxy resin
1,6-bis(2,3-epoxypropoxy)hexane
Bisphenol F diglycidyl ether, mixture of isomers
4-morpholinecarbaldehyde
- **Hazard statements**
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.

(Contd. on page 2)

Safety data sheet according to UK REACH

Printing date 17.10.2025

Version number 8 (replaces version 7)

Revision: 17.10.2025

Trade name Epoxy Topcoat EP 100 TC Komp. A

(Contd. of page 1)

H360F May damage fertility.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

Contains epoxy constituents. May produce an allergic reaction.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.








vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture consisting of the following components with harmless additives.

Dangerous components:

| | | |
|---|--|------------|
| CAS: 1675-54-3 EINECS: 216-823-5 | Bisphenol A epoxy resin  Aquatic Chronic 2, H411  Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 EUH205 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5% Skin Irrit. 2; H315: C ≥ 5% | 50-100% |
| Reg.nr.: 01-2119454392-40-0003 | Bisphenol F diglycidyl ether, mixture of isomers Consisting of: 9003-36-5 Bisphenol-F-epichlorohydrin resin  Aquatic Chronic 2, H411  Skin Irrit. 2, H315; Skin Sens. 1A, H317 | ≥10-<25% |
| CAS: 933999-84-9 Reg.nr.: 01-2119463471-41 | 1,6-bis(2,3-epoxypropoxy)hexane  Repr. 1A, H360F  Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 Aquatic Chronic 3, H412 | ≥10-<25% |
| CAS: 4394-85-8 EINECS: 224-518-3 | 4-morpholinecarbaldehyde  Skin Sens. 1B, H317 | ≥0.1-<0.5% |

SECTION 4: First aid measures

4.1 Description of first aid measures

General information Instantly remove any clothing soiled by the product.

After inhalation

Supply fresh air and call for doctor for safety reasons.

In case of unconsciousness bring patient into stable side position for transport.

(Contd. on page 3)

Safety data sheet according to UK REACH

Printing date 17.10.2025

Version number 8 (replaces version 7)

Revision: 17.10.2025

Trade name Epoxy Topcoat EP 100 TC Komp. A

(Contd. of page 2)

- **After skin contact**
Instantly wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
- **After eye contact**
Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.
- **After swallowing** In case of persistent symptoms consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents**
CO₂, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.
- **5.2 Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective clothing.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or water bodies.
Inform respective authorities in case product reaches water or sewage system.
Dilute with much water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Keep containers tightly sealed.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** Store only in the original container.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class 6.1 C**
- **7.3 Specific end use(s)** No further relevant information available.

GB

(Contd. on page 4)

Safety data sheet according to UK REACH

Printing date 17.10.2025

Version number 8 (replaces version 7)

Revision: 17.10.2025

Trade name Epoxy Topcoat EP 100 TC Komp. A

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Components with critical values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists that were valid during the compilation were used as basis.
- **8.2 Exposure controls**
- **Appropriate engineering controls** No further data; see section 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures**
The usual precautionary measures should be adhered to in handling the chemicals.
Keep away from foodstuffs, beverages and food.
Instantly remove any soiled and impregnated garments.
Wash hands during breaks and at the end of the work.
Avoid contact with the eyes and skin.
- **Breathing equipment:**
Filter A/P2.
In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.
- **Hand protection**
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
Protective gloves.
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
- **Material of gloves**
Butyl rubber, BR
Nitrile rubber, NBR
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye/face protection** Safety glasses recommended during refilling.
- **Body protection:** Protective work clothing.

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Physical state** Liquid
- **Colour:** Yellowish
- **Smell:** Characteristic
- **Odour threshold:** Not determined.
- **Melting point/freezing point:** Not determined
- **Boiling point or initial boiling point and boiling range** 191.5 °C (623-84-7 propane-1,2-diyl diacetate)
- **Flammability** Not applicable.
- **Lower and upper explosion limit**
- **Lower:** Not determined.
- **Upper:** Not determined.
- **Flash point:** 87 °C (623-84-7 propane-1,2-diyl diacetate)
- **Auto-ignition temperature:** 471 °C (623-84-7 propane-1,2-diyl diacetate)
- **Decomposition temperature:** Not determined.

(Contd. on page 5)

Safety data sheet according to UK REACH

Printing date 17.10.2025

Version number 8 (replaces version 7)

Revision: 17.10.2025

Trade name Epoxy Topcoat EP 100 TC Komp. A

(Contd. of page 4)

| | |
|---|--|
| · pH at 20 °C | 6-8 |
| · Viscosity: | |
| · Kinematic viscosity | Not determined. |
| · dynamic at 20 °C: | 500-850 mPas |
| · Solubility | |
| · Water: | Not determined. |
| · Partition coefficient n-octanol/water (log value) | Not determined. |
| · Steam pressure at 20 °C: | 0.8 hPa (Bisphenol F diglycidyl ether, mixture of isomers) |
| · Density and/or relative density | |
| · Density at 20 °C | 1.1 g/cm ³ |
| · Relative density | Not determined. |
| · Vapour density | Not determined. |

· 9.2 Other information

· Appearance:

· Form:

Fluid

· Important information on protection of health and environment, and on safety.

· Self-inflammability:

Product is not selfigniting.

· Explosive properties:

Product is not explosive.

· Solvent content:

· Solids content:

0.4 %

· Change in condition

· Evaporation rate

Not determined.

· Information with regard to physical hazard classes

· Explosives

Void

· Flammable gases

Void

· Aerosols

Void

· Oxidising gases

Void

· Gases under pressure

Void

· Flammable liquids

Void

· Flammable solids

Void

· Self-reactive substances and mixtures

Void

· Pyrophoric liquids

Void

· Pyrophoric solids

Void

· Self-heating substances and mixtures

Void

· Substances and mixtures, which emit flammable gases in contact with water

Void

· Oxidising liquids

Void

· Oxidising solids

Void

· Organic peroxides

Void

· Corrosive to metals

Void

· Desensitised explosives

Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

· Conditions to be avoided: To avoid thermal decomposition do not overheat.

· 10.3 Possibility of hazardous reactions Reacts with amines

· 10.4 Conditions to avoid No further relevant information available.

· 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 6)

Safety data sheet according to UK REACH

Printing date 17.10.2025

Version number 8 (replaces version 7)

Revision: 17.10.2025

Trade name Epoxy Topcoat EP 100 TC Komp. A

(Contd. of page 5)

· 10.6 Hazardous decomposition products: None

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:

1675-54-3 Bisphenol A epoxy resin

Oral LD50 >2,000 mg/kg (rat)

Dermal LD50 >2,000 mg/kg (rat)

4394-85-8 4-morpholinecarbaldehyde

Dermal LD50 >18,300 mg/kg (rabbit)

· Primary irritant effect:

· Skin corrosion/irritation Causes skin irritation.

· Serious eye damage/irritation Causes serious eye irritation.

· Reproductive toxicity May damage fertility.

· Additional toxicological information:

· CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction) -

· 11.2 Information on other hazards

· Endocrine disrupting properties

7447-41-8 lithium chloride

List III

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity: No further relevant information available.

· 12.2 Persistence and degradability No further relevant information available.

· 12.3 Bioaccumulative potential No further relevant information available.

· 12.4 Mobility in soil No further relevant information available.

· 12.5 Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

· 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

· 12.7 Other adverse effects

· Remark: Toxic for fish

· Additional ecological information:

· General notes:

Toxic for aquatic organisms

Also poisonous for fish and plankton in water bodies.

Water hazard class (Germany) 2 (Self-assessment): hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)

Safety data sheet according to UK REACH

Printing date 17.10.2025

Version number 8 (replaces version 7)



Revision: 17.10.2025

Trade name Epoxy Topcoat EP 100 TC Komp. A

(Contd. of page 6)

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleaning agent:** Water, if necessary with cleaning agent.

SECTION 14: Transport information

| | | |
|---|--|---|
| <ul style="list-style-type: none"> · 14.1 UN number or ID number · ADR, IMDG, IATA | UN3082 | |
| <ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR · IMDG · IATA | 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A epoxy resin, Bisphenol F diglycidyl ether, mixture of isomers) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A epoxy resin, Bisphenol F diglycidyl ether, mixture of isomers), MARINE POLLUTANT ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A epoxy resin, Bisphenol F diglycidyl ether, mixture of isomers) | |
| <ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · ADR, IMDG, IATA | <div style="display: flex; align-items: center; gap: 10px;">   </div> <ul style="list-style-type: none"> · Class · Label | 9 Miscellaneous dangerous substances and articles. 9 |
| <ul style="list-style-type: none"> · 14.4 Packing group · ADR, IMDG, IATA | III | |
| <ul style="list-style-type: none"> · 14.5 Environmental hazards: · Marine pollutant: · Special marking (ADR): · Special marking (IATA): | Product contains environmentally hazardous substances: Bisphenol A epoxy resin No Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree) | |
| <ul style="list-style-type: none"> · 14.6 Special precautions for user · Kemler Number: · EMS Number: · Stowage Category | Warning: Miscellaneous dangerous substances and articles. 90 F-A,S-F A | |
| <ul style="list-style-type: none"> · 14.7 Maritime transport in bulk according to IMO instruments | Not applicable. | |
| <ul style="list-style-type: none"> · Transport/Additional information: · ADR · Limited quantities (LQ) · Transport category · Tunnel restriction code | ----- 5L 3 (-) | |
| <ul style="list-style-type: none"> · UN "Model Regulation": | UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL A | |

(Contd. on page 8)

Safety data sheet according to UK REACH

Printing date 17.10.2025

Version number 8 (replaces version 7)

Revision: 17.10.2025

Trade name Epoxy Topcoat EP 100 TC Komp. A

(Contd. of page 7)

EPOXY RESIN, BISPHENOL F DIGLYCIDYL
ETHER, MIXTURE OF ISOMERS), 9, III

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- **Poisons Act**

- **Regulated explosives precursors**

| | | |
|-----------|-----------------|-----|
| 7664-38-2 | phosphoric acid | 30% |
|-----------|-----------------|-----|

- **Regulated poisons**

None of the ingredients is listed.

- **Reportable explosives precursors**

None of the ingredients is listed.

- **Reportable poisons**

None of the ingredients is listed.

- **Directive 2012/18/EU**

- **Named dangerous substances - ANNEX I** None of the ingredients is listed.

- **Seveso category E2** Hazardous to the Aquatic Environment

- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t

- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

- **National regulations**

- **Additional classification according to Decree on Hazardous Materials, Annex II:**

Carcinogenic hazardous material group III (dangerous)

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H360F May damage fertility.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

EUH205 Contains epoxy constituents. May produce an allergic reaction.

- **Contact:** chemikalieninfo@murexin.com (+43 02622/27401)

- **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

(Contd. on page 9)

**Safety data sheet
according to UK REACH**

Printing date 17.10.2025

Version number 8 (replaces version 7)

Revision: 17.10.2025

Trade name Epoxy Topcoat EP 100 TC Komp. A

(Contd. of page 8)

*Skin Sens. 1: Skin sensitisation – Category 1**Skin Sens. 1A: Skin sensitisation – Category 1A**Skin Sens. 1B: Skin sensitisation – Category 1B**Repr. 1A: Reproductive toxicity – Category 1A**Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2**Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3***· * Data compared to the previous version altered.**

GB