

Safety data sheet according to UK REACH

Printing date 23.04.2026

Version number 7

Revision: 23.04.2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name** *EPOXY-VERSIEGELUNG ASV 106 ABLEITFÄHIG KOMP. B*
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Epoxy resin
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
MUREXIN GmbH
Franz v. Furtenbachstr. 1
A-2700 Wiener Neustadt
Tel.: +43 (0)2622/27401
- **Informing department:** chemikalieninfo@murexin.com
- **1.4 Emergency telephone number:**
UK National poisons Emergency number.: +44 (0) 870 600 6266

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS08 health hazard

Muta. 2 H341 Suspected of causing genetic defects.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.
 Eye Irrit. 2 H319 Causes serious eye irritation.
 Skin Sens. 1 H317 May cause an allergic skin reaction.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS07 GHS08 GHS09

- **Signal word** Warning
- **Hazard-determining components of labelling:**
Bisphenol A epoxy resin
2,3-epoxypropyl o-tolyl ether
- **Hazard statements**
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H341 Suspected of causing genetic defects.
H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 2)

Safety data sheet according to UK REACH

Printing date 23.04.2026

Version number 7

Revision: 23.04.2026

Trade name **EPOXY-VERSIEGELUNG ASV 106 ABLEITFÄHIG KOMP. B**

(Contd. of page 1)

Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P103 Read carefully and follow all instructions.
 P261 Avoid breathing mist/vapours/spray.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

Contains epoxy constituents. May produce an allergic reaction.

2.3 Other hazards

Results of PBT and vPvB assessment






- **PBT:** Not applicable
- **vPvB:** Not applicable

SECTION 3: Composition/information on ingredients

3.2 Mixtures

· **Description:** Mixture consisting of the following components with harmless additives.

Dangerous components:

CAS: 1675-54-3 EINECS: 216-823-5	Bisphenol A epoxy resin  Aquatic Chronic 2, H411  Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 EUH205 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 %	50-100%
CAS: 2210-79-9 EINECS: 218-645-3	2,3-epoxypropyl o-tolyl ether  Muta. 2, H341  Aquatic Chronic 2, H411  Skin Irrit. 2, H315; Skin Sens. 1A, H317	≥10-<25%

SECTION 4: First aid measures

4.1 Description of first aid measures

After inhalation

Take affected persons into the open air and position comfortably
 Supply fresh air and call for doctor for safety reasons.
 In case of unconsciousness bring patient into stable side position for transport.

After skin contact

Instantly wash with water and soap and rinse thoroughly.
 Call a doctor immediately.

After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

After swallowing

Seek medical treatment.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

GB

(Contd. on page 3)

Safety data sheet according to UK REACH

Printing date 23.04.2026

Version number 7

Revision: 23.04.2026

Trade name **EPOXY-VERSIEGELUNG ASV 106 ABLEITFÄHIG KOMP. B**

(Contd. of page 2)

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** Use fire fighting measures that suit the environment.
- **5.2 Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
- **5.3 Advice for firefighters**
- **Protective equipment:**
Wear self-contained breathing apparatus.
Do not inhale explosion gases or combustion gases.
- **Additional information**
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective clothing.
- **6.2 Environmental precautions:**
Do not allow to enter the ground/soil.
Do not allow product to reach sewage system or water bodies.
Inform respective authorities in case product reaches water or sewage system.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Keep containers tightly sealed.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:**
Provide floor trough without outlet.
Store only in the original container.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:**
Protect from frost.
Keep container tightly sealed.
- **Storage class 10**
- **7.3 Specific end use(s)** No further relevant information available.

GB

(Contd. on page 4)

Safety data sheet according to UK REACH

Printing date 23.04.2026

Version number 7

Revision: 23.04.2026

Trade name **EPOXY-VERSIEGELUNG ASV 106 ABLEITFÄHIG KOMP. B**

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Components with critical values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists that were valid during the compilation were used as basis.
- **8.2 Exposure controls**
- **Appropriate engineering controls** No further data; see section 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures**
The usual precautionary measures should be adhered to in handling the chemicals.
Keep away from foodstuffs, beverages and food.
Instantly remove any soiled and impregnated garments.
Wash hands during breaks and at the end of the work.
Avoid contact with the eyes and skin.
- **Breathing equipment:**
Filter AX.
In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.
- **Hand protection** Protective gloves.
- **Material of gloves**
Butyl rubber, BR
Nitrile rubber, NBR
Fluorocarbon rubber (Viton)
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Not suitable are gloves made of the following materials:**
Strong gloves
Leather gloves
- **Eye/face protection** Tightly sealed safety glasses.
- **Body protection:** Protective work clothing.

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Physical state** Liquid
- **Colour:** Yellow-brown
- **Smell:** Aromatic
- **Odour threshold:** Not determined
- **Melting point/freezing point:** Not determined
- **Boiling point or initial boiling point and boiling range** >200 °C
- **Flammability** Not applicable
- **Lower and upper explosion limit**
- **Lower:** Not determined
- **Upper:** Not determined
- **Flash point:** 138 °C
- **Decomposition temperature:** Not determined
- **pH** Mixture is non-soluble (in water).

(Contd. on page 5)

Safety data sheet according to UK REACH

Printing date 23.04.2026

Version number 7

Revision: 23.04.2026

Trade name EPOXY-VERSIEGELUNG ASV 106 ABLEITFÄHIG KOMP. B

(Contd. of page 4)

· Viscosity:	
· Kinematic viscosity	Not determined
· dynamic at 20 °C:	500-650 mPas
· Solubility	
· Water:	Not miscible or difficult to mix
· Partition coefficient n-octanol/water (log value)	Not determined
· Steam pressure at 20 °C:	0 hPa (2210-79-9 2,3-epoxypropyl o-tolyl ether)
· Density and/or relative density	
· Density at 20 °C	1.2 g/cm ³
· Relative density	Not determined
· Vapour density	Not determined

· 9.2 Other information

· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Self-inflammability:	Product is not selfigniting.
· Explosive properties:	Product is not explosive.
· Change in condition	
· Evaporation rate	Not determined

· Information with regard to physical hazard classes

· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Reacts with alkali, amines and strong acids
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Poisonous gases/vapours

GB

(Contd. on page 6)

Safety data sheet according to UK REACH

Printing date 23.04.2026

Version number 7

Revision: 23.04.2026

Trade name **EPOXY-VERSIEGELUNG ASV 106 ABLEITFÄHIG KOMP. B**

(Contd. of page 5)

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values that are relevant for classification:**

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)

- **1675-54-3 Bisphenol A epoxy resin**

Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Germ cell mutagenicity** Suspected of causing genetic defects.
- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

EC 50	3.3 mg/l (G) (48h)
-------	--------------------

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable
- **vPvB:** Not applicable
- **12.6 Endocrine disrupting properties**
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms
Water hazard class (Germany) 2 (Self-assessment): hazardous for water.
Do not allow product to reach ground water, water bodies or sewage system.
Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**

- **Recommendation**

Can be deposited with household garbage after solidification following consultation with the operator of the waste disposal facility and the pertinent authorities and under adherence to the necessary technical regulations.

Must be specially treated under adherence to official regulations.

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)

Safety data sheet according to UK REACH

Printing date 23.04.2026

Version number 7

Revision: 23.04.2026

Trade name EPOXY-VERSIEGELUNG ASV 106 ABLEITFÄHIG KOMP. B

(Contd. of page 6)

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

· **14.1 UN number or ID number**

· **ADR, IMDG, IATA** UN3082

· **14.2 UN proper shipping name**

· **ADR** 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A epoxy resin, 2,3-epoxypropyl o-tolyl ether)

· **IMDG** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A epoxy resin, 2,3-epoxypropyl o-tolyl ether), MARINE POLLUTANT

· **IATA** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A epoxy resin, 2,3-epoxypropyl o-tolyl ether)

· **14.3 Transport hazard class(es)**

· **ADR, IMDG, IATA**



· **Class** 9 Miscellaneous dangerous substances and articles.

· **Label** 9

· **14.4 Packing group**

· **ADR, IMDG, IATA** III

· **14.5 Environmental hazards:**

Product contains environmentally hazardous substances: Bisphenol A epoxy resin

· **Marine pollutant:**

Yes
Symbol (fish and tree)

· **Special marking (ADR):**

Symbol (fish and tree)

· **Special marking (IATA):**

Symbol (fish and tree)

· **14.6 Special precautions for user**

Warning: Miscellaneous dangerous substances and articles.

· **Kemler Number:**

90

· **EMS Number:**

F-A, S-F

· **Stowage Category**

A

· **14.7 Maritime transport in bulk according to IMO instruments**

Not applicable

· **Transport/Additional information:**

· **ADR**

· **Limited quantities (LQ)** 5L

· **Transport category** 3

· **Tunnel restriction code** (-)

(Contd. on page 8)

Safety data sheet according to UK REACH

Printing date 23.04.2026

Version number 7

Revision: 23.04.2026

Trade name **EPOXY-VERSIEGELUNG ASV 106 ABLEITFÄHIG KOMP. B**

(Contd. of page 7)

- | | |
|---|---|
| <ul style="list-style-type: none"> · UN "Model Regulation": | <p>UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL A EPOXY RESIN, 2,3-EPOXYPROPYL O-TOLYL ETHER), 9, III</p> |
|---|---|

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Poisons Act**

<ul style="list-style-type: none"> · Regulated explosives precursors 	None of the ingredients is listed.
<ul style="list-style-type: none"> · Regulated poisons 	None of the ingredients is listed.
<ul style="list-style-type: none"> · Reportable explosives precursors 	None of the ingredients is listed.
<ul style="list-style-type: none"> · Reportable poisons 	None of the ingredients is listed.

- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category E2** Hazardous to the Aquatic Environment
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
 - H315 Causes skin irritation.
 - H317 May cause an allergic skin reaction.
 - H319 Causes serious eye irritation.
 - H341 Suspected of causing genetic defects.
 - H411 Toxic to aquatic life with long lasting effects.
 - EUH205 Contains epoxy constituents. May produce an allergic reaction.
- **Contact:** chemikalieninfo@murexin.com (+43 02622/27401)
- **Abbreviations and acronyms:**
 - RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 - ICAO: International Civil Aviation Organisation
 - ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 - IMDG: International Maritime Code for Dangerous Goods
 - IATA: International Air Transport Association
 - GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - PBT: Persistent, Bioaccumulative and Toxic
 - vPvB: very Persistent and very Bioaccumulative
 - Skin Irrit. 2: Skin corrosion/irritation – Category 2
 - Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

(Contd. on page 9)

**Safety data sheet
according to UK REACH**

Printing date 23.04.2026

Version number 7

Revision: 23.04.2026

Trade name EPOXY-VERSIEGELUNG ASV 106 ABLEITFÄHIG KOMP. B

(Contd. of page 8)

*Skin Sens. 1: Skin sensitisation – Category 1**Skin Sens. 1A: Skin sensitisation – Category 1A**Muta. 2: Germ cell mutagenicity – Category 2**Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2***· * Data compared to the previous version altered.**

GB