Revision: 28.08.2023

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.08.2023

Version number 5 (replaces version 4)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier
- · Trade name FASERKLEBSTOFF EL 630
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Adhesives
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

MUREXIN GmbH

Franz v. Furtenbachstr. 1 A-2700 Wiener Neustadt Tel.: +43 (0)2622/27401

- · Informing department: chemikalieninfo@murexin.com
- · 1.4 Emergency telephone number:

UK National poisons Emergency number.: +44 (0) 870 600 6266

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

The product is not classified, according to the GB CLP regulation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008 Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Additional information:

Contains poly[oxy(methyl-1,2-ethanediyl)], α-(methylphenyl)-ω-hydroxy-, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1), 1,2-benzisothiazol-3(2H)-one, Natriumdicyanamid. May produce an allergic reaction. Safety data sheet available on request.

- 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture consisting of the following components with harmless additives.

Dangerous components:	Dangerous components:	
CAS: 7440-44-0 EINECS: 231-153-3 Reg.nr.: 01-2119966900-32- XXXX	carbon substance with a Community workplace exposure limit	1-2.5%
CAS: 9064-13-5	poly[oxy(methyl-1,2-ethanediyl)], α- (methylphenyl)-ω-hydroxy- ♦ Skin Sens. 1, H317	≥0.5-<1%

(Contd. on page 2)

Printing date 28.08.2023 Version number 5 (replaces version 4) Revision: 28.08.2023

Trade name FASERKLEBSTOFF EL 630

		(Contd. of page 1)
CAS: 1934-75-4 EINECS: 217-703-5	Natriumdicyanamid Eye Dam. 1, H318 Acute Tox. 4, H302; Skin Sens. 1, H317	≥0.1-<0.5%
CAS: 2634-33-5 EINECS: 220-120-9	1,2-benzisothiazol-3(2H)-one Eye Dam. 1, H318 Aquatic Acute 1, H400 Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317 Specific concentration limit: Skin Sens. 1;H317: C ≥ 0.05 %	<0.05%
CAS: 55965-84-9 EC number: 611-341-5	reaction mass of: 5-chloro-2-methyl-4- isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220- 239-6] (3:1) Acute Tox. 3, H301; Acute Tox. 1, H310; Acute Tox. 2, H330 Skin Corr. 1B, H314; Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100) Skin Sens. 1A, H317 EUH071 Specific concentration limits: Skin Corr. 1C;H314: C ≥ 0.6 % Skin Irrit. 2; H315: 0.06 % ≤ C < 0.6 % Eye Dam. 1; H318: C ≥ 0.6 % Eye Irrit. 2; H319: 0.06 % ≤ C < 0.6 % Skin Sens. 1A; H317: C ≥ 0.0015 %	

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- After skin contact

If skin irritation continues, consult a doctor.

Instantly wash with water and soap and rinse thoroughly.

- · After eye contact Rinse opened eye for several minutes under running water.
- After swallowing In case of persistent symptoms consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents

Use fire fighting measures that suit the environment.

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

- For safety reasons unsuitable extinguishing agents Water with a full water jet.
- · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

GB

Printing date 28.08.2023 Version number 5 (replaces version 4)

Trade name FASERKLEBSTOFF EL 630

(Contd. of page 2)

Revision: 28.08.2023

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective clothing.
- · 6.2 Environmental precautions: Do not allow product to reach sewage system or water bodies.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Allow to solidify. Collect mechanically.

Dispose of the material collected according to regulations.

· 6.4 Reference to other sections

No dangerous materials are released.

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling No special precautions necessary if used correctly.
- Information about protection against explosions and fires: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage
- · Requirements to be met by storerooms and containers: Store only in the original container.
- Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Protect from frost.

Keep container tightly sealed.

- · Storage class 10
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Components with critical values that require monitoring at the workplace:

7440-44-0 carbon

WEL Long-term value: 10* 4** mg/m³
*inhalable dust **respirable

- · Additional information: The lists that were valid during the compilation were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data: see section 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures

The usual precautionary measures should be adhered to in handling the chemicals.

Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

- · Breathing equipment: Not necessary if room is well-ventilated.
- · Hand protection Protective gloves.
- · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 4)

Printing date 28.08.2023 Version number 5 (replaces version 4) Revision: 28.08.2023

Trade name FASERKLEBSTOFF EL 630

(Contd. of page 3)

- · Eye/face protection Safety glasses recommended during refilling.
- · Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical state
Colour:
Smell:
Fluid
Light grey
Mild

Odour threshold:
 Melting point/freezing point:
 Not determined
 Not determined

Boiling point or initial boiling point and

boiling range 100 °C (7732-18-5 water, distilled, conductivity or

of similar purity)

• Flammability Product is not inflammable.

Lower and upper explosion limit

Lower: Not determined.
Upper: Not determined.
Flash point: >150 °C

• Decomposition temperature: Not determined. • pH Not determined.

· Viscosity:

Kinematic viscositydynamic:Not determined.Not determined.

Solubility

· Water: not miscible

· Partition coefficient n-octanol/water (log

value) Not determined.

• Steam pressure at 20 °C: 23 hPa (7732-18-5 water, distilled, conductivity or

of similar purity)

· Density and/or relative density

Density at 20 °C
 Relative density
 Vapour density
 Particle characteristics
 1.1 g/cm³
 Not determined.
 See section 3.

· 9.2 Other information

· Appearance:

· Form: Pasty

· Important information on protection of health

and environment, and on safety.

Self-inflammability: Product is not selfigniting.
 Explosive properties: Product is not explosive.

Solvent content:

• Water: 39.0 %
 • Solids content: 26.4 %

· Change in condition

· Evaporation rate Not determined.

· Information with regard to physical hazard

classes

Explosives

Flammable gases

Aerosols

Oxidising gases

Gases under pressure

Void

Void

(Contd. on page 5)

Printing date 28.08.2023 Version number 5 (replaces version 4) Revision: 28.08.2023

Trade name FASERKLEBSTOFF EL 630

		(Contd. of page 4)
· Flammable liquids	Void	
Flammable solids	Void	
· Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit		
flammable gases in contact with water	Void	
· Oxidising liquids	Void	
Oxidising solids	Void	
· Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- · Conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: None

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values that are relevant for classification:

9064-13-5 poly[oxy(methyl-1,2-ethanediyl)], α-(methylphenyl)-ω-hydroxy-

Oral LD50 >5,000 mg/kg (rat)

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) -
- 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

9064-13-5 poly[oxy(methyl-1,2-ethanediyl)], α-(methylphenyl)-ω-hydroxy-

EC 50/48h >100 mg/l (G)

(Contd. on page 6)

Revision: 28.08.2023

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.08.2023 Version number 5 (replaces version 4)

Trade name FASERKLEBSTOFF EL 630

	(Contd. of page 5)
EC 50	>100 mg/l (Desmodesmus subspicatus)
LC50	>10-100 mg/l (Daphnie)
2634-33-5	1,2-benzisothiazol-3(2H)-one
EC 50/48h	3.27 mg/l (Daphnie)

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class (Germany) 1 (Self-assessment): slightly hazardous for water. Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

44.4.11N1		
14.1 UN number or ID number ADR, ADN, IMDG, IATA	Void	
14.2 UN proper shipping name ADR, ADN, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA Class	Void	
14.4 Packing group ADR, IMDG, IATA	Void	
14.5 Environmental hazards: Marine pollutant:	No	
14.6 Special precautions for user	Not applicable.	
14.7 Maritime transport in bulk accordi	ng to Not applicable.	
UN "Model Regulation":	Void	

Printing date 28.08.2023 Version number 5 (replaces version 4) Revision: 28.08.2023

Trade name FASERKLEBSTOFF EL 630

(Contd. of page 6)

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H301 Toxic if swallowed. H302 Harmful if swallowed.

H310 Fatal in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H330 Fatal if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

EUH071 Corrosive to the respiratory tract.

· Contact: chemikalieninfo@murexin.com (+43 02622/27401)

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 3: Acute toxicity - Category 3

Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 1: Acute toxicity - Category 1

Acute Tox. 2: Acute toxicity - Category 2

Skin Corr. 1B: Skin corrosion/irritation – Category 1B Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation - Category 1A

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

· * Data compared to the previous version altered.