Printing date 22.11.2024 Version number 6 Revision: 13.11.2024

1 SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name FASSADENFARBE AUSTROSIL SX 40
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Dispersion paint/ Latex paint
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

MUREXIN GmbH

Franz v. Furtenbachstr. 1 A-2700 Wiener Neustadt Tel.: +43 (0)2622/27401

- · Informing department: chemikalieninfo@murexin.com
- · 1.4 Emergency telephone number:

UK National poisons Emergency number.: +44 (0) 870 600 6266

2 SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Skin Sens. 1

H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms



GHS07

- · Signal word Warning
- · Hazard-determining components of labelling:

2-octyl-2H-isothiazol-3-one

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

1,2-benzisothiazol-3(2H)-one [EC no. 220-120-9]

· Hazard statements

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves.

P362+P364 Take off contaminated clothing and wash it before reuse. P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

(Contd. on page 2)

Printing date 22.11.2024 Version number 6 Revision: 13.11.2024

Trade name FASSADENFARBE AUSTROSIL SX 40

(Contd. of page 1)

· Additional information:

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

3 SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description**: Mixture consisting of the following components with harmless additives.

CAS: 1317-65-3 EINECS: 215-279-6	Calciumcarbonat	25-50%
	substance with a Community workplace exposure limit	
CAS: 57-55-6 EINECS: 200-338-0 Reg.nr.: 01-2119456809-23- xxxx	Propylene glycol substance with a Community workplace exposure limit	1-2.5%
CAS: 2634-33-5 EINECS: 220-120-9	1,2-benzisothiazol-3(2H)-one [EC no. 220- 120-9] Eye Dam. 1, H318 Aquatic Acute 1, H400 Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317 Specific concentration limit: Skin Sens. 1;H317: C ≥ 0.05 %	<0.1%
CAS: 52-51-7 EINECS: 200-143-0	bronopol (INN) Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=10) Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Irrit. 2, H315; STOT SE 3, H335	<0.025%

Printing date 22.11.2024 Version number 6 Revision: 13.11.2024

Trade name FASSADENFARBE AUSTROSIL SX 40

		(Contd. of page 2)
CAS: 26530-20-1 EINECS: 247-761-7	2-octyl-2H-isothiazol-3-one Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330 Skin Corr. 1, H314; Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100) Skin Sens. 1A, H317 EUH071 ATE: LD50 oral: 125 mg/kg LD50 dermal: 311 mg/kg LC50/4 h inhalative: 0.27 mg/l Specific concentration limit: Skin Sens. 1A;H317: C ≥ 0.0015 %	≥0.0025-<0.025%
CAS: 55965-84-9 EC number: 611-341-5	reaction mass of: 5-chloro-2-methyl-4- isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220- 239-6] (3:1) Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox. 2, H330 Skin Corr. 1C, H314 Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100) Skin Sens. 1A, H317 EUH071 Specific concentration limits: Skin Corr. 1C;H314: C ≥ 0.6 % Skin Irrit. 2; H315: 0.06 % ≤ C < 0.6 % Eye Dam. 1; H318: C ≥ 0.6 % Skin Sens. 1A; H317: C ≥ 0.0015 %	≥0.00025-<0.0025%

4 SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation

Supply fresh air and call for doctor for safety reasons.

In case of unconsciousness bring patient into stable side position for transport.

· After skin contact

Instantly wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

- · After swallowing In case of persistent symptoms consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents Use fire fighting measures that suit the environment.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 4)

Printing date 22.11.2024 Version number 6 Revision: 13.11.2024

Trade name FASSADENFARBE AUSTROSIL SX 40

(Contd. of page 3)

- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- · Additional information

Cool endangered containers with water spray jet.

Collect contaminated fire fighting water separately. It must not enter drains.

6 SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective clothing.

6.2 Environmental precautions:

Do not allow product to reach sewage system or water bodies.

Inform respective authorities in case product reaches water or sewage system.

Dilute with much water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

No dangerous materials are released.

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

7 SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- Requirements to be met by storerooms and containers: Store only in the original container.
- Information about storage in one common storage facility:

Store away from oxidising agents.

Store away from foodstuffs.

Further information about storage conditions:

Protect from frost.

Keep container tightly sealed.

- · Storage class 12
- · 7.3 Specific end use(s) No further relevant information available.

8 SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with critical values that require monitoring at the workplace:

1317-65-3 Calciumcarbonat

WEL Long-term value: 10* 4** mg/m³
*inhalable dust; **respirable

57-55-6 Propylene glycol

WEL Long-term value: 474* 10** mg/m³, 150* ppm *total vapour and particulates **particulates

· Additional information: The lists that were valid during the compilation were used as basis.

(Contd. on page 5)

Printing date 22.11.2024 Version number 6 Revision: 13.11.2024

Trade name FASSADENFARBE AUSTROSIL SX 40

(Contd. of page 4)

- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures

The usual precautionary measures should be adhered to in handling the chemicals.

Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Breathing equipment:

In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.

Hand protection

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Use gloves of stable material (e.g. Nitrile) - if necessary tricoted to improve the wearability.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye/face protection Safety glasses recommended during refilling.
- · Body protection: Protective work clothing.

9 SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical state Fluid

· Colour: According to product specification

Smell: Characteristic

· **Odour threshold:** Not determined.

· Melting point/freezing point: 0 °C

· Boiling point or initial boiling point and

boiling range 100 °C (7732-18-5 water, distilled, conductivity or

of similar purity)

· Flammability Not applicable.

· Lower and upper explosion limit

Lower: Not determined.
Upper: Not determined.
Flash point: Not applicable
Decomposition temperature: Not determined.

· pH at 20 °C

· Viscosity:

Kinematic viscosity
dynamic at 20 °C:

Not determined.
17,000 mPas

·Solubility

Water: Partly miscible

· Partition coefficient n-octanol/water (log

value) Not determined.

Steam pressure at 20 °C: 23 hPa (7732-18-5 water, distilled, conductivity or

of similar purity)

· Density and/or relative density

Density at 20 °C ~1.9-~2 g/cm³

(Contd. on page 6)

Printing date 22.11.2024 Version number 6 Revision: 13.11.2024

Trade name FASSADENFARBE AUSTROSIL SX 40

(Contd. of page 5)

Relative densityVapour densityNot determined.Not determined.

· 9.2 Other information

· Appearance:

Form: Fluid

· Important information on protection of health

and environment, and on safety.

Self-inflammability: Product is not selfigniting.
 Explosive properties: Product is not explosive.

· Solvent content:

 Water:
 32.6 %

 Solids content:
 49.2-49.3 %

· Change in condition

Evaporation rate Not determined.

Information with regard to physical hazard

classes

Void **Explosives** Flammable gases Void **Aerosols** Void Oxidising gases Void Gases under pressure Void Flammable liquids Void Flammable solids Void Self-reactive substances and mixtures Void Pyrophoric liquids Void Pyrophoric solids Void Self-heating substances and mixtures Void Substances and mixtures, which emit flammable gases in contact with water Void Oxidising liquids Void Oxidising solids Void Organic peroxides Void Corrosive to metals Void Desensitised explosives Void

10 SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- · Conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

11 SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 7)

Printing date 22.11.2024 Version number 6 Revision: 13.11.2024

Trade name FASSADENFARBE AUSTROSIL SX 40

			(Contd. of page 6)
· LD/LC50 v	values tha	t are relevant for classification:	
1317-65-3	Calciumo	earbonat	
Oral	LD50	>5,000 mg/kg (rat)	
57-55-6 Pi	ropylene g	glycol	
Oral	LD50	22,000 mg/kg (rat)	
Dermal	LD50	>2,000 mg/kg (rabbit)	
52-51-7 bi	52-51-7 bronopol (INN)		
Oral	LD50	305 mg/kg (rat)	
26530-20-1 2-octyl-2H-isothiazol-3-one			
Oral	LD50	125 mg/kg (ATE)	
Dermal	LD50	311 mg/kg (ATE)	
Inhalative	LC50/4 h	0.27 mg/l (ATE)	

- · Additional toxicological information:
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) -
- · 11.2 Information on other hazards

· Endocrine disrupting properties		
330-54-1	diuron	List II
128-37-0	Butylated hydroxytoluene	List II

12 SECTION 12: Ecological information

· 12.1 Toxicity

	•		
· Aquatic to	· Aquatic toxicity:		
1317-65-3	1317-65-3 Calciumcarbonat		
EC 50/48h	>1,000 mg/l (G)		
EC 50	289 mg/l (Desmodesmus subspicatus)		
LC50	>10,000 mg/l (Oncorhynchus mykiss (Regenbogenforelle))		
57-55-6 Pro	57-55-6 Propylene glycol		
LC50/96h	40,613 mg/l (Oncorhynchus mykiss (Regenbogenforelle))		
LC50	40,613 mg/l (Oncorhynchus mykiss (Regenbogenforelle))		
2634-33-5	2634-33-5 1,2-benzisothiazol-3(2H)-one [EC no. 220-120-9]		
EC 50/48h	3.27 mg/l (Daphnie)		

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Harmful to aquatic organisms

Water hazard class (Germany) 2 (Self-assessment): hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

Printing date 22.11.2024 Version number 6 Revision: 13.11.2024

Trade name FASSADENFARBE AUSTROSIL SX 40

(Contd. of page 7)

13 SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation:

Disposal must be made according to official regulations.

Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

· Recommended cleaning agent: Water, if necessary with cleaning agent.

14.1 UN number or ID number ADR, ADN, IMDG, IATA	Void	
14.2 UN proper shipping name ADR, ADN, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA Class	Void	
14.4 Packing group ADR, IMDG, IATA	Void	
14.5 Environmental hazards: Marine pollutant:	No	
14.6 Special precautions for user	Not applicable.	
14.7 Maritime transport in bulk according IMO instruments	ng to Not applicable.	
UN "Model Regulation":	Void	

15 SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act

7 0.001.0 7 101			
· Regulated explosives precursors			
None of the ingredients is listed.			
· Regulated poisons			
None of the ingredients is listed.			
· Reportable explosives precursors			
None of the ingredients is listed.			
· Reportable poisons			
7664-41-7 ammonia, anhydrous	Listed		
1310-73-2 sodium hydroxide	12% of total caustic alkalinity		

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.

(Contd. on page 9)

Printing date 22.11.2024 Version number 6 Revision: 13.11.2024

Trade name FASSADENFARBE AUSTROSIL SX 40

(Contd. of page 8)

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H301 Toxic if swallowed.
H302 Harmful if swallowed.
H310 Fatal in contact with skin.
H311 Toxic in contact with skin.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H335 May cause respiratory irritation.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

EUH071 Corrosive to the respiratory tract.

· Contact: chemikalieninfo@murexin.com (+43 02622/27401)

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Acute Tox. 3: Acute toxicity - Category 3

Acute Tox. 4: Acute toxicity - Category 4

Acute Tox. 2: Acute toxicity - Category 2

Skin Corr. 1: Skin corrosion/irritation – Category 1

Skin Corr. 1C: Skin corrosion/irritation - Category 1C

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Skin Sens. 1A: Skin sensitisation - Category 1A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

* Data compared to the previous version altered.