Printing date 13.05.2024 Version number 8 (replaces version 7) Revision: 13.05.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier
- · Trade name GIESSHARZ 2K SI 60 Komp. B
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Reaction resin
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

MUREXIN GmbH

Franz v. Furtenbachstr. 1 A-2700 Wiener Neustadt Tel.: +43 (0)2622/27401

- · Informing department: chemikalieninfo@murexin.com
- · 1.4 Emergency telephone number:

UK National poisons Emergency number.: +44 (0) 870 600 6266

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carc. 2 H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation

Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms





GHS07 GHS08

- · Signal word Danger
- Hazard-determining components of labelling: diphenylmethanediisocyanate,isomeres and homologues
- · Hazard statements

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

(Contd. on page 2)

Printing date 13.05.2024 Version number 8 (replaces version 7) Revision: 13.05.2024

Trade name GIESSHARZ 2K SI 60 Komp. B

(Contd. of page 1)

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.
P260 Do not breathe mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P284 [In case of inadequate ventilation] wear respiratory protection. P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

Contains isocyanates. May produce an allergic reaction.

As from 24 August 2023 adequate training is required before industrial or professional use.

- 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture consisting of the following components with harmless additives.

Dangerous components:

9016-87-9 diphenylmethanediisocyanate,isomeres and homologues

50-100%

Consisting of: 101-68-8 diphenylmethane-4,4'-di-isocyanante (37.5%); 5873-54-1 diphenylmethane-2,4'-diisocyanate (3%); 2536-05-2 diphenylmethane-2,2'-diisocyanate (0.5%)

🕸 Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373

Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335

EUH204

Specific concentration limits: Eye Irrit. 2; H319: $C \ge 5 \%$

Skin Irrit. 2; H315: $C \ge 5$ % Resp. Sens. 1; H334: $C \ge 0.1$ %

STOT SE 3; C ≥ 5 %

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation

Supply fresh air and call for doctor for safety reasons.

In case of unconsciousness bring patient into stable side position for transport.

· After skin contact

If skin irritation continues, consult a doctor,

Instantly wash with water and soap and rinse thoroughly.

After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

· After swallowing In case of persistent symptoms consult doctor.

(Contd. on page 3)

Printing date 13.05.2024 Version number 8 (replaces version 7) Revision: 13.05.2024

Trade name GIESSHARZ 2K SI 60 Komp. B

(Contd. of page 2)

• **4.2 Most important symptoms and effects, both acute and delayed**No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents

Use fire fighting measures that suit the environment.

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

5.2 Special hazards arising from the substance or mixture

Can be released in case of fire

Nitrogen oxides (NOx)

Hydrogen cyanide (HCN)

Carbon monoxide (CO)

Formation of poisonous gases during heating or in fires.

- 5.3 Advice for firefighters
- · Protective equipment:

Wear full protective suit.

Put on breathing apparatus.

Additional information

Collect contaminated fire fighting water separately. It must not enter drains.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Put on breathing apparatus.

Wear protective clothing.

6.2 Environmental precautions:

Do not allow to enter drainage system, surface or ground water.

Do not allow product to reach sewage system or water bodies.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Use only in well ventilated areas.

Keep containers tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: Keep breathing equipment ready.
- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage
- Requirements to be met by storerooms and containers: Store only in the original container.

(Contd. on page 4)

Printing date 13.05.2024 Version number 8 (replaces version 7) Revision: 13.05.2024

Trade name GIESSHARZ 2K SI 60 Komp. B

(Contd. of page 3)

· Information about storage in one common storage facility:

Store away from water.

Store away from foodstuffs.

- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class 10
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Components with critical values that require monitoring at the workplace:

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

WEL Short-term value: 0.07 mg/m3

Long-term value: 0.02 mg/m³

Sen; as -NCO

- · Additional information: The lists that were valid during the compilation were used as basis.
- 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures

The usual precautionary measures should be adhered to in handling the chemicals.

Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Store protective clothing separately.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Breathing equipment:

Breathing protection recommended.

Filter P3.

In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.

Hand protection

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

Butyl rubber, BR

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eve/face protection Safety glasses recommended during refilling.
- · **Body protection:** Protective work clothing.

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Physical state

Fluid

Colour:

Various colours

Smell:

Weak, characteristic

(Contd. on page 5)

Printing date 13.05.2024 Version number 8 (replaces version 7) Revision: 13.05.2024

Trade name GIESSHARZ 2K SI 60 Komp. B

(Contd. of page 4) Not determined. · Odour threshold: · Melting point/freezing point: Not determined · Boiling point or initial boiling point and >200 °C boiling range Flammability Not applicable. Lower and upper explosion limit · Lower: Not determined. · Upper: Not determined. >100 °C · Flash point: 530 °C · Auto-ignition temperature: · Decomposition temperature: Not determined. Mixture is non-soluble (in water). · pH Not determined. · Viscosity: · Kinematic viscosity Not determined. · dynamic at 20 °C: 160 mPas · Solubility · Water: Not miscible or difficult to mix · Partition coefficient n-octanol/water (log value) Not determined. (9016-87-9 · Steam pressure at 20 °C: h P a diphenylmethanediisocyanate,isomeres and homologues) · Vapour pressure at 50 °C: >0 hPa Density and/or relative density · Density at 20 °C 1.1 g/cm³ Relative density Not determined. · Vapour density Not determined. · 9.2 Other information · Appearance: · Form: Fluid · Important information on protection of health and environment, and on safety. · Self-inflammability: Product is not selfigniting. · Explosive properties: Product is not explosive. · Solvent content: · Solids content: 0.0 % · Change in condition · Evaporation rate Not determined. · Information with regard to physical hazard classes · Explosives Void Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void Flammable liquids Void Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void Void · Pyrophoric solids · Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void Oxidising solids Void

Printing date 13.05.2024 Version number 8 (replaces version 7) Revision: 13.05.2024

Trade name GIESSHARZ 2K SI 60 Komp. B

(Contd. of page 5)

· Organic peroxides	Void
Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: None

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Harmful if inhaled.
- LD/LC50 values that are relevant for classification:

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

 Oral
 LD50
 >100,000 mg/kg (rat)

 Dermal
 LD50
 >9,400 mg/kg (rabbit)

 Inhalative
 LC50/4 h
 0.49 mg/l (rat)

- Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye irritation.
- · Carcinogenicity Suspected of causing cancer.
- · STOT-single exposure May cause respiratory irritation.
- · STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.
- 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

EC 50 >100 mg/l (F2) (OECD 209 Activated Sludge, Respiration Inhibition)

- >1,000 mg/l (G) (OECD 202 Acute Immobilisation Tet)
- 12.2 Persistence and degradability No further relevant information available. 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

(Contd. on page 7)

Printing date 13.05.2024 Version number 8 (replaces version 7) Revision: 13.05.2024

Trade name GIESSHARZ 2K SI 60 Komp. B

(Contd. of page 6)

- · 12.7 Other adverse effects
- · Additional ecological information:
- General notes:

Water danger class (Germany) 3 (Self-assessment): extremely hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into soil.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must be specially treated under adherence to official regulations.

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleaning agent: Water, if necessary with cleaning agent.

SECTION 14: Transport information	
· 14.1 UN number or ID number · ADR, ADN, IMDG, IATA	Void
· 14.2 UN proper shipping name · ADR, ADN, IMDG, IATA	Void
· 14.3 Transport hazard class(es)	
· ADR, ADN, IMDG, IATA · Class	Void
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user	Not applicable.
· 14.7 Maritime transport in bulk accordin IMO instruments	ng to Not applicable.
· Transport/Additional information:	Not dangerous according to the above specifications.
· UN "Model Regulation":	Void

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

Regulated poisons

None of the ingredients is listed.

(Contd. on page 8)

Printing date 13.05.2024 Version number 8 (replaces version 7) Revision: 13.05.2024

Trade name GIESSHARZ 2K SI 60 Komp. B

(Contd. of page 7)

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer.
- H373 May cause damage to organs through prolonged or repeated exposure.

EUH204 Contains isocyanates. May produce an allergic reaction.

- · Contact: chemikalieninfo@murexin.com (+43 02622/27401)
- Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Resp. Sens. 1: Respiratory sensitisation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Carc. 2: Carcinogenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

* Data compared to the previous version altered.