Printing date 22.07.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

[•] 1.1 Product identifier

• Trade name HOLZKITTLÖSUNG LV 15

• **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.

· Application of the substance / the mixture Knife filler/ Surfacer

· 1.3 Details of the supplier of the safety data sheet

• *Manufacturer/Supplier:* MUREXIN GmbH Franz v. Furtenbachstr. 1 A-2700 Wiener Neustadt Tel.: +43 (0)2622/27401

· Informing department: chemikalieninfo@murexin.com

1.4 Emergency telephone number:

UK National poisons Emergency number.: +44 (0) 870 600 6266

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture
 Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Eye Irrit. 2 H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness.

· 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms



· Signal word Danger

· Hazard-determining components of labelling:

acetone

ethyl acetate n-butyl acetate

propan-2-ol

Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

- [•] Precautionary statements
- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P103 Read carefully and follow all instructions.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

(Contd. on page 2)

Printing date 22.07.2024

Version number 5 (replaces version 4)

Revision: 22.07.2024

Trade name HOLZKITTLÖSUNG LV 15

| | (Contd. of page 1) |
|-----------------------|--|
| P243 | Take action to prevent static discharges. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. |
| P303+P361+ | P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. |
| P305+P351+ | P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P501 | Dispose of contents/container in accordance with local/regional/national/ international regulations. |
| · Additional ir | nformation: |
| EUH066 Rep | eated exposure may cause skin dryness or cracking. |
| 2.3 Other ha | |
| Results of P | BT and vPvB assessment |
| · PBT: Not app | |
| • vPvB: Not ap | |

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture consisting of the following components.

| Dangerous components: | | |
|---|--|--------|
| CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49- 0008 | acetone | 25-50% |
| CAS: 141-78-6 EINECS: 205-500-4 Reg.nr.: 2119475103-46 01-2119475103-46- xxxx | ethyl acetate Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 EUH066 | 10-25% |
| CAS: 123-86-4 EINECS: 204-658-1 | n-butyl acetate Flam. Liq. 3, H226 STOT SE 3, H336 EUH066 | 5-10% |
| CAS: 67-63-0 EINECS: 200-661-7 | propan-2-ol Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 | 2.5-5% |

SECTION 4: First aid measures

· 4.1 Description of first aid measures

• After inhalation Supply fresh air; consult doctor in case of symptoms.

· After skin contact

Instantly wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor. • After swallowing

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; instantly call for medical help.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 3)

GB

Printing date 22.07.2024

Version number 5 (replaces version 4)

Revision: 22.07.2024

Trade name HOLZKITTLÖSUNG LV 15

(Contd. of page 2)

• **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

Suitable extinguishing agents

Alcohol-resistant foam

Carbon dioxide

Water haze

• For safety reasons unsuitable extinguishing agents Water with a full water jet.

5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- [•] 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Keep away from ignition sources Ensure adequate ventilation Wear protective equipment. Keep unprotected persons away. Wear protective clothing.
6.2 Environmental precautions: Do not allow product to reach sewage system or water bodies. Prevent material from reaching sewage system, holes and cellars. Inform respective authorities in case product reaches water or sewage system.
6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

6.4 Reference to other sections See Section 7 for information on safe handling See Section 8 for information on personal protection equipment. See Section 13 for information on disposal.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Keep containers tightly sealed.
 Ensure good ventilation/exhaustion at the workplace.
 Prevent formation of aerosols.
 Information about protection against explosions and fires: Fumes can combine with air to form an explosive mixture. Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.

· 7.2 Conditions for safe storage, including any incompatibilities

- · Storage
- **Requirements to be met by storerooms and containers:** Store in cool location.
- Store only in the original container.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.

Store in cool, dry conditions in well sealed containers.

(Contd. on page 4)

⁻ GB

Version number 5 (replaces version 4)

Revision: 22.07.2024

(Contd. of page 3)

Trade name HOLZKITTLÖSUNG LV 15

• Storage class 3

Printing date 22.07.2024

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Components with critical values that require monitoring at the workplace:

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm

141-78-6 ethyl acetate

WEL Short-term value: 1468 mg/m³, 400 ppm Long-term value: 734 mg/m³, 200 ppm

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

67-63-0 propan-2-ol

WEL Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm

· Additional information: The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

· Appropriate engineering controls No further data; see section 7.

- Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures
- The usual precautionary measures should be adhered to in handling the chemicals.

Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

• Breathing equipment:

In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.

· Hand protection Protective gloves.

· Material of gloves Butyl rubber, BR

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection Safety glasses

· Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

| 9.1 Information on basic physical and General Information | t chemical properties |
|--|------------------------------------|
| · Physical state | Fluid |
| · Colour: | According to product specification |
| · Smell: | Solvent-like |
| · Melting point/freezing point: | Not determined |
| Boiling point or initial boiling point a | nd |
| boiling range | 56 °C |
| · Lower and upper explosion limit | |
| · Lower: | 2 Vol % |
| | (Contd. on page 5) |

a. on page 5

Printing date 22.07.2024

Version number 5 (replaces version 4)

Revision: 22.07.2024

Trade name HOLZKITTLÖSUNG LV 15

| | (Contd. of page 4 |
|--|---|
| Upper: | 13 Vol % |
| Flash point: | <-20 °C |
| Auto-ignition temperature: | 370 °C |
| Decomposition temperature: | Not determined. |
| pH at 20 °C | 6-8 |
| Viscosity: | |
| Kinematic viscosity at 20 °C | 50 s (DIN 53211/4) |
| dynamic: | Not determined. |
| Solubility | |
| Water: | Partly soluble |
| Partition coefficient n-octanol/water (log | |
| value) | Not determined. |
| Steam pressure at 20 °C: | 247 hPa |
| Density and/or relative density | |
| Density at 20 °C | 0.9 g/cm³ |
| Relative density | Not determined. |
| Vapour density | Not determined. |
| 9.2 Other information | |
| Appearance: | |
| Form: | Fluid |
| | |
| Important information on protection of hea | 11(11 |
| and environment, and on safety. | 270 °C |
| Self-inflammability: | 370 °C |
| Explosive properties: | Product is not explosive. However, formation of explosive air/steam mixtures is possible. |
| Change in condition | - , , |
| Evaporation rate | Not determined. |
| Information with regard to physical haza | ard |
| classes | |
| Explosives | Void |
| Flammable gases | Void |
| Aerosols | Void |
| Oxidising gases | Void |
| Gases under pressure | Void |
| Flammable liquids | Highly flammable liquid and vapour. |
| Flammable solids | Void |
| Self-reactive substances and mixtures | Void |
| Pyrophoric liquids | Void |
| Pyrophoric solids | Void |
| Self-heating substances and mixtures | Void |
| Substances and mixtures, which emit | |
| flammable gases in contact with water | Void |
| Oxidising liquids | Void |
| Oxidising solids | Void |
| | Void |
| Organic peroxides Corrosive to metals | Void |
| Desensitised explosives | Void Void |
| | N/ 1/ 1 |

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

10.2 Chemical stability

· Conditions to be avoided: No decomposition if used according to specifications.

• 10.3 Possibility of hazardous reactions No dangerous reactions known

• **10.4 Conditions to avoid** No further relevant information available.

(Contd. on page 6)

⁻ GB

Version number 5 (replaces version 4)

Revision: 22.07.2024

Trade name HOLZKITTLÖSUNG LV 15

Printing date 22.07.2024

(Contd. of page 5)

• **10.5 Incompatible materials:** No further relevant information available.

· 10.6 Hazardous decomposition products: None

SECTION 11: Toxicological information

• **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008** • **Acute toxicity** Based on available data, the classification criteria are not met.

| · LD/LC50 | · LD/LC50 values that are relevant for classification: | | | | | |
|------------|--|---|--|--|--|--|
| 67-64-1 a | cetone | | | | | |
| Oral | LD50 | 5,800 mg/kg (rat) | | | | |
| Dermal | LD50 | 20,000 mg/kg (rabbit) | | | | |
| 141-78-6 | ethyl aceta | ate | | | | |
| Oral | LD50 | 5,600 mg/kg (rat) | | | | |
| Dermal | LD50 | 18,000 mg/kg (rabbit) | | | | |
| 123-86-4 | n-butyl ac | etate | | | | |
| Oral | LD50 | 14,000 mg/kg (rat) | | | | |
| Inhalative | LC50/4 h | >21 mg/l (rat) | | | | |
| 67-63-0 p | ropan-2-o | | | | | |
| Oral | LD50 | 4,570 mg/kg (rat) | | | | |
| Dermal | LD50 | 13,400 mg/kg (rab) | | | | |
| Inhalative | LC50/4 h | 30 mg/l (rat) | | | | |
| | | ation Based on available data, the classification criteria are not met. | | | | |
| | | e/irritation | | | | |
| | erious eye I mutagen | icity Based on available data, the classification criteria are not met. | | | | |
| | | sed on available data, the classification criteria are not met. | | | | |
| | | ity Based on available data, the classification criteria are not met. | | | | |
| · STOT-sin | | | | | | |
| | | ss or dizziness. | | | | |
| | | osure Based on available data, the classification criteria are not met. | | | | |
| | | Based on available data, the classification criteria are not met. | | | | |
| | | other hazards | | | | |
| | <u> </u> | ng properties | | | | |
| None of th | e ingredie | nts is listed. | | | | |
| | | | | | | |

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

141-78-6 ethyl acetate

EC 50 3,300 mg/l (Acartia Tonsa)

717 mg/l (G)

LC50 230 mg/l (F2)

• **12.2 Persistence and degradability** No further relevant information available.

- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

12.5 Results of PBT and vPvB assessment

· PBT: Not applicable.

• vPvB: Not applicable.

(Contd. on page 7)

GB

Version number 5 (replaces version 4)

Revision: 22.07.2024

Trade name HOLZKITTLÖSUNG LV 15

(Contd. of page 6)

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

· Additional ecological information:

General notes:

Printing date 22.07.2024

Water hazard class (Germany) 1 (Self-assessment): slightly hazardous for water.

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

• **Recommendation:** Disposal must be made according to official regulations.

| <i>14.1 UN number or ID number ADR, IMDG, IATA</i> | UN1263 |
|---|-----------------------------------|
| 14.2 UN proper shipping name ADR IMDG, IATA | 1263 PAINT PAINT |
| 14.3 Transport hazard class(es) | |
| ADR, IMDG, IATA | |
| | |
| Class | 3 Flammable liquids. |
| Label | 3 |
| 14.4 Packing group ADR, IMDG, IATA | 11 |
| 14.5 Environmental hazards: Marine pollutant: | No |
| 14.6 Special precautions for user Kemler Number: | Warning: Flammable liquids. 33 |
| EMS Number: | F-E, <u>S-E</u> |
| Stowage Category | В |
| 14.7 Maritime transport in bulk accordi | ing to |
| IMO instruments | Not applicable. |
| Transport/Additional information: | |
| ADR | |
| Limited quantities (LQ) | 5L |
| Transport category | 2 |
| Tunnel restriction code | D/E |

Version number 5 (replaces version 4)

Revision: 22.07.2024

(Contd. of page 7)

Listed

Trade name HOLZKITTLÖSUNG LV 15

· UN "Model Regulation":

UN 1263 PAINT, 3, II

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Poisons Act

Printing date 22.07.2024

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

Reportable explosives precursors

67-64-1 acetone

Reportable poisons

None of the ingredients is listed.

Directive 2012/18/EU

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS

· Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH210 Safety data sheet available on request.

Contact: chemikalieninfo@murexin.com (+43 02622/27401)

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids – Category 3 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3