Printing date 11.08.2023 Version number 8 Revision: 11.08.2023

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name KLEBSTOFF 2K PU 330 KOMP. B
- · CAS Number:

9016-87-9

- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Isocyanate resin
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MUREXIN GmbH

Franz v. Furtenbachstr. 1 A-2700 Wiener Neustadt Tel.: +43 (0)2622/27401

- · Informing department: chemikalieninfo@murexin.com
- 1.4 Emergency telephone number:

UK National poisons Emergency number.: +44 (0) 870 600 6266

### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carc. 2 H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause respiratory irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The substance is classified and labelled according to the GB CLP regulation.

· Hazard pictograms





GHS07 GHS08

- Signal word Danger
- · Hazard statements

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

(Contd. on page 2)

Printing date 11.08.2023 Version number 8 Revision: 11.08.2023

### Trade name KLEBSTOFF 2K PU 330 KOMP. B

(Contd. of page 1)

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P284 [In case of inadequate ventilation] wear respiratory protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Additional information:

Contains isocyanates. May produce an allergic reaction.

As from 24 August 2023 adequate training is required before industrial or professional use.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

# SECTION 3: Composition/information on ingredients

- · 3.1 Substances
- · CAS No. Designation:

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation

Supply fresh air and call for doctor for safety reasons.

In case of unconsciousness bring patient into stable side position for transport.

· After skin contact

Seek medical treatment.

Instantly wash with water and soap and rinse thoroughly.

· After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

- · After swallowing In case of persistent symptoms consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

# SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents

Use fire fighting measures that suit the environment.

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

5.2 Special hazards arising from the substance or mixture

No further relevant information available.

(Contd. on page 3)

Printing date 11.08.2023 Version number 8 Revision: 11.08.2023

### Trade name KLEBSTOFF 2K PU 330 KOMP. B

(Contd. of page 2)

- 5.3 Advice for firefighters
- · Protective equipment: Put on breathing apparatus.

### SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective clothing.

Use breathing protection against the effects of fumes/dust/aerosol.

- 6.2 Environmental precautions: Do not allow product to reach sewage system or water bodies.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

# SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep containers tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

- Information about protection against explosions and fires: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage
- · Requirements to be met by storerooms and containers: Store only in the original container.
- Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class 10
- · 7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Components with critical values that require monitoring at the workplace:

### 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

WEL Short-term value: 0.07 mg/m³

Long-term value: 0.02 mg/m3

Sen; as -NCO

- · Additional information: The lists that were valid during the compilation were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures

The usual precautionary measures should be adhered to in handling the chemicals.

Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

- · Breathing equipment: Filter P3.
- Hand protection Protective gloves.

(Contd. on page 4)

Printing date 11.08.2023 Version number 8 Revision: 11.08.2023

### Trade name KLEBSTOFF 2K PU 330 KOMP. B

(Contd. of page 3)

Material of gloves Nitrile rubber, NBR

Butyl rubber, BR

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

>300 °C

· Eye/face protection

Safety glasses

Face protection

· Body protection: Protective work clothing.

SECTION 9: Ph	ysical and	l chemical	properties
---------------	------------	------------	------------

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid · Colour: Brown · Smell: Characteristic -24 °C

· Melting point/freezing point:

Boiling point or initial boiling point and

boiling range

Lower and upper explosion limit

· Lower: Not determined. Not determined. · Upper: >250 °C · Flash point: >400 °C Auto-ignition temperature:

Decomposition temperature: Not determined. · pH Not determined.

Viscosity:

300 mPas · dynamic at 20 °C:

Solubility

Unsoluble Water:

· Partition coefficient n-octanol/water (log

Not determined. value) Steam pressure: Not determined.

· Density and/or relative density

1.2 g/cm3 Density at 20 °C

· 9.2 Other information No further relevant information available.

· Appearance:

Fluid · Form:

· Important information on protection of health and environment, and on safety.

· Self-inflammability: Not determined.

Product is not explosive. Explosive properties:

· Change in condition

Not determined. · Evaporation rate

· Information with regard to physical hazard

classes Void · Explosives · Flammable gases Void Aerosols Void · Oxidising gases Void · Gases under pressure Void

· Flammable liquids Void · Flammable solids Void

(Contd. on page 5)

Printing date 11.08.2023 Version number 8 Revision: 11.08.2023

### Trade name KLEBSTOFF 2K PU 330 KOMP. B

		(Contd. of page 4
· Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
· Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit		
flammable gases in contact with water	Void	
· Oxidising liquids	Void	
· Oxidising solids	Void	
· Organic peroxides	Void	
· Corrosive to metals	Void	
Desensitised explosives	Void	

# SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: None

## **SECTION 11: Toxicological information**

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Harmful if inhaled.

· LD/LC50	· LD/LC50 values that are relevant for classification:   Oral LD50 >100,000 mg/kg (rat)			
Oral	LD50	>100,000 mg/kg (rat)		
Dermal	LD50	>9,400 mg/kg (rabbit)		
Inhalative	LC50/4 h	0.49 mg/l (rat)		

- Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye irritation.
- · Carcinogenicity Suspected of causing cancer.
- · STOT-single exposure May cause respiratory irritation.
- · STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties Substance is not listed.

# SECTION 12: Ecological information

· 12.1 Toxicity

## · Aquatic toxicity:

EC 50 >100 mg/l (F2) (OECD 209 Activated Sludge, Respiration Inhibition)

>1,000 mg/l (G) (OECD 202 Acute Immobilisation Tet)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

(Contd. on page 6)

Printing date 11.08.2023 Version number 8 Revision: 11.08.2023

### Trade name KLEBSTOFF 2K PU 330 KOMP. B

(Contd. of page 5)

- · 12.7 Other adverse effects
- Additional ecological information:
- · General notes:

Water hazard class (Germany) 1 (Assessment by list): slightly hazardous for water. Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

## SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Hand over to disposers of hazardous waste.

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information	n	
· 14.1 UN number or ID number · ADR, IMDG, IATA	Void	
· 14.2 UN proper shipping name · ADR, IMDG, IATA	Void	
· 14.3 Transport hazard class(es)		
· ADR, ADN, IMDG, IATA · Class	Void	
· 14.4 Packing group · ADR, IMDG, IATA	Void	
· 14.5 Environmental hazards: · Marine pollutant:	No	
· 14.6 Special precautions for user	Not applicable.	
· 14.7 Maritime transport in bulk accordi IMO instruments	ing to Not applicable.	
· UN "Model Regulation":	Void	

# **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I Substance is not listed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Contact: chemikalieninfo@murexin.com (+43 02622/27401)

(Contd. on page 7)

Printing date 11.08.2023 Version number 8 Revision: 11.08.2023

### Trade name KLEBSTOFF 2K PU 330 KOMP. B

(Contd. of page 6)

#### · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Resp. Sens. 1: Respiratory sensitisation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Carc. 2: Carcinogenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

\* Data compared to the previous version altered.

GB