Printing date 22.07.2024 Version number 6 Revision: 22.07.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name MALERLACK KHX 90 GLÄNZEND WEISS
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Lacquer
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

MUREXIN GmbH

Franz v. Furtenbachstr. 1 A-2700 Wiener Neustadt Tel.: +43 (0)2622/27401

- · Informing department: chemikalieninfo@murexin.com
- · 1.4 Emergency telephone number:

UK National poisons Emergency number.: +44 (0) 870 600 6266

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms



- · Signal word Warning
- · Hazard statements

H226 Flammable liquid and vapour.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P261 Avoid breathing mist/vapours/spray.
P280 Wear protective gloves / eye protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water or shower.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Contains phthalic anhydride, cobalt(II) 2-ethylhexanoate. May produce an allergic reaction.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

(Contd. on page 2)

Printing date 22.07.2024 Version number 6 Revision: 22.07.2024

Trade name MALERLACK KHX 90 GLÄNZEND WEISS

(Contd. of page 1)

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- Description: Mixture consisting of the following components with harmless additives.

· Dangerous components:		
CAS: 64742-48-9 EINECS: 265-150-3	Hydrotreated heavy Naphtha Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336 EUH066	10-25%
CAS: 64742-48-9 EC number: 918-481-9 Reg.nr.: 01-2119457273-39- xxxx	NAPHTA (petroleum), hydrotreated heavy & Asp. Tox. 1, H304 EUH066	2.5-5%
CAS: 85-44-9 EINECS: 201-607-5	phthalic anhydride Resp. Sens. 1, H334 Eye Dam. 1, H318 Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	≥0.1-<0.5%

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information Instantly remove any clothing soiled by the product.
- · After inhalation

Take affected persons into the open air and position comfortably

In case of unconsciousness bring patient into stable side position for transport.

- · After skin contact Instantly wash with water and soap and rinse thoroughly.
- · After eye contact Rinse opened eye for several minutes under running water. Then consult doctor.
- After swallowing

Do not induce vomiting; instantly call for medical help.

Rinse out mouth and then drink plenty of water.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam. Use fire fighting measures that suit the environment.

- · For safety reasons unsuitable extinguishing agents Water with a full water jet.
- · 5.2 Special hazards arising from the substance or mixture

A fire produces thick black smoke.

Inhalation of hazardous decomposition products may cause serious damage to health.

Vapors are heavier than air and spread on the ground. Inflammation possible over a great distance

(Contd. on page 3)

Printing date 22.07.2024 Version number 6 Revision: 22.07.2024

Trade name MALERLACK KHX 90 GLÄNZEND WEISS

(Contd. of page 2)

- 5.3 Advice for firefighters
- · Protective equipment: Put on breathing apparatus.
- Additional information

Cool endangered containers with water spray jet.

Collect contaminated fire fighting water separately. It must not enter drains.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or water bodies.

Prevent material from reaching sewage system, holes and cellars.

Inform respective authorities in case product reaches water or sewage system.

· 6.3 Methods and material for containment and cleaning up:

Contain with non-combustible absorbent material (e.g. sand, earth, vermiculite, diatomaceous earth).

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep containers tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Store in cool, dry place in tightly closed containers.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Do not spray on flames or red-hot objects.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- Requirements to be met by storerooms and containers:

Store only in the original container.

Store in cool location.

· Information about storage in one common storage facility:

Do not store together with oxidising and acidic materials as well as heavy-metal compounds.

- Further information about storage conditions: Keep container tightly sealed.
- · Storage class 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Components with critical values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

• Additional information: The lists that were valid during the compilation were used as basis.

(Contd. on page 4)

Printing date 22.07.2024 Version number 6 Revision: 22.07.2024

Trade name MALERLACK KHX 90 GLÄNZEND WEISS

(Contd. of page 3)

- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures

The usual precautionary measures should be adhered to in handling the chemicals.

Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

Do not eat, drink or smoke while working.

Do not inhale gases / fumes / aerosols.

Breathing equipment:

Use breathing protection in case of insufficient ventilation.

Filter A/P2.

- · Hand protection Protective gloves.
- · Material of gloves

Use gloves of stable material (e.g. Nitrile) - if necessary tricoted to improve the wearability. Nitrile rubber, NBR

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye/face protection Tightly sealed safety glasses.
- **Body protection:**

Antistatic protective workwear made of natural fibres (cotton) or heat-resistant synthetic fibres.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state

· Colour: According to product specification

· Smell: Characteristic

Melting point/freezing point: Not determined

· Boiling point or initial boiling point and

boiling range 180 °C

Lower and upper explosion limit

0.6 Vol % · Lower: · Upper: 7 Vol % 36 °C Flash point: 240 °C Auto-ignition temperature:

Decomposition temperature: Not determined.

pH at 20 °C 6-8

· Viscosity:

· Kinematic viscosity at 40 °C 1,192.37 mm²/s · dynamic at 20 °C: 1,500 mPas

Solubility · Water:

Not miscible or difficult to mix

· Partition coefficient n-octanol/water (log

Not determined. value)

· Steam pressure at 20 °C: 0.1 hPa

· Density and/or relative density

Density at 20 °C 1.3 g/cm³ · Relative density Not determined. Vapour density Not determined.

(Contd. on page 5)

Printing date 22.07.2024 Version number 6 Revision: 22.07.2024

Trade name MALERLACK KHX 90 GLÄNZEND WEISS

(Contd. of page 4)

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health

and environment, and on safety.

· Self-inflammability: Product is not selfigniting.

· Explosive properties: Product is not explosive. However, formation of

explosive air/steam mixtures is possible.

· Solvent content:

· Water: 0% · Solids content: 77.0 %

· Change in condition

· Evaporation rate Not determined.

· Information with regard to physical hazard

classes · Explosives Void · Flammable gases Void **Aerosols** Void Oxidising gases Void · Gases under pressure Void

Flammable liquids Flammable liquid and vapour.

Flammable solids Void Self-reactive substances and mixtures Void · Pyrophoric liquids Void Pyrophoric solids Void Self-heating substances and mixtures Void

· Substances and mixtures, which emit

flammable gases in contact with water Void · Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void · Corrosive to metals Void · Desensitised explosives Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions

Reacts with acids, alkalis and oxidizing agents

At high temperatures, hazardous decomposition products such as carbon dioxide, carbon monoxide, smoke and nitrogen oxides may be produced: Carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: None

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 6)

Printing date 22.07.2024 Version number 6 Revision: 22.07.2024

Trade name MALERLACK KHX 90 GLÄNZEND WEISS

(Contd. of page 5)

			•	•	•	,
· LD/LC50 values that are relevant for classification:						
64742-4	18-9 NA	APHTA (petroleum), hydrotreated heavy				
Oral	LD50	>2,000 mg/kg (rat)				
Dermal	LD50	>2.000 mg/kg (rabbit)				

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) -
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

64742-48-9 NAPHTA (petroleum), hydrotreated heavy

IC 50 >100 mg/l (Acartia Tonsa)

LC50 >100 mg/l (Oncorhynchus mykiss (Regenbogenforelle))

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Harmful to aquatic organisms

Water hazard class (Germany) 1 (Self-assessment): slightly hazardous for water.

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Must be specially treated under adherence to official regulations.

- · Uncleaned packagings:
- Recommendation:

Disposal must be made according to official regulations.

(Contd. on page 7)

Printing date 22.07.2024 Version number 6 Revision: 22.07.2024

Trade name MALERLACK KHX 90 GLÄNZEND WEISS

(Contd. of page 6)

Non contaminated packagings can be used for recycling.

Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

· Recommended cleaning agent: Water, if necessary with cleaning agent.

14.1 UN number or ID number	
ADR, ADN, IMDG	Void
IATA	UN1263
14.2 UN proper shipping name	
ADR, ADN, IMDG	Void
IATA	PAINT
14.3 Transport hazard class(es)	
ADR, ADN, IMDG	
Class	Void
Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR, IMDG	Void
IATA	III
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Not applicable.
14.7 Maritime transport in bulk accordi	
IMO instruments	Not applicable.

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.

(Contd. on page 8)

Printing date 22.07.2024 Version number 6 Revision: 22.07.2024

Trade name MALERLACK KHX 90 GLÄNZEND WEISS

(Contd. of page 7)

- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

- · Contact: chemikalieninfo@murexin.com (+43 02622/27401)
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

* * Data compared to the previous version altered.