

Safety data sheet according to UK REACH

Printing date 09.09.2026

Version number 4 (replaces version 3)

Revision: 09.09.2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name** *MureFix KK 346*
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** *Adhesives*
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
MUREXIN GmbH
Franz v. Furtenbachstr. 1
A-2700 Wiener Neustadt
Tel.: +43 (0)2622/27401
- **Informing department:** *chemikalieninfo@murexin.com*
- **1.4 Emergency telephone number:**
UK National poisons Emergency number.: +44 (0) 870 600 6266

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.
 Eye Irrit. 2 H319 Causes serious eye irritation.
 Skin Sens. 1 H317 May cause an allergic skin reaction.
 STOT SE 3 H336 May cause drowsiness or dizziness.

- **Additional information:**
The full text of the classification and labelling elements mentioned is given in Section 16.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS02 GHS07 GHS09

- **Signal word** *Danger*
- **Hazard-determining components of labelling:**
ethyl acetate
p-tert-Butylphenol-Formaldehyde Resin
Hydrocarbons C6-C7, isoalkanes, cyclic, <5%n-hexane
Rosin
- **Hazard statements**
H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.

(Contd. on page 2)

GB

Safety data sheet according to UK REACH

Printing date 09.09.2026

Version number 4 (replaces version 3)

Revision: 09.09.2026

Trade name MureFix KK 346

(Contd. of page 1)

H319 Causes serious eye irritation.
 H317 May cause an allergic skin reaction.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P273 Avoid release to the environment.
 P280 Wear protective gloves / eye protection / face protection.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P312 Call a POISON CENTER/doctor if you feel unwell.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards**Results of PBT and vPvB assessment**

- **PBT:** Not applicable
- **vPvB:** Not applicable

SECTION 3: Composition/information on ingredients

3.2 Mixtures

· **Description:** Mixture consisting of the following components with harmless additives.

Dangerous components:

CAS: 141-78-6 EINECS: 205-500-4 Reg.nr.: 2119475103-46 01-2119475103-46-xxxx	ethyl acetate ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	25-50%
EC number: 926-605-8 Reg.nr.: 01-2119486291-36-xxxx	Hydrocarbons C6-C7, isoalkanes, cyclic, <5%-hexane ⚠ Flam. Liq. 2, H225 ⚠ Asp. Tox. 1, H304 ⚠ Aquatic Chronic 2, H411 ⚠ STOT SE 3, H336 EUH066	≥10-<25%
CAS: 78-93-3 EINECS: 201-159-0 Reg.nr.: 01-2119457290-43-xxxx	butanone ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	10-25%
CAS: 64742-49-0 EC number: 927-510-4 Reg.nr.: 01-2119475515-33-xxxx	Naphtha (petroleum), hydrotreated light ⚠ Flam. Liq. 2, H225 ⚠ Asp. Tox. 1, H304 ⚠ Aquatic Chronic 2, H411 ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	2.5-5%
CAS: 64742-49-0 EC number: 931-254-9 Reg.nr.: 01-2119484651-34-xxxx	Naphtha (petroleum), hydrotreated light ⚠ Flam. Liq. 2, H225 ⚠ Asp. Tox. 1, H304 ⚠ Aquatic Chronic 2, H411 ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	2.5-5%
EC number: 921-024-6	Kohlenwasserstoffe, C6-C7, n-Alkane, Isoalkane, Cyclene, <5% n-Hexan ⚠ Flam. Liq. 2, H225 ⚠ Asp. Tox. 1, H304 ⚠ Aquatic Chronic 2, H411 ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	2.5-5%

(Contd. on page 3)

Safety data sheet according to UK REACH

Printing date 09.09.2026

Version number 4 (replaces version 3)

Revision: 09.09.2026

Trade name MureFix KK 346

CAS: 25085-50-1	p-tert-Butylphenol-Formaldehyde Resin ⚠ Skin Sens. 1, H317	(Contd. of page 2) 2.5-5%
CAS: 8050-09-7 EINECS: 232-475-7	Rosin ⚠ Skin Sens. 1, H317	1-2.5%
CAS: 68610-51-5 EINECS: 271-867-2	phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene ⚠ Repr. 2, H361d Aquatic Chronic 4, H413	<0.5%
CAS: 1314-13-2 EINECS: 215-222-5 Reg.nr.: 01-2119463881-32-01029	zinc oxide ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	≥0.025-<0.25%

SECTION 4: First aid measures

4.1 Description of first aid measures

After inhalation

Supply fresh air and call for doctor for safety reasons.

In case of unconsciousness bring patient into stable side position for transport.

After skin contact

If skin irritation continues, consult a doctor.

Instantly wash with water and soap and rinse thoroughly.

After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

After swallowing

In case of persistent symptoms consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents

CO₂, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

Use fire fighting measures that suit the environment.

For safety reasons unsuitable extinguishing agents

Water with a full water jet.

5.2 Special hazards arising from the substance or mixture

No further relevant information available.

5.3 Advice for firefighters

Protective equipment: No special measures required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Wear protective clothing.

6.2 Environmental precautions:

Do not allow product to reach sewage system or water bodies.

Prevent material from reaching sewage system, holes and cellars.

Inform respective authorities in case product reaches water or sewage system.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

(Contd. on page 4)

Safety data sheet according to UK REACH

Printing date 09.09.2026

Version number 4 (replaces version 3)

Revision: 09.09.2026

Trade name MureFix KK 346

(Contd. of page 3)

See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Keep containers tightly sealed.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:**
Store in cool location.
Store only in the original container.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed containers.
- **Storage class 3**
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with critical values that require monitoring at the workplace:

141-78-6 ethyl acetate

WEL	Short-term value: 1468 mg/m ³ , 400 ppm Long-term value: 734 mg/m ³ , 200 ppm
-----	--

78-93-3 butanone

WEL	Short-term value: 899 mg/m ³ , 300 ppm Long-term value: 600 mg/m ³ , 200 ppm Sk, BMGV
-----	---

8050-09-7 Rosin

WEL	Short-term value: 0.15 mg/m ³ Long-term value: 0.05 mg/m ³ Sen
-----	--

· Ingredients with biological limit values:

78-93-3 butanone

BMGV	70 µmol/L Medium: urine Sampling time: post shift Parameter: butan-2-one
------	---

· **Additional information:** The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

- **Appropriate engineering controls** No further data; see section 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures**
The usual precautionary measures should be adhered to in handling the chemicals.
Keep away from foodstuffs, beverages and food.
Instantly remove any soiled and impregnated garments.
Wash hands during breaks and at the end of the work.
Avoid contact with the eyes and skin.
- **Breathing equipment:**
Not necessary if room is well-ventilated.
Use breathing protection in case of insufficient ventilation.

(Contd. on page 5)

Safety data sheet according to UK REACH

Printing date 09.09.2026

Version number 4 (replaces version 3)

Revision: 09.09.2026

Trade name MureFix KK 346

(Contd. of page 4)

Filter A/P2.

- **Hand protection**

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Material of gloves**

Butyl rubber, BR

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye/face protection**

Safety glasses

Face protection

- **Body protection:** Protective work clothing.

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Physical state**

Liquid

- **Colour:**

Light brown

- **Smell:**

Fruit-like

- **Odour threshold:**

Not determined

- **Melting point/freezing point:**

Not determined

- **Boiling point or initial boiling point and boiling range**

60 °C

- **Flammability**

Highly flammable.

- **Lower and upper explosion limit**

- **Lower:**

1.8 Vol % (Hydrocarbons C6-C7,n-alkanes, isoalkanes, cyclenes <5%n-hexane)

- **Upper:**

11.5 Vol % (141-78-6 ethyl acetate)

- **Flash point:**

-25 °C

- **Auto-ignition temperature:**

460 °C

- **Decomposition temperature:**

Not determined

- **pH**

Mixture is non-polar/aprotic.

- **Viscosity:**

- **Kinematic viscosity**

Not determined

- **dynamic at 20 °C:**

2,800 mPas

- **Solubility**

- **Water:**

Not miscible or difficult to mix

- **Partition coefficient n-octanol/water (log value)**

Not determined

- **Steam pressure at 20 °C:**

105 hPa

- **Density and/or relative density**

- **Density at 20 °C**

0.9 g/cm³

- **Relative density**

Not determined

- **Vapour density**

Not determined

- **9.2 Other information**

- **Appearance:**

- **Form:**

Fluid

- **Important information on protection of health and environment, and on safety.**

- **Self-inflammability:**

Product is not selfigniting.

- **Explosive properties:**

Product is not explosive. However, formation of explosive air/steam mixtures is possible.

(Contd. on page 6)

Safety data sheet according to UK REACH

Printing date 09.09.2026

Version number 4 (replaces version 3)

Revision: 09.09.2026

Trade name MureFix KK 346

(Contd. of page 5)

· Solvent content:	
· Solids content:	21.5 %
· Change in condition	
· Evaporation rate	Not determined
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Highly flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** None

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:

141-78-6 ethyl acetate

Oral	LD50	5,600 mg/kg (rat)
Dermal	LD50	18,000 mg/kg (rabbit)

Hydrocarbons C6-C7, isoalkanes, cyclic, <5% n-hexane

Oral	LD50	>5,000 mg/kg (rat)
------	------	--------------------

78-93-3 butanone

Oral	LD50	3,300 mg/kg (rat)
Dermal	LD50	6,400-8,000 mg/kg (rabbit)

64742-49-0 Naphtha (petroleum), hydrotreated light

Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC50/4 h	5 mg/l (rat)

(Contd. on page 7)

Safety data sheet according to UK REACH

Printing date 09.09.2026

Version number 4 (replaces version 3)

Revision: 09.09.2026

Trade name MureFix KK 346

(Contd. of page 6)

64742-49-0 Naphtha (petroleum), hydrotreated light

Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC50/4 h	5 mg/l (rat)

1314-13-2 zinc oxide

Oral	LD50	>5,000 mg/kg (rat)
Inhalative	LC50/4 h	>5,700 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

78-93-3 butanone

List II

SECTION 12: Ecological information

· **12.1 Toxicity**· **Aquatic toxicity:****141-78-6 ethyl acetate**

EC 50	3,300 mg/l (Acartia Tonsa)
	717 mg/l (G)
LC50	230 mg/l (F2)

Hydrocarbons C6-C7, isoalkanes, cyclic, <5%n-hexane

ErL50	55 mg/l (Acartia Tonsa)
EL50	3 mg/l (G)
LC50	3.87 mg/l (G)

78-93-3 butanone

ErC50	2,029 mg/l (F2)
EC 50	308 mg/l (G) (48h)

64742-49-0 Naphtha (petroleum), hydrotreated light

IC 50	1-10 mg/l (Acartia Tonsa)
LC50	1-10 mg/l (Cyprinus carpio (Karpfen))

64742-49-0 Naphtha (petroleum), hydrotreated light

IC 50	1-10 mg/l (Acartia Tonsa)
LC50	1-10 mg/l (Cyprinus carpio (Karpfen))

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable
- **vPvB:** Not applicable
- **12.6 Endocrine disrupting properties**
- For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Water hazard class (Germany) 2 (Self-assessment): hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system.

(Contd. on page 8)

GB

Safety data sheet according to UK REACH

Printing date 09.09.2026

Version number 4 (replaces version 3)

Revision: 09.09.2026

Trade name MureFix KK 346

Danger to drinking water if even small quantities leak into soil.

(Contd. of page 7)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncleaned packagings:

Recommendation:

Disposal must be made according to official regulations.

Packagings that cannot be cleaned are to be disposed of in the same manner as the product.

SECTION 14: Transport information

14.1 UN number or ID number

ADR, IMDG, IATA

UN1133

14.2 UN proper shipping name

ADR

1133 ADHESIVES, ENVIRONMENTALLY HAZARDOUS

IMDG

ADHESIVES, MARINE POLLUTANT

IATA

ADHESIVES

14.3 Transport hazard class(es)

ADR, IMDG



Class

3 Flammable liquids.

Label

3

IATA



Class

3 Flammable liquids.

Label

3

14.4 Packing group

ADR, IMDG, IATA

II

14.5 Environmental hazards:

Product contains environmentally hazardous substances: Hydrocarbons C6-C7, n-alkanes, isoalkanes, cyclenes <5% n-hexane

Marine pollutant:

Yes

Special marking (ADR):

Symbol (fish and tree)

Symbol (fish and tree)

14.6 Special precautions for user

Warning: Flammable liquids.

Kemler Number:

33

EMS Number:

F-E, S-D

Stowage Category

B

14.7 Maritime transport in bulk according to IMO instruments

Not applicable

(Contd. on page 9)

Safety data sheet according to UK REACH

Printing date 09.09.2026

Version number 4 (replaces version 3)

Revision: 09.09.2026

Trade name MureFix KK 346

(Contd. of page 8)

· Transport/Additional information:

· ADR

· Limited quantities (LQ)	5L
· Transport category	2
· Tunnel restriction code	D/E

· UN "Model Regulation":	UN 1133 ADHESIVES, 3, II, ENVIRONMENTALLY HAZARDOUS
--------------------------	---

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

· Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H361d Suspected of damaging the unborn child.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- H413 May cause long lasting harmful effects to aquatic life.
- EUH066 Repeated exposure may cause skin dryness or cracking.

· Contact: chemikalieninfo@murexin.com (+43 02622/27401)

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

(Contd. on page 10)

Safety data sheet according to UK REACH

Printing date 09.09.2026

Version number 4 (replaces version 3)

Revision: 09.09.2026

Trade name MureFix KK 346

(Contd. of page 9)

IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 Flam. Liq. 2: Flammable liquids – Category 2
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 Skin Sens. 1: Skin sensitisation – Category 1
 Repr. 2: Reproductive toxicity – Category 2
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 Asp. Tox. 1: Aspiration hazard – Category 1
 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
 Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4

· *** Data compared to the previous version altered.**

GB