

## Safety data sheet according to UK REACH

Printing date 15.04.2026

Version number 1

Revision: 15.04.2026

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name MurePrime MPE 3 Metall Primer**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the mixture Primer/ Subcoating**
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
MUREXIN GmbH  
Franz v. Furtenbachstr. 1  
A-2700 Wiener Neustadt  
Tel.: +43 (0)2622/27401
- **Informing department:** chemikalieninfo@murexin.com
- **1.4 Emergency telephone number:**  
UK National poisons Emergency number.: +44 (0) 870 600 6266

### SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3      H226 Flammable liquid and vapour.



GHS08 health hazard

Resp. Sens. 1      H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
Carc. 2              H351 Suspected of causing cancer.  
STOT RE 2         H373 May cause damage to the hearing organs through prolonged or repeated exposure.



GHS07

Acute Tox. 4        H332 Harmful if inhaled.  
Skin Irrit. 2        H315 Causes skin irritation.  
Eye Irrit. 2         H319 Causes serious eye irritation.  
Skin Sens. 1        H317 May cause an allergic skin reaction.  
STOT SE 3          H335 May cause respiratory irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word Danger**

(Contd. on page 2)

GB

## Safety data sheet according to UK REACH

Printing date 15.04.2026

Version number 1

Revision: 15.04.2026

**Trade name MurePrime MPE 3 Metall Primer**

(Contd. of page 1)

· **Hazard-determining components of labelling:**

Xylol

*m*-tolylidene diisocyanate

ethylbenzene

Triphenylphosphite

Mixture of *alpha*-3-(3-(2*H*-benzotriazol-2-yl)-5-*tert*-butyl-4-hydroxyphenyl)propionyl-*omega*-hydroxypoly(oxyethylene) and *alpha*-3-(3-(2

· **Hazard statements**

H226 Flammable liquid and vapour.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

H373 May cause damage to the hearing organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Additional information:**

Contains isocyanates. May produce an allergic reaction.

As from 24 August 2023 adequate training is required before industrial or professional use. Handling this product may cause allergic reactions in people who are already sensitized to diisocyanates. If you have asthma, eczema, or skin problems, avoid contact with the product, including skin contact.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable· **vPvB:** Not applicable

### SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**

· **Description:** Mixture consisting of the following components with harmless additives.

(Contd. on page 3)

GB

## Safety data sheet according to UK REACH

Printing date 15.04.2026

Version number 1

Revision: 15.04.2026

Trade name MurePrime MPE 3 Metall Primer

(Contd. of page 2)

· <b>Dangerous components:</b>		
CAS: 1330-20-7 EINECS: 215-535-7	Xylol Flam. Liq. 3, H226 STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 Aquatic Chronic 3, H412	25-50%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate Consisting of: 70657-70-4 2-methoxypropyl acetate (0.29%) Flam. Liq. 3, H226 STOT SE 3, H336	10-25%
CAS: 100-41-4 EINECS: 202-849-4	ethylbenzene Flam. Liq. 2, H225 STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H332 Aquatic Chronic 3, H412	≥5-<10%
CAS: 26471-62-5 EINECS: 247-722-4	m-tolylidene diisocyanate Acute Tox. 2, H330 Resp. Sens. 1, H334; Carc. 2, H351 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335 Aquatic Chronic 3, H412 EUH204 Specific concentration limit: Resp. Sens. 1; H334: C ≥ 0.1 %	1%
CAS: 101-02-0 EINECS: 202-908-4	Triphenylphosphite Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1A, H317	≥0.1-<0.25%
CAS: 104810-48-2 ELINCS: 400-830-7 Reg.nr.: 01-0000015075-76-0017	Mixture of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2 Aquatic Chronic 2, H411 Skin Sens. 1, H317	≥0.1-<0.25%
CAS: 108-88-3 EINECS: 203-625-9	Toluole Flam. Liq. 2, H225 Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304 Skin Irrit. 2, H315; STOT SE 3, H336 Aquatic Chronic 3, H412	<0.5%

### SECTION 4: First aid measures

#### · 4.1 Description of first aid measures

##### · **General information**

Instantly remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

##### · **After inhalation**

Supply fresh air and call for doctor for safety reasons.

In case of unconsciousness bring patient into stable side position for transport.

##### · **After skin contact**

Instantly wash with water and soap and rinse thoroughly.

(Contd. on page 4)

## Safety data sheet according to UK REACH

Printing date 15.04.2026

Version number 1

Revision: 15.04.2026

**Trade name MurePrime MPE 3 Metall Primer**

(Contd. of page 3)

*If skin irritation continues, consult a doctor.*

- **After eye contact**  
*Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.*
- **After swallowing** *In case of persistent symptoms consult doctor.*
- **4.2 Most important symptoms and effects, both acute and delayed**  
*No further relevant information available.*
- **4.3 Indication of any immediate medical attention and special treatment needed**  
*No further relevant information available.*

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents**  
*CO<sub>2</sub>, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.*
- **For safety reasons unsuitable extinguishing agents** *Water with a full water jet.*
- **5.2 Special hazards arising from the substance or mixture**  
*Formation of poisonous gases during heating or in fires.*
- **5.3 Advice for firefighters**
- **Protective equipment:** *Put on breathing apparatus.*

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
*Put on breathing apparatus.  
Wear protective equipment. Keep unprotected persons away.  
Wear protective clothing.*
- **6.2 Environmental precautions:**  
*Do not allow product to reach sewage system or water bodies.  
Inform respective authorities in case product reaches water or sewage system.*
- **6.3 Methods and material for containment and cleaning up:**  
*Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose of contaminated material as waste according to item 13.  
Ensure adequate ventilation.*
- **6.4 Reference to other sections**  
*See Section 7 for information on safe handling  
See Section 8 for information on personal protection equipment.  
See Section 13 for information on disposal.*

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
*Keep containers tightly sealed.  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle container with care.  
Prevent formation of aerosols.*
- **Information about protection against explosions and fires:**  
*Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Keep breathing equipment ready.*
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** *Store only in the original container.*
- **Information about storage in one common storage facility:** *Store away from foodstuffs.*
- **Further information about storage conditions:** *Keep container tightly sealed.*
- **Storage class 3**

(Contd. on page 5)

## Safety data sheet according to UK REACH

Printing date 15.04.2026

Version number 1

Revision: 15.04.2026

Trade name **MurePrime MPE 3 Metall Primer**

(Contd. of page 4)

· **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

#### · 8.1 Control parameters

##### · Components with critical values that require monitoring at the workplace:

###### 1330-20-7 Xylol

WEL	Short-term value: 441 mg/m <sup>3</sup> , 100 ppm Long-term value: 220 mg/m <sup>3</sup> , 50 ppm Sk; BMGV
-----	--

###### 108-65-6 2-methoxy-1-methylethyl acetate

WEL	Short-term value: 548 mg/m <sup>3</sup> , 100 ppm Long-term value: 274 mg/m <sup>3</sup> , 50 ppm Sk
-----	--

###### 100-41-4 ethylbenzene

WEL	Short-term value: 552 mg/m <sup>3</sup> , 125 ppm Long-term value: 441 mg/m <sup>3</sup> , 100 ppm Sk
-----	---

###### 26471-62-5 m-tolyldiene diisocyanate

WEL	Short-term value: 0.07 mg/m <sup>3</sup> Long-term value: 0.02 mg/m <sup>3</sup> Sen; as -NCO
-----	---

###### 108-88-3 Toluole

WEL	Short-term value: 384 mg/m <sup>3</sup> , 100 ppm Long-term value: 191 mg/m <sup>3</sup> , 50 ppm Sk
-----	--

##### · Ingredients with biological limit values:

###### 1330-20-7 Xylol

BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
------	--

· **Additional information:** The lists that were valid during the compilation were used as basis.

#### · 8.2 Exposure controls

· **Appropriate engineering controls** No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

##### · General protective and hygienic measures

The usual precautionary measures should be adhered to in handling the chemicals.

Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

##### · Breathing equipment:

In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.

##### · Hand protection

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

##### · Material of gloves

Nitrile rubber, NBR

(Contd. on page 6)

## Safety data sheet according to UK REACH

Printing date 15.04.2026

Version number 1

Revision: 15.04.2026

Trade name MurePrime MPE 3 Metall Primer

(Contd. of page 5)

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye/face protection** Safety glasses recommended during refilling.

- **Body protection:** Protective work clothing.

### SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Physical state**

Liquid

- **Colour:**

Light yellow

- **Smell:**

Solvent-like

- **Odour threshold:**

Not determined

- **Melting point/freezing point:**

Not determined

- **Boiling point or initial boiling point and boiling range**

100-200 °C

- **Flammability**

Flammable.

- **Lower and upper explosion limit**

- **Lower:**

1 Vol %

- **Upper:**

7 Vol %

- **Flash point:**

~32 °C

- **Auto-ignition temperature:**

&gt;330 °C

- **Decomposition temperature:**

Not determined

- **pH**

Mixture is non-soluble (in water).

- **Viscosity:**

- **Kinematic viscosity at 40 °C**

>20.5 mm<sup>2</sup>/s

- **dynamic:**

Not determined

- **Solubility**

- **Water:**

Not miscible or difficult to mix

- **Partition coefficient n-octanol/water (log value)**

Not determined

- **Steam pressure at 20 °C:**

8 hPa

- **Density and/or relative density**

- **Density at 20 °C**

1 g/cm<sup>3</sup>

- **Relative density**

Not determined

- **Vapour density**

Not determined

- **9.2 Other information**

- **Appearance:**

- **Form:**

Liquid

- **Important information on protection of health and environment, and on safety.**

- **Self-inflammability:**

Product is not selfigniting.

- **Explosive properties:**

Product is not explosive. However, formation of explosive air/steam mixtures is possible.

- **Change in condition**

- **Evaporation rate**

Not determined

- **Information with regard to physical hazard classes**

- **Explosives**

Void

- **Flammable gases**

Void

- **Aerosols**

Void

(Contd. on page 7)

## Safety data sheet according to UK REACH

Printing date 15.04.2026

Version number 1

Revision: 15.04.2026

Trade name MurePrime MPE 3 Metall Primer

(Contd. of page 6)

· <b>Oxidising gases</b>	Void
· <b>Gases under pressure</b>	Void
· <b>Flammable liquids</b>	Flammable liquid and vapour.
· <b>Flammable solids</b>	Void
· <b>Self-reactive substances and mixtures</b>	Void
· <b>Pyrophoric liquids</b>	Void
· <b>Pyrophoric solids</b>	Void
· <b>Self-heating substances and mixtures</b>	Void
· <b>Substances and mixtures, which emit flammable gases in contact with water</b>	Void
· <b>Oxidising liquids</b>	Void
· <b>Oxidising solids</b>	Void
· <b>Organic peroxides</b>	Void
· <b>Corrosive to metals</b>	Void
· <b>Desensitised explosives</b>	Void

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** None

### SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Harmful if inhaled.

- **LD/LC50 values that are relevant for classification:**

#### 1330-20-7 Xylol

Oral	LD50	5,251-5,627 mg/kg (mouse) 4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (not defined) >1,700 mg/kg (rabbit)
Inhalative	LC50/4 h	21.7 mg/l (rat)

#### 108-65-6 2-methoxy-1-methylethyl acetate

Oral	LD50	8,500 mg/kg (rat)
Inhalative	LC50/4 h	35.7 mg/l (rat)

#### 100-41-4 ethylbenzene

Oral	LD50	3,500 mg/kg (rat)
Dermal	LD50	17,800 mg/kg (not defined) 15,400 mg/kg (rabbit)

#### 101-02-0 Triphenylphosphite

Oral	LD50	1,600 mg/kg (not defined) 444 mg/kg (rat)
------	------	--

#### 108-88-3 Toluole

Oral	LD50	5,000 mg/kg (not defined) 636 mg/kg (rat)
------	------	--

(Contd. on page 8)

## Safety data sheet according to UK REACH

Printing date 15.04.2026

Version number 1

Revision: 15.04.2026

**Trade name MurePrime MPE 3 Metall Primer**

(Contd. of page 7)

Dermal	LD50	12,124 mg/kg (not defined)
		12,200 mg/kg (rabbit)
Inhalative	LC50/4 h	5,320 mg/l (not defined)
		49 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Carcinogenicity** Suspected of causing cancer.
- **STOT-single exposure** May cause respiratory irritation.
- **STOT-repeated exposure**  
May cause damage to the hearing organs through prolonged or repeated exposure.
- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

None of the ingredients is listed.

### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable
- **vPvB:** Not applicable
- **12.6 Endocrine disrupting properties**  
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**  
Harmful to aquatic organisms  
Water hazard class (Germany) 2 (Self-assessment): hazardous for water.  
Do not allow product to reach ground water, water bodies or sewage system.  
Danger to drinking water if even small quantities leak into soil.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Waste disposal key number:**  
55903  
Harzrückstände, nicht ausgehärtet  
gefährlich
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

GB

(Contd. on page 9)

## Safety data sheet according to UK REACH

Printing date 15.04.2026


Version number 1

Revision: 15.04.2026

Trade name MurePrime MPE 3 Metall Primer

(Contd. of page 8)

### SECTION 14: Transport information

· 14.1 UN number or ID number · ADR, IMDG, IATA	UN1866
· 14.2 UN proper shipping name · ADR · IMDG, IATA	1866 RESIN SOLUTION RESIN SOLUTION
· 14.3 Transport hazard class(es) · ADR, IMDG, IATA	
· Class · Label	3 Flammable liquids. 3
· 14.4 Packing group · ADR, IMDG, IATA	III
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user · Kemler Number: · EMS Number: · Stowage Category	Warning: Flammable liquids. 30 F-E, S-E A
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Transport category · Tunnel restriction code	5L 3 D/E
· UN "Model Regulation":	UN 1866 RESIN SOLUTION, 3, III

### SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Poisons Act
- Regulated explosives precursors  
None of the ingredients is listed.
- Regulated poisons  
None of the ingredients is listed.
- Reportable explosives precursors  
None of the ingredients is listed.
- Reportable poisons  
None of the ingredients is listed.
- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

(Contd. on page 10)

## Safety data sheet according to UK REACH

Printing date 15.04.2026

Version number 1

Revision: 15.04.2026

**Trade name MurePrime MPE 3 Metall Primer**

(Contd. of page 9)

- **Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t**
- **15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.**

### SECTION 16: Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

#### · **Relevant phrases**

- H225 *Highly flammable liquid and vapour.*
- H226 *Flammable liquid and vapour.*
- H302 *Harmful if swallowed.*
- H304 *May be fatal if swallowed and enters airways.*
- H312 *Harmful in contact with skin.*
- H315 *Causes skin irritation.*
- H317 *May cause an allergic skin reaction.*
- H319 *Causes serious eye irritation.*
- H330 *Fatal if inhaled.*
- H332 *Harmful if inhaled.*
- H334 *May cause allergy or asthma symptoms or breathing difficulties if inhaled.*
- H335 *May cause respiratory irritation.*
- H336 *May cause drowsiness or dizziness.*
- H351 *Suspected of causing cancer.*
- H361d *Suspected of damaging the unborn child.*
- H373 *May cause damage to organs through prolonged or repeated exposure.*
- H400 *Very toxic to aquatic life.*
- H410 *Very toxic to aquatic life with long lasting effects.*
- H411 *Toxic to aquatic life with long lasting effects.*
- H412 *Harmful to aquatic life with long lasting effects.*
- EUH204 *Contains isocyanates. May produce an allergic reaction.*

- **Contact:** chemikalieninfo@murexin.com (+43 02622/27401)

#### · **Abbreviations and acronyms:**

- RID: *Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)*
- ICAO: *International Civil Aviation Organisation*
- ADR: *Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)*
- IMDG: *International Maritime Code for Dangerous Goods*
- IATA: *International Air Transport Association*
- GHS: *Globally Harmonised System of Classification and Labelling of Chemicals*
- EINECS: *European Inventory of Existing Commercial Chemical Substances*
- ELINCS: *European List of Notified Chemical Substances*
- CAS: *Chemical Abstracts Service (division of the American Chemical Society)*
- LC50: *Lethal concentration, 50 percent*
- LD50: *Lethal dose, 50 percent*
- PBT: *Persistent, Bioaccumulative and Toxic*
- vPvB: *very Persistent and very Bioaccumulative*
- Flam. Liq. 2: *Flammable liquids – Category 2*
- Flam. Liq. 3: *Flammable liquids – Category 3*
- Acute Tox. 4: *Acute toxicity – Category 4*
- Acute Tox. 2: *Acute toxicity – Category 2*
- Skin Irrit. 2: *Skin corrosion/irritation – Category 2*
- Eye Irrit. 2: *Serious eye damage/eye irritation – Category 2*
- Resp. Sens. 1: *Respiratory sensitisation – Category 1*
- Skin Sens. 1: *Skin sensitisation – Category 1*
- Skin Sens. 1A: *Skin sensitisation – Category 1A*
- Carc. 2: *Carcinogenicity – Category 2*
- Repr. 2: *Reproductive toxicity – Category 2*
- STOT SE 3: *Specific target organ toxicity (single exposure) – Category 3*
- STOT RE 2: *Specific target organ toxicity (repeated exposure) – Category 2*
- Asp. Tox. 1: *Aspiration hazard – Category 1*
- Aquatic Acute 1: *Hazardous to the aquatic environment - acute aquatic hazard – Category 1*
- Aquatic Chronic 1: *Hazardous to the aquatic environment - long-term aquatic hazard – Category 1*
- Aquatic Chronic 2: *Hazardous to the aquatic environment - long-term aquatic hazard – Category 2*

(Contd. on page 11)

**Safety data sheet  
according to UK REACH**

Printing date 15.04.2026

Version number 1

Revision: 15.04.2026

**Trade name MurePrime MPE 3 Metall Primer**

*Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3*

(Contd. of page 10)

· **\* Data compared to the previous version altered.**

GB