Revision: 31.01.2024

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.02.2024

Version number 7 (replaces version 6)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name PARKETTKLEBSTOFF X-BOND MS-K 539
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Adhesives
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

MUREXIN GmbH

Franz v. Furtenbachstr. 1 A-2700 Wiener Neustadt Tel.: +43 (0)2622/27401

- · Informing department: chemikalieninfo@murexin.com
- · 1.4 Emergency telephone number:

UK National poisons Emergency number.: +44 (0) 870 600 6266

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

 The product is not classified, according to the GB CLP regulation.
- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008 Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Additional information:

Contains trimethoxyvinylsilane. May produce an allergic reaction.

Safety data sheet available on request.

- 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture consisting of the following components with harmless additives.

· Dangerous components:		
CAS: 1317-65-3 EINECS: 215-279-6	Calciumcarbonat substance with a Community workplace exposure limit	10-25%
CAS: 7727-43-7 EINECS: 231-784-4	barium sulphate, natural substance with a Community workplace exposure limit	5-10%
CAS: 34396-03-7 EINECS: 251-995-5 Reg.nr.: 01-2119970322-42- 0000	trimethoxy(2,4,4-trimethylpentyl)silane Flam. Liq. 3, H226	2.5-5%

(Contd. on page 2)

Printing date 01.02.2024 Version number 7 (replaces version 6) Revision: 31.01.2024

Trade name PARKETTKLEBSTOFF X-BOND MS-K 539

CAS: 2996-92-1 EINECS: 221-066-9 Reg.nr.: 01-2119964479-19- 0001	(Contribution of the contribution of the contr	ntd. of page 1) 2.5-5%
CAS: 2768-02-7 EINECS: 220-449-8 Reg.nr.: 01-2119513215-52- xxxx	trimethoxyvinylsilane Flam. Liq. 3, H226 Skin Sens. 1B, H317	≥0.5-<1%

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After skin contact

Instantly wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

- · After swallowing In case of persistent symptoms consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents Use fire fighting measures that suit the environment.
- · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective clothing.
- · 6.2 Environmental precautions:

Do not allow product to reach sewage system or water bodies.

Dilute with much water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· 6.4 Reference to other sections

No dangerous materials are released.

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling No special precautions necessary if used correctly.
- Information about protection against explosions and fires: No special measures required.

(Contd. on page 3)

Printing date 01.02.2024 Version number 7 (replaces version 6) Revision: 31.01.2024

Trade name PARKETTKLEBSTOFF X-BOND MS-K 539

(Contd. of page 2)

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- Requirements to be met by storerooms and containers: Store only in the original container.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class 10
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with critical values that require monitoring at the workplace:

1317-65-3 Calciumcarbonat

WEL Long-term value: 10* 4** mg/m³
*inhalable dust; **respirable

7727-43-7 barium sulphate, natural

WEL Long-term value: 10* 4** mg/m³ *inhalable dust **respirable dust

- · Additional information: The lists that were valid during the compilation were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures

The usual precautionary measures should be adhered to in handling the chemicals.

Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

- · Breathing equipment: Not required.
- · Hand protection

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

Use gloves of stable material (e.g. Nitrile) - if necessary tricoted to improve the wearability.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye/face protection Safety glasses recommended during refilling.
- · Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information

· Physical state Fluid · Colour: Beige

Smell: Characteristic
 Odour threshold: Not determined.
 Melting point/freezing point: Not determined

· Boiling point or initial boiling point and

boiling range >300 °C (Silanterminiertes Prepolymer)

(Contd. on page 4)

Printing date 01.02.2024 Version number 7 (replaces version 6) Revision: 31.01.2024

Trade name PARKETTKLEBSTOFF X-BOND MS-K 539

(Contd. of page 3)

· Flammability Not applicable.

· Lower and upper explosion limit

· Lower: Not determined.
· Upper: Not determined.

· Flash point: 138 °C

· Auto-ignition temperature: 380 °C (Silanterminiertes Prepolymer)

· **Decomposition temperature:** Not determined.

· **pH** Mixture is non-soluble (in water).

· Viscosity:

Kinematic viscositydynamic:Not determined.Not determined.

· Solubility

· Water: Not determined.

· Partition coefficient n-octanol/water (log

value) Not determined.
Steam pressure: Not determined.

· Density and/or relative density

Density at 20 °C
 Relative density
 Vapour density
 1.7 g/cm³
 Not determined.
 Not determined.

· 9.2 Other information

· Appearance:

· Form: Pasty

· Important information on protection of health

and environment, and on safety.

• Self-inflammability: Product is not selfigniting. • Explosive properties: Product is not explosive.

· Change in condition

· Evaporation rate Not determined.

· Information with regard to physical hazard classes

· Explosives Void Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void Flammable liquids Void Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void Void · Pyrophoric solids · Self-heating substances and mixtures Void · Substances and mixtures, which emit Void flammable gases in contact with water · Oxidising liquids Void Oxidising solids Void · Organic peroxides Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability

· Corrosive to metals

Desensitised explosives

· Conditions to be avoided: No decomposition if used according to specifications.

Void

Void

(Contd. on page 5)

Printing date 01.02.2024

Version number 7 (replaces version 6)

Trade name PARKETTKLEBSTOFF X-BOND MS-K 539

(Contd. of page 4)

Revision: 31.01.2024

- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: None

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	values tha	t are relevant for classification:
1317-65-3	Calciumo	carbonat
Oral	LD50	>5,000 mg/kg (rat)
34396-03-	7 trimetho	oxy(2,4,4-trimethylpentyl)silane
Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC50/4 h	>11.2 mg/l (rat)
2996-92-1	Trimetho	xyphenylsilan
Oral	LD50	1,049 mg/kg (rat)
Dermal	LD50	3,014 mg/kg (rabbit)
2768-02-7	trimethox	kyvinylsilane
Oral	LD50	7,130 mg/kg (rat)
Dermal	LD50	3,260 mg/kg (rabbit)

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) -
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic t	oxicity:	
1317-65-3	B Calciumcarbonat	
EC 50/48	h >1,000 mg/l (G)	
EC 50	289 mg/l (Desmodesmus subspicatus)	
LC50	>10,000 mg/l (Oncorhynchus mykiss (Regenbogenforelle))	
34396-03	-7 trimethoxy(2,4,4-trimethylpentyl)silane	
EC 50	>100 mg/l (G) (Klärschlamm (3h))	
LC50	>100 mg/l (Oncorhynchus mykiss (Regenbogenforelle))	
2996-92-1	Trimethoxyphenylsilan	
EC 50/48	h >100 mg/l (G)	
		(Contd. on page 6)

iliu. Oli page t

Printing date 01.02.2024

Version number 7 (replaces version 6)

Trade name PARKETTKLEBSTOFF X-BOND MS-K 539

(Contd. of page 5)

Revision: 31.01.2024

	(Conta. or page 5)
EC 50	>100 mg/l (Acartia Tonsa)
LC50	>100 mg/l (Oncorhynchus mykiss (Regenbogenforelle))

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class (Germany) 1 (Self-assessment): slightly hazardous for water.

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Can be deposited with household garbage after solidification following consultation with the operator of the waste disposal facility and the pertinent authorities and under adherence to the necessary technical regulations.

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleaning agent: Water, if necessary with cleaning agent.

14.1 UN number or ID number		
ADR, ADN, IMDG, IATA	Void	
14.2 UN proper shipping name		
ADR, ADN, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA		
Class	Void	
14.4 Packing group		
ADR, IMDG, IATA	Void	
14.5 Environmental hazards:		
Marine pollutant:	No	
14.6 Special precautions for user	Not applicable.	
14.7 Maritime transport in bulk accordi	ing to	
IMO instruments	Not applicable.	
UN "Model Regulation":	Void	

- GB

Printing date 01.02.2024

Version number 7 (replaces version 6)

Trade name PARKETTKLEBSTOFF X-BOND MS-K 539

(Contd. of page 6)

Revision: 31.01.2024

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

Reportable explosives precursors

None of the ingredients is listed.

Reportable poisons

None of the ingredients is listed.

- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H317 May cause an allergic skin reaction.

H373 May cause damage to organs through prolonged or repeated exposure.

- · Contact: chemikalieninfo@murexin.com (+43 02622/27401)
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Sens. 1B: Skin sensitisation - Category 1B

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

* * Data compared to the previous version altered.