

Safety data sheet according to UK REACH

Printing date 17.07.2024

Version number 6 (replaces version 5)

Revision: 17.07.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name** **SILBERFARBE HITZEBESTÄNDIG**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Paint
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
MUREXIN GmbH
Franz v. Furtenbachstr. 1
A-2700 Wiener Neustadt
Tel.: +43 (0)2622/27401
- **Informing department:** chemikalieninfo@murexin.com
- **1.4 Emergency telephone number:**
UK National poisons Emergency number.: +44 (0) 870 600 6266

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.

Water-react. 1 H260 In contact with water releases flammable gases which may ignite spontaneously.



environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS02 GHS07 GHS09

- **Signal word** Danger
- **Hazard-determining components of labelling:**
Solvent naphtha (petroleum), light arom.
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics
- **Hazard statements**
H226 Flammable liquid and vapour.

(Contd. on page 2)

Safety data sheet according to UK REACH

Printing date 17.07.2024

Version number 6 (replaces version 5)

Revision: 17.07.2024

Trade name **SILBERFARBE HITZEBESTÄNDIG**

(Contd. of page 1)

H260 In contact with water releases flammable gases which may ignite spontaneously.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P223 Do not allow contact with water.

P260 Do not breathe mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture consisting of the following components with harmless additives.

Dangerous components:

| | | |
|--|---|---------|
| CAS: 64742-95-6 Reg.nr.: 01-2119455851-35 | Solvent naphtha (petroleum), light arom. Flam. Liq. 1, H224 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H335 STOT SE 3, H336 EUH066 | 50-100% |
| CAS: 1330-20-7 EINECS: 215-535-7 | xylene, mixed isomers, pure Consisting of: 98-82-8 isopropylbenzene (0.13%) Flam. Liq. 3, H226 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319 | 10-25% |
| CAS: 7429-90-5 EINECS: 231-072-3 Reg.nr.: 01-2119529243-45 | aluminium powder (stabilised) Flam. Sol. 1, H228 | 10-25% |
| EC number: 927-241-2 Reg.nr.: 01-2119471843-32 | Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 3, H412 EUH066 | 2.5-5% |
| CAS: 162303-51-7 NLP: 500-687-1 | Tetra-n-butyltitanat, Polymer mit Wasser Flam. Liq. 3, H226 Eye Irrit. 2, H319 | 1-2.5% |

GB

(Contd. on page 3)

Safety data sheet according to UK REACH

Printing date 17.07.2024

Version number 6 (replaces version 5)

Revision: 17.07.2024

Trade name **SILBERFARBE HITZEBESTÄNDIG**

(Contd. of page 2)

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information** Instantly remove any clothing soiled by the product.
- **After inhalation** In case of unconsciousness bring patient into stable side position for transport.
- **After skin contact**
Instantly wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
- **After eye contact** Rinse opened eye for several minutes under running water. Then consult doctor.
- **After swallowing**
Call a doctor immediately.
A person vomiting while lying on their back should be turned onto their side.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents**
Extinguishing powder. Do not use water.
CO2. Do not use water.
Sand. Do not use water.
Special powder for metal fires. Do not use water.
CO2, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents** Water with a full water jet.
- **5.2 Special hazards arising from the substance or mixture**
Formation of poisonous gases during heating or in fires.
- **5.3 Advice for firefighters**
- **Protective equipment:** Put on breathing apparatus.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Keep away from ignition sources
Ensure adequate ventilation
Put on breathing apparatus.
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or water bodies.
Prevent material from reaching sewage system, holes and cellars.
Inform respective authorities in case product reaches water or sewage system.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

GB

(Contd. on page 4)

Safety data sheet according to UK REACH

Printing date 17.07.2024

Version number 6 (replaces version 5)

Revision: 17.07.2024

Trade name **SILBERFARBE HITZEBESTÄNDIG**

(Contd. of page 3)

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep containers tightly sealed.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep breathing equipment ready.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and containers: Store only in the original container.

Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions:

Protect from frost.
Store in cool, dry conditions in well sealed containers.

Storage class 4.3

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with critical values that require monitoring at the workplace:

1330-20-7 xylene, mixed isomers, pure

| | |
|-----|--|
| WEL | Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV |
|-----|--|

Ingredients with biological limit values:

1330-20-7 xylene, mixed isomers, pure

| | |
|------|--|
| BMGV | 650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid |
|------|--|

Additional information: The lists that were valid during the compilation were used as basis.

8.2 Exposure controls

Appropriate engineering controls No further data; see section 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures

Do not eat, drink or smoke while working.
The usual precautionary measures should be adhered to in handling the chemicals.
Keep away from foodstuffs, beverages and food.
Instantly remove any soiled and impregnated garments.
Wash hands during breaks and at the end of the work.
Store protective clothing separately.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.

Hand protection

DIN EN 374
Protective gloves.

(Contd. on page 5)

Safety data sheet according to UK REACH

Printing date 17.07.2024

Version number 6 (replaces version 5)

Revision: 17.07.2024

Trade name **SILBERFARBE HITZEBESTÄNDIG**

(Contd. of page 4)

- **Material of gloves**
Nitrile rubber, NBR
Butyl rubber, BR
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye/face protection** Safety glasses
- **Body protection:** Protective work clothing.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

- | | |
|--|----------------------------------|
| · Colour: | Silver-coloured |
| · Smell: | Characteristic |
| · Lower and upper explosion limit | |
| · Lower: | 0.7 Vol % |
| · Upper: | 7 Vol % |
| · Flash point: | 36 °C |
| · Auto-ignition temperature: | >230 °C |
| · pH | Not determined. |
| · Solubility | |
| · Water: | Not miscible or difficult to mix |
| · Steam pressure at 20 °C: | 10 hPa |
| · Density and/or relative density | |
| · Density at 20 °C | 1 g/cm ³ |

· 9.2 Other information

- | | |
|--|---|
| · Appearance: | |
| · Form: | Fluid |
| · Important information on protection of health and environment, and on safety. | |
| · Self-inflammability: | Product is not selfigniting. |
| · Explosive properties: | Product is not explosive. However, formation of explosive air/steam mixtures is possible. |

· Information with regard to physical hazard classes

- | | |
|--|--|
| · Explosives | Void |
| · Flammable gases | Void |
| · Aerosols | Void |
| · Oxidising gases | Void |
| · Gases under pressure | Void |
| · Flammable liquids | Flammable liquid and vapour. |
| · Flammable solids | Void |
| · Self-reactive substances and mixtures | Void |
| · Pyrophoric liquids | Void |
| · Pyrophoric solids | Void |
| · Self-heating substances and mixtures | Void |
| · Substances and mixtures, which emit flammable gases in contact with water | In contact with water releases flammable gases which may ignite spontaneously. |
| · Oxidising liquids | |
| · Oxidising solids | Void |
| · Organic peroxides | Void |
| · Corrosive to metals | Void |

(Contd. on page 6)

GB

Safety data sheet according to UK REACH

Printing date 17.07.2024

Version number 6 (replaces version 5)

Revision: 17.07.2024

Trade name **SILBERFARBE HITZEBESTÄNDIG**

(Contd. of page 5)

· **Desensitised explosives**

Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Contact with water releases flammable gases
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** None

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values that are relevant for classification:**

1330-20-7 xylene, mixed isomers, pure

| | | |
|------------|----------|----------------------|
| Oral | LD50 | 8,700 mg/kg (rat) |
| Dermal | LD50 | 2,000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | 6,350 mg/l (rat) |

- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause respiratory irritation.
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Remark:** Toxic for fish

(Contd. on page 7)

GB

Safety data sheet according to UK REACH

Printing date 17.07.2024

Version number 6 (replaces version 5)

Revision: 17.07.2024

Trade name **SILBERFARBE HITZEBESTÄNDIG**

(Contd. of page 6)

· **Additional ecological information:**

· **General notes:**

Toxic for aquatic organisms

Also poisonous for fish and plankton in water bodies.

Water hazard class (Germany) 2 (Self-assessment): hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

· **14.1 UN number or ID number**

· **ADR, IMDG, IATA**

UN1263

· **14.2 UN proper shipping name**

· **ADR**

1263 PAINT, ENVIRONMENTALLY HAZARDOUS

· **IMDG**

PAINT, MARINE POLLUTANT

· **IATA**

PAINT

· **14.3 Transport hazard class(es)**

· **ADR, IMDG**



· **Class**

3 Flammable liquids.

· **Label**

3

· **IATA**



· **Class**

3 Flammable liquids.

· **Label**

3

· **14.4 Packing group**

· **ADR, IMDG, IATA**

III

· **14.5 Environmental hazards:**

Product contains environmentally hazardous substances: Solvent naphtha (petroleum), light arom.

· **Marine pollutant:**

Yes

· **Special marking (ADR):**

Symbol (fish and tree)

Symbol (fish and tree)

· **14.6 Special precautions for user**

Warning: Flammable liquids.

· **Kemler Number:**

39

(Contd. on page 8)

Safety data sheet according to UK REACH

Printing date 17.07.2024

Version number 6 (replaces version 5)

Revision: 17.07.2024

Trade name **SILBERFARBE HITZEBESTÄNDIG**

(Contd. of page 7)

| | |
|---|--|
| · EMS Number: | <u>F-E, S-E</u> |
| · Stowage Category | A |
| · 14.7 Maritime transport in bulk according to IMO instruments | Not applicable. |
| · Transport/Additional information: | |
| · ADR | |
| · Limited quantities (LQ) | 5L |
| · Transport category | 3 |
| · Tunnel restriction code | D/E |
| · UN "Model Regulation": | UN 1263 PAINT, 3, III, ENVIRONMENTALLY HAZARDOUS |

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Poisons Act**

· **Regulated explosives precursors**

None of the ingredients is listed.

· **Regulated poisons**

None of the ingredients is listed.

· **Reportable explosives precursors**

None of the ingredients is listed.

· **Reportable poisons**

None of the ingredients is listed.

· **Directive 2012/18/EU**

- **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category**

O2 Substances and mixtures which in contact with water emit flammable gases

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 100 t

- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H224 Extremely flammable liquid and vapour.

H226 Flammable liquid and vapour.

H228 Flammable solid.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

(Contd. on page 9)

Safety data sheet according to UK REACH

Printing date 17.07.2024

Version number 6 (replaces version 5)

Revision: 17.07.2024

Trade name SILBERFARBE HITZEBESTÄNDIG

(Contd. of page 8)

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

· **Contact:** chemikalieninfo@murexin.com (+43 02622/27401)

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 1: Flammable liquids – Category 1

Flam. Liq. 3: Flammable liquids – Category 3

Flam. Sol. 1: Flammable solids – Category 1

Water-react. 1: Substances and mixtures which in contact with water emit flammable gases – Category 1

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· *** Data compared to the previous version altered.**

GB