Revision: 19.06.2023

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.06.2023

Version number 13 (replaces version 12)

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name UNIVERSALGRUNDIERUNG LV 45
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Priming
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MUREXIN GmbH

Franz v. Furtenbachstr. 1 A-2700 Wiener Neustadt Tel.: +43 (0)2622/27401

- · Informing department: chemikalieninfo@murexin.com
- · 1.4 Emergency telephone number:

UK National poisons Emergency number.: +44 (0) 870 600 6266

### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- Hazard-determining components of labelling:

propan-2-ol ethyl acetate

· Hazard statements

H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

(Contd. on page 2)

Printing date 19.06.2023 Version number 13 (replaces version 12) Revision: 19.06.2023

#### Trade name UNIVERSALGRUNDIERUNG LV 45

(Contd. of page 1)

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

- 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- Description: Mixture consisting of the following components with harmless additives.

· Dangerous components:		
CAS: 67-63-0	propan-2-ol	50-100%
EINECS: 200-661-7	Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	
CAS: 141-78-6	ethyl acetate	25-50%
EINECS: 205-500-4	♠ Flam. Liq. 2, H225	
Reg.nr.: 2119475103-46 01-2119475103	Eye Irrit. 2, H319; STOT SE 3, H336	
46-xxxx	5-EUNU00	
70-2222		
CAS: 64-17-5	ethanol	2.5-5%
EINECS: 200-578-6	♦ Flam. Liq. 2, H225	

## SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information Instantly remove any clothing soiled by the product.
- · After skin contact

Instantly wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

- · After eye contact Rinse opened eye for several minutes under running water. Then consult doctor.
- · After swallowing In case of persistent symptoms consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

## SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

- · For safety reasons unsuitable extinguishing agents Water with a full water jet.
- 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

(Contd. on page 3)

Printing date 19.06.2023 Version number 13 (replaces version 12) Revision: 19.06.2023

#### Trade name UNIVERSALGRUNDIERUNG LV 45

(Contd. of page 2)

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

#### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources

Wear protective equipment. Keep unprotected persons away.

Wear protective clothing.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or water bodies.

Prevent material from reaching sewage system, holes and cellars.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

## SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Keep containers tightly sealed.
- · Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- · Requirements to be met by storerooms and containers:

Store in cool location.

Store only in the original container.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed containers.

- · Storage class 3
- · 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with critical values that require monitoring at the workplace	· Components with o	critical values th	hat require mo	nitoring at th	e workplace:
--	---------------------	--------------------	----------------	----------------	--------------

#### 67-63-0 propan-2-ol

WEL Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm

### 141-78-6 ethyl acetate

WEL Short-term value: 1468 mg/m³, 400 ppm Long-term value: 734 mg/m³, 200 ppm

### 64-17-5 ethanol

WEL Long-term value: 1920 mg/m³, 1000 ppm

· Additional information: The lists that were valid during the compilation were used as basis.

(Contd. on page 4)

Printing date 19.06.2023 Version number 13 (replaces version 12) Revision: 19.06.2023

#### Trade name UNIVERSALGRUNDIERUNG LV 45

(Contd. of page 3)

- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures

The usual precautionary measures should be adhered to in handling the chemicals.

Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

- · Breathing equipment: Not required.
- · Hand protection

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

Use gloves of stable material (e.g. Nitrile) - if necessary tricoted to improve the wearability.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye/face protection Tightly sealed safety glasses.
- · Body protection: Protective work clothing.

## SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information

Physical state
Colour:
Smell:
Odour threshold:
Melting point/freezing point:

Fluid

Colourless
Solvent-like
Not determined

Not determined

Boiling point or initial boiling point and

boiling range 70-78 °C (141-78-6 ethyl acetate)

· Flammability Highly flammable.

Lower and upper explosion limit

Lower: 2 Vol %
Upper: 12 Vol %
Flash point: 6 °C
Auto-ignition temperature: 425 °C

Decomposition temperature: Not determined.

· pH at 20 °C 6.4

· Viscosity:

• Kinematic viscosity Not determined. • dynamic: Not determined.

Solubility

· Water: Not miscible or difficult to mix

· Partition coefficient n-octanol/water (log

value)
Not determined.
Steam pressure at 20 °C:
100 hPa

Density and/or relative density

Density at 20 °C
 Relative density
 Vapour density
 Not determined.
 Not determined.

(Contd. on page 5)

Printing date 19.06.2023 Version number 13 (replaces version 12) Revision: 19.06.2023

#### Trade name UNIVERSALGRUNDIERUNG LV 45

(Contd. of page 4)

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health

and environment, and on safety.

· Self-inflammability: Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of

explosive air/steam mixtures is possible.

· Change in condition

· Evaporation rate Not determined.

Information with regard to physical hazard

classes

· Explosives
· Flammable gases
· Aerosols
· Oxidising gases
· Gases under pressure

Void

Void
Void

Flammable liquids Highly flammable liquid and vapour.

Flammable solids
Self-reactive substances and mixtures
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures, which emit

Substances and mixtures, which emit flammable gases in contact with water Void Oxidising liquids Void Oxidising solids Void Organic peroxides Void Corrosive to metals Void Desensitised explosives

# SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: None

## **SECTION 11: Toxicological information**

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity

· LD/LC50	· LD/LC50 values that are relevant for classification:		
67-63-0 p	67-63-0 propan-2-ol		
Oral	LD50	4,570 mg/kg (rat)	
Dermal	LD50	13,400 mg/kg (rab)	
Inhalative	LC50/4 h	30 mg/l (rat)	
141-78-6	141-78-6 ethyl acetate		
Oral	LD50	5,600 mg/kg (rat)	

(Contd. on page 6)

Printing date 19.06.2023 Version number 13 (replaces version 12) Revision: 19.06.2023

#### Trade name UNIVERSALGRUNDIERUNG LV 45

			(Contd. of page 5)
D	ermal	LD50	18,000 mg/kg (rabbit)
64-17-5 ethanol			
0	ral	LD50	7,060 mg/kg (rat)
In	nhalative	LC50/4 h	20,000 mg/l (rat)

- · Serious eye damage/irritation Causes serious eye irritation.
- · STOT-single exposure May cause drowsiness or dizziness.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

78-93-3 butanone

List II

## SECTION 12: Ecological information

· 12.1 Toxicity

	uatic toxicity:			
· Aquati				
141-78	141-78-6 ethyl acetate			
EC 50	3,300 mg/l (Pseudokirchneriella subcapitata)			
	717 mg/l (G)			
LC50	230 mg/l (F2)			

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB:** Not applicable.
- · 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class (Germany) 1 (Self-assessment): slightly hazardous for water.

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

## SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

## **SECTION 14: Transport information**

- · 14.1 UN number or ID number
- · ADR, IMDG, IATA UN1993

(Contd. on page 7)

Printing date 19.06.2023 Version number 13 (replaces version 12) Revision: 19.06.2023

## Trade name UNIVERSALGRUNDIERUNG LV 45

	(Contd. of page
14.2 UN proper shipping name ADR	1993 FLAMMABLE LIQUID, N.O.S
AUN	(ISOPROPANOL (ISOPROPYL ALCOHOL ETHYL ACETATE)
IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (ISOPROPANC (ISOPROPYL ALCOHOL), ETHYL ACETATE)
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group ADR, IMDG, IATA	II
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Kemler Number:	33
EMS Number: Stowage Category	F-E, <u>S-E</u> B
14.7 Maritime transport in bulk accord	
IMO instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Transport category	2
Tunnel restriction code	D/E
UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S (ISOPROPANOL (ISOPROPYL ALCOHOL ETHYL ACETATE), 3, II

## SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 8)

Printing date 19.06.2023 Version number 13 (replaces version 12) Revision: 19.06.2023

### Trade name UNIVERSALGRUNDIERUNG LV 45

(Contd. of page 7)

### · Relevant phrases

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Contact: chemikalieninfo@murexin.com (+43 02622/27401)

#### · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

\* Data compared to the previous version altered.

GB