

Tile laying technology

EPOXY JOINT CLEANER ERY 92



Product description

Solvent-based, acidic cleaner.

Cleaning agent for removal of epoxy resin veils which can occur when working with grouts on ceramic tiles or glass mosaics based on reaction resin. Also suitable for acid-resistant (as well as rough) natural stones.

Delivery format

Container	Outer packaging	Pallet
1 L / KFL	10	400 KFL

Storage

Can be stored frost-free, cool, and dry on wooden shelves in the unopened original container for 730 days

Processing

Processing

Wear gloves during the processing! Apply to the dry substrate with a roller or brush and depending on contamination and full hardening, allow to work for up to 2 hours (at 20 °C). Then, if required, apply water with a sponge or soft pad and brush through. Immediately rewash with plenty of water!

Attention: always test suitability and effect beforehand on a sample area. Use on acid-resistant substrates only. Surfaces which are sensitive to acids could be irreparably damaged!

Materials which are sensitive to solvents (wood, lacquered surfaces etc.) must be protected through suitable measures (e.g. masking). Excessive working time can impair the joint colour, make the joint soft or destroy the joint. For this reason, occasionally test the joint strength before expiry of the recommended working time. Allow joints which have become too soft, to harden for a longer period of time (days) and protect from mechanical loads during this period.

42037, EPOXY JOINT CLEANER ERY 92, valid from: 14.12.2023, Magdalena Riegler, Page 1

Technical data

Density	approx. 1.1 g/cm ³
pH value	approx. 2.5
Colour	transparent
Processing temperature	+10°C bis +30°C
Range	approx. 15 m ² /l (for glazed tiles)

Substrate

Suitable substrates

Concrete
Cement screed
Anhydrite screed
Mastic asphalt
Plaster
Lime-cement plaster
Masonry
Gypsum plasterboards
Smooth concrete
Aerated concrete
Wooden substrates

The substrate must be dry, frost-free, solid, weight-bearing, dimensionally stable, free of dust, dirt, oil, grease, release agents and loose parts, and it must comply with the applicable technical national and European directives, standards and "generally accepted rules of the trade".

Product and processing instructions

Material information:

- When working outside the ideal temperature and/or humidity range, the material properties may change significantly.
- Temper materials accordingly before processing!
- To retain the product properties, no foreign materials may be mixed in!
- Water dosing amounts or thinning specifications must be precisely kept!
- Check coloured products before use for colour accuracy!
- Colour consistency can only be guaranteed within a batch.
- The colouring is significantly influenced by the environmental conditions.

Environmental information:

- Do not process at temperatures below + 5 °C!
- The ideal temperature range for material, substrate and air is +15 °C to +25 °C.
- The ideal relative air humidity range is between 40% to 60%.
- Increased humidity and/or lower temperatures delay, lower air humidity and/or higher temperatures accelerate drying, setting and hardening.
- Ensure sufficient ventilation during the drying, reaction and hardening phase; avoid draughts!
- Protect from direct sunlight, wind and weather!
- Protect adjacent components!

Tips:

- We recommend using a test surface first or a small area for initial, small-scale testing.
- Observe the product data sheets of all MUREXIN products used in the system.
- Keep a genuine original container of the respective batch for later repair work.

The information provided reflects average values that were obtained under laboratory conditions. Due to the use of natural raw materials, the indicated values of individual deliveries may vary slightly without impacting the product suitability.

Safety instructions

This leaflet is based on extensive experience, is intended to convey the best of our knowledge, is not legally binding and does neither constitute a contractual legal relationship nor a subsidiary obligation resulting from the bill of sale. The quality of our materials is guaranteed within the framework of our general terms and conditions. Our products may be used by professionals and/or experienced and accordingly technically skilled persons only. Users are not released from inquiring in case of uncertainties or from rendering professional workmanship. We recommend using a test surface first or a small area for initial, small-scale testing. Naturally, it is not possible to describe or foresee all possible current and future uses and peculiarities. Information that is assumed to be familiar to experts has been omitted.

Please observe the current, technical, national and European standards, guidelines and data sheets regarding materials, substrates and the subsequent construction. Please contact us if you have any reservations or doubt.

This version is rendered invalid if a new version is released. The most recent data sheets, safety data sheets and the terms and conditions are available online at www.murexin.com.