

UNIFLEX PROFESSIONAL TILE MAGNETS



- > holds cover plates of up to 10 kg
- > easy installation
- > invisibly covers installation access points

Product description

Magnet holder for invisible covering of installation access points.

For invisible covering of installation access points like stop cocks, soot doors etc. For all tile formats and wall openings up to 60 x 60 cm, also for marble tile. The magnets hold covering weights of up to 10 kg.

Delivery format

Container	Outer packaging	Pallet
25 STK / STK	25	3250 STK

Storage

Can be stored frost-free, cool, and dry on wooden shelves in the unopened original container for 0 days

Processing

Processing

Place the holding parts in fresh mortar bed or put them between masonry and boards.

Holder tongues are to be attached variably according to the joints up to 10 mm and the magnets set accordingly. Precisely position metal plates on the rear of the cover plate with contact adhesive. Insert seal and close with Murexin sanitary silicone. For multiple tiles, glue a tile on the rear or use MUREXIN Uniflex Classic tiling door.

The cover can now be easily opened with the suction cups supplied.

Technical data

Max. sustainable weight	10 kg
Max. opening	600 x 600 mm
Warranty	5 years

Substrate

Suitable substrates

Concrete
Cement screed, Anhydrite screed
Mastic asphalt
Plaster, Lime-cement plaster
Masonry
Gypsum plasterboards
Smooth concrete, Aerated concrete
Wooden substrates

The substrate must be dry, frost-free, solid, weight-bearing, dimensionally stable, free of dust, dirt, oil, grease, release agents and loose parts, and it must comply with the applicable technical national and European directives, standards and "generally accepted rules of the trade".

Product and processing instructions

Material information:

- When working outside the ideal temperature and/or humidity range, the material properties may change significantly.
- Temper materials accordingly before processing!
- To retain the product properties, no foreign materials may be mixed in!
- Water dosing amounts or thinning specifications must be precisely kept!
- Check coloured products before use for colour accuracy!
- Colour consistency can only be guaranteed within a batch.
- The colouring is significantly influenced by the environmental conditions.

Environmental information:

- Do not process at temperatures below + 5 °C!
- The ideal temperature range for material, substrate and air is +15 °C to +25 °C.
- The ideal relative air humidity range is between 40% to 60%.
- Increased humidity and/or lower temperatures delay, lower air humidity and/or higher temperatures accelerate drying, setting and hardening.
- Ensure sufficient ventilation during the drying, reaction and hardening phase; avoid draughts!
- Protect from direct sunlight, wind and weather!
- Protect adjacent components!

Tips:

- We recommend using a test surface first or a small area for initial, small-scale testing.
- Observe the product data sheets of all MUREXIN products used in the system.
- Keep a genuine original container of the respective batch for later repair work.

The information provided reflects average values that were obtained under laboratory conditions. Due to the use of natural raw materials, the indicated values of individual deliveries may vary slightly without impacting the product suitability.

Safety instructions

This leaflet is based on extensive experience, is intended to convey the best of our knowledge, is not legally binding and does neither constitute a contractual legal relationship nor a subsidiary obligation resulting from the bill of sale. The quality of our materials is guaranteed within the framework of our general terms and conditions. Our products may be used by professionals and/or experienced and accordingly technically skilled persons only. Users are not released from inquiring in case of uncertainties or from rendering professional workmanship. We recommend using a test surface first or a small area for initial, small-scale testing. Naturally, it is not possible to describe or foresee all possible current and future uses and peculiarities. Information that is assumed to be familiar to experts has been omitted.

Please observe the current, technical, national and European standards, guidelines and data sheets regarding materials, substrates and the subsequent construction. Please contact us if you have any reservations or doubt.

This version is rendered invalid if a new version is released. The most recent data sheets, safety data sheets and the terms and conditions are available online at www.murexin.com.