

## ROUND EDGE END PROFILE



- > elegant finish
- > many design variants
- > protects tile edges

### Product description

Round edge end profile in many design variants for a clean, elegant finish of tile edges. Do not use brass variants in wet rooms. Along with offering an elegant finish for tile edges, the product also serves to protect them and can be used as a decorative transition between different covering types (e.g. tiles to carpet) or for bordering covering materials like carpet, parquet and laminate.

### Delivery format

Container	Outer packaging	Pallet
3 M / STK	-	200 STK
3 M / STK	-	310 STK
3 M / STK	-	320 STK
3 M / STK	-	400 STK
3 M / STK	-	500 STK
3 M / STK	-	550 STK
3 M / STK	-	560 STK
3 M / STK	-	600 STK
3 M / STK	-	700 STK

### Storage

Can be stored frost-free, cool, and dry on wooden shelves in the unopened original container for unlimited days

### Processing

#### Processing

Very simple to use thanks to the Murexin hole pattern: apply the adhesive mortar with the toothed trowel. Push in the round edge end profile into the mortar bed with the moulded arm and align it. Then fill fully with adhesive. The subsequently laid tiles should be flush with the edge of the rail. Round edge end profile pieces are recommended for forming corners.

After laying the tiles and hardening of the adhesive, a solid connection is created between tiles, profile and substrate.

Tile laying technology

## Technical data

Colour	Colour coated aluminium: white, grey, bahama, silver grey, manhattan, jasmine, crocus, red, blue, yellow, black; PVC round edge end rails: white, silver grey, jasmine
Brass, naturally anodised aluminium	Profile height: 6 mm, 8 mm, 10 mm, 12.5 mm
Stainless steel	Profile height: 6 mm, 8 mm, 10 mm, 12.5 mm, 15 mm
Naturally anodised aluminium	Profile height: 6 mm, 8 mm, 10 mm, 12.5 mm
Aluminium high gloss silver anodised and aluminium colour coated	Profile height: 6 mm, 8 mm, 10 mm, 12.5 mm
PVC round edge end profile	Profile height: 6 mm, 8 mm, 10 mm

## Test certificates

**Tested in accordance with (standard, classification ...)**

Aluminiumchromatierung gemäß DIN 50939

Passivieren von galvanischen Zink- und Kadmiumüberzügen gemäß ON C 2520

Eloxierung gemäß ON C 2531 und DIN EN 12373-1

## Substrate

### Suitable substrates

Concrete  
Cement screed  
Anhydrite screed  
Mastic asphalt  
Plaster  
Lime-cement plaster  
Masonry Gypsum plasterboards  
Smooth concrete  
Aerated concrete  
Wooden substrates

The substrate must be dry, frost-free, solid, weight-bearing, dimensionally stable, free of dust, dirt, oil, grease, release agents, and loose parts, and it must comply with the applicable technical national and European directives, standards, and "generally accepted rules of the trade".

## For a perfect system

### Description

Murexin end pieces for round edge end profile for elegant formation of external corners.

44005, ROUND EDGE END PROFILE, valid from: 18.12.2023, Magdalena Riegler, Page 2

## Product and processing instructions

### Material information:

- When working outside the ideal temperature and/or humidity range, the material properties may change significantly.
- Bring materials up to temperature accordingly before processing!
- To retain the product properties, no foreign materials may be mixed in!
- Water dosing amounts or dilution specifications must be precisely kept!
- Check coloured products before use for colour accuracy!
- Colour consistency can only be guaranteed within a batch.
- Environmental conditions significantly influence colouring.

### Environmental information:

- Do not process at temperatures below 5 °C!
- The ideal temperature range for material, substrate, and air is +15 °C to +25 °C.
- The ideal relative air humidity range is between 40% to 60%.
- Increased humidity and/or lower temperatures delay, lower air humidity and/or higher temperatures accelerate drying, setting, and hardening.
- Ensure sufficient ventilation during the drying, reaction, and hardening phase; avoid draughts!
- Protect from direct sunlight, wind, and weather!
- Protect adjacent components!

### Tips:

- We highly recommend using a test surface first or a small area for initial small-scale testing.
- Observe the product data sheets of all MUREXIN products used in the system.
- Keep a genuine original container of the respective batch for later repair work.

The information provided reflects average values obtained under laboratory conditions. Due to the use of natural raw materials, the indicated values of individual deliveries may vary slightly without impacting the product suitability.

## Safety instructions

This leaflet is based on extensive experience, is intended to convey the best of our knowledge, is not legally binding and does neither constitute a contractual legal relationship nor a subsidiary obligation resulting from the bill of sale. The quality of our materials is guaranteed within the framework of our general terms and conditions. Our products may be used by professionals and/or experienced and accordingly technically skilled persons only. Users are not released from inquiring in case of uncertainties or from rendering professional workmanship. We recommend using a test surface first or a small area for initial, small-scale testing. Naturally, it is not possible to describe or foresee all possible current and future uses and peculiarities. Information that is assumed to be familiar to experts has been omitted.

Please observe the current, technical, national and European standards, guidelines and data sheets regarding materials, substrates and the subsequent construction. Please contact us if you have any reservations or doubt.

This version is rendered invalid if a new version is released. The most recent data sheets, safety data sheets and the terms and conditions are available online at [www.murexin.com](http://www.murexin.com).