

UNIVERSALFIXIERUNG WL 720



Product description

Solvent-free, easy to process, rollable fixing.

Indoor use only for full area fixing of CV, PVC and textile coverings with smooth foam backings and selfplacing carpets tiles. Floor coverings can be fixed and are easy to remove again. Suitable for underfloor heating systems and castor wheel loads.

Delivery format

Container	Outer packaging	Pallet
25 KG / KE	-	12 KE
5 KG / KE	-	85 KE
2.8 KG / KE	-	100 KE

Storage

Can be stored frost-free, cool, and dry on wooden shelves in the unopened original container for 365 days

Processing

Recommended tools

Microfibre roller, brush.

Processing

Lay out the floor covering to be installed in the room, roughly cut to size and cut the seams, if necessary. Fold back half of the covering, then evenly and fully apply the fixing on the substrate using a microfibre roller. Use a small roller or brushes in corners and wall areas. As soon as the fixing has dried up transparently, the covering can be installed and rubbed over the entire area. Coat removal: To remove the coat, start to slowly release it from the edge area. To restore the original laying surface, soften any present covering residue and the remainder of the fixing material with warm water (add a little detergent) and wash off after approx. 15 minutes. Repeat cleaning process if necessary. Before relaying, ensure that the substrate has dried sufficiently!

Technical data

Colour	yellowish white
Consumption	approx. 100 - 150 g/m ² , depending on substrate and back of the covering
Flash-off time	approx. 20 - 60 min.
Spezifisches Gewicht	1,1 g/cm ³

Test certificates

Tested in accordance with (standard, classification ...)

DIBt

Substrate

Suitable substrates

absorbent, smoothed substrates

The substrate must be dry, frost-free, solid, weight-bearing, dimensionally stable, free of dust, dirt, oil, grease, release agents and loose parts and it must comply with the applicable technical national and European directives, standards and "generally accepted rules of the trade".

Product and processing instructions

Material instructions:

- When working outside the ideal temperature and/or humidity range the material properties may change significantly.
- Bring materials to correct temperature before processing!
- To retain the product properties, no foreign materials may be mixed in!
- Water addition amounts or dilution instructions may be precisely kept!
- Check coloured products before use for colour accuracy!
- Colour consistency can only be guaranteed within a batch.
- The colouring is significantly influenced by the environmental conditions.

Environmental advice:

- Do not process at temperatures below +15 °C!
- The ideal temperature range for material, substrate and air is +15 °C to +25°C.
- The ideal air relative humidity range is between 40% to 60%.
- Increased humidity and/or lower temperatures delay, lower air humidity and/or higher temperatures accelerate drying, setting and hardening.
- Ensure sufficient ventilation during the drying, reaction and hardening phase; avoid draughts!
- Protect from direct sunlight, wind and weather!
- Protect adjacent components!

Tips:

- We highly recommend using a test surface first or a small area for initial, small-scale testing.
- Observe the product data sheets of all MUREXIN products used in the system.
- Keep a genuine original container of the respective batch for later repair work.

The information provided reflects average values that were obtained under laboratory conditions. Due to the use of natural raw materials, the indicated values of individual deliveries may vary slightly without impacting the product suitability.

Safety instructions

This leaflet is based on extensive experience, is intended to convey the best of our knowledge, is not legally binding and does neither constitute a contractual legal relationship nor a subsidiary obligation resulting from the bill of sale. The quality of our materials is guaranteed within the framework of our general terms and conditions. Our products may be used by professionals and/or experienced and accordingly technically skilled persons only. Users are not released from inquiring in case of uncertainties or from rendering professional workmanship. We recommend using a test surface first or a small area for initial, small-scale testing. Naturally, it is not possible to describe or foresee all possible current and future uses and peculiarities. Information that is assumed to be familiar to experts has been omitted.

Please observe the current, technical, national and European standards, guidelines and data sheets regarding materials, substrates and the subsequent construction. Please contact us if you have any reservations or doubt.

This version is rendered invalid if a new version is released. The most recent data sheets, safety data sheets and the terms and conditions are available online at www.murexin.com.