

## FIXING DISPERSION WL 730



- > high-quality fixing
- > economical to use
- > high re-saturation capability



### Product description

High-quality fixing dispersion with high re-saturation capability. Indoor use only for fixing self-laying carpet tiles with fleece, PVC or PUR backings, as well as complete fixing of CV, PVC and textile coverings with smooth foam backings. Floor coverings can be fixed repeatedly and are easy to remove again. Suitable for underfloor heating systems and castor wheel loads.

#### Delivery format

Container	Outer packaging	Pallet
10 KG / KE	-	36 KE

#### Storage

Can be stored frost-free, cool, and dry on wooden shelves in the unopened original container for 365 days

### Processing

#### Recommended tools

Microfibre roller, brush.

#### Processing

Lay out the floor covering to be installed in the room, roughly cut to size and cut the seams, if necessary. Fold back half of the covering, then evenly and fully apply the fixing on the substrate using a microfibre roller. Use a small roller or brushes in corners and wall areas. As soon as the fixing has dried up transparently, the covering can be installed and rubbed over the entire area.

### Technical data

Colour	yellowish white
Consumption	approx. 100 - 150 g/m <sup>2</sup> , depending on substrate and back of the covering.
Flash-off time	approx. 20 - 60 min
Specific weight	1,0 g/cm <sup>3</sup>

63075, FIXING DISPERSION WL 730, valid from: 27.11.2023, Magdalena Riegler, Page 1

## Test certificates

### Tested in accordance with (standard, classification ...)

DIBt-Grundsätzen

## Substrate

### Suitable substrates

Absorbent, plastered substrates, double and cavity floors, chipboard and non-absorbent substrates, e.g. existing coverings.

The substrate must be dry, frost-free, solid, weight-bearing, dimensionally stable, free of dust, dirt, oil, grease, release agents and loose parts and it must comply with the applicable technical national and European directives, standards and "generally accepted rules of the trade".

## Product and processing instructions

### Material information:

- When working outside the ideal temperature and/or humidity range, the material properties may change significantly.
- Temper materials accordingly before processing!
- To retain the product properties, no foreign materials may be mixed in!
- Water dosing amounts or thinning specifications must be precisely kept!
- Check coloured products before use for colour accuracy!
- Colour consistency can only be guaranteed within a batch.
- The colouring is significantly influenced by the environmental conditions.

### Environmental advice:

- Do not process at temperatures below +15 °C!
- The ideal temperature range for material, substrate, and air is +15 °C to +25°C.
- The ideal air humidity range is between 40% to 60%.
- Increased humidity and/or lower temperatures delay, lower air humidity and/or higher temperatures accelerate drying, setting, and hardening.
- Ensure sufficient ventilation during the drying, reaction, and hardening phase; avoid draughts!
- Protect from direct sunlight, wind, and weather!
- Protect adjacent components!

### Tips:

- We recommend using a test surface first or a small area for initial, small-scale testing.
- Observe the product data sheets of all MUREXIN products used in the system.
- Keep a genuine original container of the respective batch for later repair work.

The information provided reflects average values that were obtained under laboratory conditions. Due to the use of natural raw materials, the indicated values of individual deliveries may vary slightly without impacting the product suitability.

## Safety instructions

This leaflet is based on extensive experience, is intended to convey the best of our knowledge, is not legally binding and does neither constitute a contractual legal relationship nor a subsidiary obligation resulting from the bill of sale. The quality of our materials is guaranteed within the framework of our general terms and conditions. Our products may be used by professionals and/or experienced and accordingly technically skilled persons only. Users are not released from inquiring in case of uncertainties or from rendering professional workmanship. We recommend using a test surface first or a small area for initial, small-scale testing. Naturally, it is not possible to describe or foresee all possible current and future uses and peculiarities. Information that is assumed to be familiar to experts has been omitted.

Please observe the current, technical, national and European standards, guidelines and data sheets regarding materials, substrates and the subsequent construction. Please contact us if you have any reservations or doubt.

This version is rendered invalid if a new version is released. The most recent data sheets, safety data sheets and the terms and conditions are available online at [www.murexin.com](http://www.murexin.com).