

ADHESIVE FOR GLASS FABRIC D 910



Product description

Solvent-free, ready-to-use, odourless, high-quality dispersion adhesive with very good adhesive strength.

Only indoors on wall areas for adhesion of all sorts of textile wallpapers (fabric or warp thread) with paper backings and glass fabric wallpapers.

Delivery format

Container	Outer packaging	Pallet
15 KG / KE	-	24 KE
6 KG / KE	-	85 KE

Storage

Can be stored frost-free, cool, and dry on wooden shelves in the unopened original container for 365 days

Processing

Recommended tools

Notched trowel A1, roller

Processing

1.) FABRIC WALLPAPERS:

Apply the adhesive directly to the wall with a notched trowel or roller. Do not cover too large wall areas, so that the adhesive does not dry out. Lay the membranes vertically in the fresh adhesive bed on the wall or ceiling, press down firmly and roll with a rubber roller first in the middle from top to bottom, then to the sides without bubbles. Then again carefully roll the membranes in the seam area with a narrow rubber roller.

2.) WARP THREAD WALLPAPER:

Variety A: cover the cut membranes fully and evenly with the adhesive. Do not fold the wallpaper, allow the adhesive to work briefly on the treated tracks and stick together. Pressing and rolling

then takes place analogous to the processing of fabric carpets. Variety B: evenly moisten the rear of the wallpaper with a mop soaked in water, briefly let it relax and proceed as with the processing of fabric carpets - adhesive application to walls etc.

Technical data

Consumption	approx. 250 - 350 g/m ² depending on the substrate and covering type
Flash-off time	none
Working time	approx. 10 - 20 min.
Final strength	after approx. 72 hrs
Processing temperature	ideally +16 °C to +22 °C
Specific weight	1,1 g/cm ³

Substrate

Suitable substrates

Suitable for all kinds of standard absorbent substrates.

No suitable directly on old coatings, wallpaper,...

The substrate must be dry, frost-free, solid, weight-bearing, dimensionally stable, free of dust, dirt, oil, grease, release agents and loose parts, and it must comply with the applicable technical national and European directives, standards and "generally accepted rules of the trade".

Removal of glue-bound distemper, multi-layer coatings and wallpaper. Oil and varnish coatings must be pretreated with lye or by sanding.

Plastering of uneven and coarse substrates: Murexin WALL SMOOTHER WG 26

Priming of heavily absorbent substrates: Murexin PRIMER D1 Murexin PLASTER PRIMER LF The covering to be glued must be adapted to the surface temperature of the substrate. Optimum surface temperature of the substrate: + 16 °C to + 22 °C

Product and processing instructions

Material information:

- When working outside the ideal temperature and/or humidity range, the material properties may change significantly.
- Temper materials accordingly before processing!
- To retain the product properties, no foreign materials may be mixed in!
- Water dosing amounts or thinning specifications must be precisely kept!
- Check coloured products before use for colour accuracy!
- Colour consistency can only be guaranteed within a batch.
- The colouring is significantly influenced by the environmental conditions.

Environmental information:

- Do not process at substrate temperatures below + 15 °C!
- The ideal temperature range for the material, substrate and air is + 15 °C to + 25 °C.
- The ideal relative air humidity range is between 40% to 60%.
- Ensure sufficient ventilation during the drying, reaction and hardening phase; avoid draughts!
- Increased humidity and/or lower temperatures delay, lower air humidity and/or higher temperatures accelerate drying, setting and hardening.
- Protect from direct sunlight, wind and weather!
- Protect adjacent components!

64010, ADHESIVE FOR GLASS FABRIC D 910, valid from: 27.11.2023, Magdalena Riegler, Page 2

Tips:

- We recommend using a test surface first or a small area for initial, small-scale testing.
- Observe the product data sheets of all MUREXIN products used in the system.
- Keep a genuine original container of the respective batch for later repair work.

The information provided reflects average values that were obtained under laboratory conditions. Due to the use of natural raw materials, the indicated values of individual deliveries may vary slightly without impacting the product suitability.

Safety instructions

This leaflet is based on extensive experience, is intended to convey the best of our knowledge, is not legally binding and does neither constitute a contractual legal relationship nor a subsidiary obligation resulting from the bill of sale. The quality of our materials is guaranteed within the framework of our general terms and conditions. Our products may be used by professionals and/or experienced and accordingly technically skilled persons only. Users are not released from inquiring in case of uncertainties or from rendering professional workmanship. We recommend using a test surface first or a small area for initial, small-scale testing. Naturally, it is not possible to describe or foresee all possible current and future uses and peculiarities. Information that is assumed to be familiar to experts has been omitted.

Please observe the current, technical, national and European standards, guidelines and data sheets regarding materials, substrates and the subsequent construction. Please contact us if you have any reservations or doubt.

This version is rendered invalid if a new version is released. The most recent data sheets, safety data sheets and the terms and conditions are available online at www.murexin.com.