

DesignCoat NP 90 Premium Oil

- > Solid content > 99%
- > high durability
- > very efficient
- > quick drying



Product description

Delivery format

Container	Outer packaging	Pallet
2.5 L / BLE	4	168 BLE

Storage

Can be stored frost-free, cool, and dry on wooden shelves in the unopened original container for 1825 days

Processing

Processing

Apply DesignCoat NP 90 Premium Oil thinly and evenly using a short-pile paint roller or similar applicator. Alternatively, the impregnating oil may be applied section by section as thinly as possible using a stainless steel trowel.

Immediately after application, the surface must be buffed. For best results, use a single-disc machine fitted with a soft pad or a lint-free cotton cloth. This removes excess material and produces a uniform finish. Once the pad no longer absorbs excess oil during buffing, continue buffing into the adjacent dry, untreated area until the pad no longer releases any oil and regains its absorbency.

Any excess oil must be worked into the wood or removed, otherwise it will cure on the wood surface.

After a drying time of 6–8 hours, the application may be repeated if required.

With pigmented oils, the colour intensity can be increased by applying an additional coat of the same pigmented oil. Stir pigmented oils thoroughly before use. To avoid colour variations, the entire quantity required should be mixed together in a separate container before application.

Maintenance:

To maintain an attractive and durable finish over the long term, we recommend regular maintenance using Murexin Aqua Parkett Vollpflege AP 20 or a natural wood floor soap.

When maintaining wood surfaces with maintenance oils containing dark-pigmented natural oils, slight colour lightening may occur.

For routine cleaning, use a well-wrung damp cloth or a suitable floor mop.

The surface may also be re-oiled with DesignCoat NP 90 Premium Oil. However, re-oiling is only recommended if no cleaning or maintenance products other than this oil have been used between oil applications.

Warning: Flammable. Risk of spontaneous combustion. Oil-soaked cloths and pads must be stored in sealed metal containers or immersed in water until disposal.

Technical data

Consumption

Consumption/coverage per l: approx. 5 - 20 m² (depending on wood and laying type)

Safety instructions

This leaflet is based on extensive experience, is intended to convey the best of our knowledge, is not legally binding and does neither constitute a contractual legal relationship nor a subsidiary obligation resulting from the bill of sale. The quality of our materials is guaranteed within the framework of our general terms and conditions. Our products may be used by professionals and/or experienced and accordingly technically skilled persons only. Users are not released from inquiring in case of uncertainties or from rendering professional workmanship. We recommend using a test surface first or a small area for initial, small-scale testing. Naturally, it is not possible to describe or foresee all possible current and future uses and peculiarities. Information that is assumed to be familiar to experts has been omitted.

Please observe the current, technical, national and European standards, guidelines and data sheets regarding materials, substrates and the subsequent construction. Please contact us if you have any reservations or doubt.

This version is rendered invalid if a new version is released. The most recent data sheets, safety data sheets and the terms and conditions are available online at www.murexin.com.